

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|--------------|--------|--|-------|
| 10000015 | - | Aluminum | 1100 | 13/32" | DIA | AMS-QQ-A-225/1 OR ASTM B211 | |
| 10000016 | - | Steel | 1095 | .096" | DIA | C1095 HI CARBON STEEL DRILL ROD | |
| 10000027 | - | CRES | 416 | 5/32" | DIA | ASTM-A582 TYPE 416 COND. H OR 416 SE COND. H | |
| 10000028 | - | CRES | 17-4 PH | 1/4" | DIA | TYPE 17-4 ARMC STAINLESS STEEL ROD | |
| 10000029 | - | CRES | 416 | 1/4" | DIA | ASTM A582/A582M COND. H | |
| 10000031 | - | CRES | 416 | 9/32" | DIA | TYPE 416 STAINLESS STEEL ROD (RC 28-38) | |
| 10000033 | - | CRES | 416 | 1/2" | DIA | TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000034 | - | CRES | 416 | 7/16" | DIA | ASTM-A582 TYPE 416 COND. H OR 416SE COND. H | |
| 10000036 | - | CRES | 303 | 17/32" | DIA | TYPE 303 STAINLESS STEEL ROD | |
| 10000037 | A | CRES | 416 | 7/16" | DIA | ASTM-A582 TYPE 416 COND. H OR 416SE COND. H | 70218 |
| 10000040 | - | CRES | 416 | 17/32" | DIA | TYPE 416 COND. H | |
| 10000041 | - | CRES | 416 | 5/8" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000044 | - | CRES | 416 | .1517/.1520 | DIA | ASTM A582/A582M TYPE 416 COND. H OR 416SE COND. H | |
| 10000046 | - | CRES | 416 | .3950/.3953 | DIA | TYPE 416 STAINLESS STEEL ROD RC 28-35 | |
| 10000047 | - | CRES | 416 | .4260/.4265 | DIA | TYPE 416SS ROD RC 32-38 (GRD. FROM #10000037) | |
| 10000058 | - | Copper | COPPER | .016 x .040 | T x W | RECTANGULAR COPPER WIRE | |
| 10000075 | - | Misc | EVANOHM | 36 | GAUGE | 36 GAGE EVANOHM WIRE (HEATER WIRE) | |
| 10000078 | B | CRES | 416 | .2457-.2460 | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND. H | 76777 |
| 10000084 | - | CRES | 416 | .1872-.1875" | DIA | TYPE 416 COND. H OR 416 SE COND. H | |
| 10000094 | - | Iron | IRON | 9/16" | DIA | ARMCO PURE IRON BAR (COLD DRAWN) ARMCO INGOT | |
| 10000124 | - | CRES | 303 | 1/8" | HEX | ASTM A582 TYPE 303 COND A | |
| 10000127 | - | CRES | 416 | 13/16" | DIA | ASTM-A-582/A 582M TYPE 416 OR 416SE COND. A (RC 27 MAX) FOR M126 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|------------------|--------------|--------|--|-------|
| 10000128 | - | CRES | 416 | .7812/.7807 | DIA | TYPE 416 STAINLESS STEEL ROD FROM 10000127 | |
| 10000131 | - | CRES | 303 | 5/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000141 | - | Copper | BERYLLIUM | 3/4" | DIA | BERYLLIUM COPPER COND 1/2H ASTM B196 ALLOY C17200 TEMPER TDO4 HARD | |
| 10000142 | - | Iron | IRON | 3/4" | DIA | CARPENTER ELECTRICAL IRON Y117A017-102 | |
| 10000147 | - | CRES | 303 | 3/4" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000152 | - | CRES | 416 | 1 3/4" | DIA | TYPE 416 OR 416SE COND. A (RC27 MAX) | |
| 10000165 | - | CRES | 416 | .2185/.2182 | DIA | TYPE 416SS ROD GRD. FROM 1/4" RC 28-38 | |
| 10000168 | A | CRES | 416 | 1 1/8" | DIA | ASTM A582/A582M COND. A | 78060 |
| 10000169 | - | Nickel Iron | NICKEL IRON 49 | 9/32" | DIA | ALTECH 905L OR CARPENTER 49 | |
| 10000170 | - | CRES | 17-4 PH | .2460/.2457 | DIA | AMS-5643 COND. H1075 17-4 PH | |
| 10000173 | - | CRES | 416 | .120 | DIA | TYPE 416 STAINLESS STEEL ROD RC 32-36 | |
| 10000174 | - | CRES | 416 | .1520/.1517 | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND. H (RC32-38) | |
| 10000175 | - | CRES | 416 | .182 | DIA | TYPE 416 STAINLESS STEEL ROD RC 32-36 | |
| 10000176 | - | CRES | 416 | 5/16" | DIA | ASTM A582 TYPE 416 OR 416SE COND H | |
| 10000177 | - | CRES | 416 | 3/8" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. H | |
| 10000178 | - | CRES | 416 | .3100/.3097 | DIA | TYPE 416 OR 416SE COND. H (RC31-38) | |
| 10000179 | - | CRES | 416 | .3720/.3717" | DIA | TYPE 416 COND H | |
| 10000189 | A | Cobalt | COBALT 17% | 3/4" | DIA | SIMONDS #81 (C190000208 CLASS 1) | 76391 |
| 10000192 | - | CRES | 416 | .5930/.5927 | DIA | .593 SS ROD GROUND FROM 5/8" COND. A 10000041 (NOC#31923) | |
| 10000201 | - | Bronze | BRONZE, PHOSPHOR | 5/16" | DIA | ASTM B139 ALLOY C51000 TEMPER H04 (HARD) | |
| 10000202 | - | CRES | 303 | 1 1/8" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000211 | - | CRES | 416 | 5/32" | DIA | TYPE 416SS RC 32-36 | |
| 10000213 | - | CRES | 416 | 9/16" | DIA | ASTM-A582 TYPE 416 OR 416SE COND A | |
| 10000215 | - | CRES | 303 | 1 1/2" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|------------------|-----------------|---------|---|-------|
| 10000232 | - | Steel | 1095 | .1890 | DIA | C1095 STEEL GRD. TO +/-0.003 FOR 330437 DUMMY SHAFT | |
| 10000236 | - | Nickel Iron | NICKEL IRON 49 | 1/2" | DIA | IAW Y202A014-101, -102, OR -105 | |
| 10000246 | - | Aluminum | 2024 | 3/4" | DIA | AMS-QQ-A-225/6 TEMPER T4 ALUMINUM | |
| 10000257 | - | CRES | 416 | 7/16" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000258 | - | CRES | 416 | 2 1/4" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000263 | - | Aluminum | 1100 | 3/4" | DIA | AMS-QQ-A-225/1 OR ASTM B211 TEMPER F | |
| 10000264 | - | Aluminum | 2024 | 1 1/2" | DIA | AMS-QQ-A-225/6 ALUM 2024 T4 | |
| 10000271 | - | Copper | COPPER MANGANESE | 1" | DIA | 1" COPPER MANGANESE MODIFIED AMPCOLOY 905 | |
| 10000274 | - | CRES | 303 | 3/8" | DIA | ASTM A582 TYPE 303 OR 303SE COND A | |
| 10000275 | - | Aluminum | 2024 | 1 1/8" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10000276 | - | CRES | 416 | 1/8" | HEX | TYPE 416 COND. A | |
| 10000277 | - | CRES | 303 | 5/32" | DIA | ASTM A582/A582M COND. A | |
| 10000291 | - | Aluminum | 2024 | 1 5/8" | DIA | 1 5/8 ALUMINUM 2024T-351 | |
| 10000292 | - | CRES | 416 | .2340/.2337 | DIA | ASTM A581/A581M COND.H STRESS RELIEVED-CARPENTER | |
| 10000293 | - | CRES | 303 | 3/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000295 | - | Bronze | BRONZE, ALUM | 1" | DIA | ALUMINUM BRONZE, SILICON BEVERE #436 | |
| 10000298 | - | CRES | 17-4 PH | 3/16" | DIA | CRES AMS - 5643 COND. H1075 (17-4 PH) | |
| 10000303 | - | CRES | 303 | 9/32" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000304 | - | CRES | 303 | 1/4" | DIA | ASTM A582 TYPE 303 COND. A | |
| 10000311 | - | Aluminum | 2024 | 7/8" | DIA | AMS-QQ-A-225/6 TEMPER T4 (2024-T4) OR T351 | |
| 10000312 | - | Aluminum | 1100 | 1" | DIA | AMS-QQ-A-225/1 OR ASTM B211 TEMPER F | |
| 10000315 | - | CRES | 303 | 3/32" | DIA | 303" S.S. ROD TYPE 303 | |
| 10000317 | - | CRES | 416 | 7/32" | DIA | ASTM A582 TYPE 416 COND H | |
| 10000318 | - | CRES | 416 | 1 1/16" x 1.027 | OD x ID | (.018 WALL) S.S. TYPE 416 TUBING | |
| 10000319 | A | Copper | COPPER MANGANESE | 1 3/4" | DIA | PER MATERIAL BOX OF DWG. C556002110 | 77709 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------------|-------------|--------|---|-------|
| 10000322 | - | CRES | 303 | 1 3/4" | DIA | ASTM-A582 TYPE 303 COND. A | |
| 10000323 | C | CRES | 303 | 7/8" | DIA | ASTM-A582/A582M COND A | 87204 |
| 10000332 | - | CRES | 303 | 1 7/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000333 | - | Silver | 180 ALLOY | 30 | GAUGE | HOOK UP WIRE, SOLID CONDUCTOR EXTRUDED TEFLON | |
| 10000334 | - | Silver | 180 ALLOY | 31 | GAUGE | HOOK UP WIRE, SOLID CONDUCTOR EXTRUDED TEFLON | |
| 10000335 | - | CRES | 303 | 1" | DIA | ASTM-A582 TYPE 303 OR 303SE COND A | |
| 10000336 | - | CRES | 303 | 1 3/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000338 | - | Brass | BRASS 360 | 11/16" | DIA | 11/16" DIA BRASS ASTM B16-46 1/2 HARD | |
| 10000339 | - | Cobalt | COBALT 17% | 1" | DIA | IAW C190000208 | |
| 10000340 | A | CRES | 416 | .233/.235 | DIA | C'LESS GROUND FROM 10000029 1/4" DIA. | 75959 |
| 10000341 | - | Aluminum | 2024 | 1" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10000342 | - | CRES | 303 | 1 13/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000343 | - | CRES | 416 | .3756/.3760 | DIA | TYPE 416 COND. A | |
| 10000344 | A | Brass | BRASS 360 | 1" | DIA | ASTM B16 ALLOY C36000 TEMPER 1/2H | 77050 |
| 10000345 | - | CRES | 17-4 PH | 5/16" | DIA | ARMCO PH COND. A S.S. ROD | |
| 10000346 | - | CRES | 17-4 PH | .3115/.3111 | DIA | ARMCO PH COND. A S.S. ROD C'LESS GRD. | |
| 10000347 | - | Steel | STEEL DRILL ROD | .1285 | DIA | SIZE #30 DRILL ROD 12' LENGTHS | |
| 10000348 | - | CRES | 303 | 1 3/8" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000350 | - | CRES | 303 | 1 1/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000353 | - | CRES | 416 | 1/2" | DIA | STAINLESS STEEL ROD ANNEALED 13-16 RC | |
| 10000354 | - | Aluminum | 2024 | 1 1/4" | DIA | AMS-QQ-A-225/6 TEMPER T351 (2024-T351) | |
| 10000355 | - | CRES | 303 | 5/8" | DIA | ASTM-A582 TYPE 303 COND A | |
| 10000360 | - | CRES | 303 | 7/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND A | |
| 10000362 | - | Brass | BRASS 360 | 1 11/16" | DIA | BRASS ROD ASTM B16-46 1/2 HARD | |
| 10000373 | - | CRES | 416 | 3/4" | DIA | ASTM A582 TYPE 416 OR 416SE COND A | |
| 10000374 | - | CRES | 410 | 7/16" | DIA | CLASS 410 COND. A | |
| 10000375 | - | CRES | 416 | 7/32" | DIA | GROUND NO. .1890/.1887 QQ-S-764 CLASS 6 PH 20135 | |
| 10000380 | - | CRES | 303 | 1/8" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|---------------------|--------------|--------|--|------|
| 10000384 | - | Brass | BRASS 360 | 3/4" | DIA | ASTM B16 ALLOY 360 TEMPER 1/2 H | |
| 10000387 | - | Brass | BRASS | 7/8" | DIA | BRASS ROD HALF HARD | |
| 10000388 | - | CRES | 303 | .2182-.2185" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000389 | - | Cobalt | COBALT 17% | 5/8" | DIA | IAW C190000208 CLASS 1 COBALT | |
| 10000391 | - | CRES | 416 | .5000/.4995 | DIA | TYPE 416 R/C GRD. FROM 17/32 CLASS (10000040) | |
| 10000394 | - | CRES | 303 | 13/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000395 | - | Copper | COPPER | .016 x .040 | T x W | RECTANGULAR COPPER WIRE H.H. TEMPER | |
| 10000396 | - | Brass | BRASS 360 | 5/32" | DIA | ASTM B16 ALLOY 360 TEMP 1/2 H | |
| 10000397 | - | Brass | BRASS 360 | .620/.625 | DIA | COMMERCIAL C'LESS ASTM B16 COMP. 22 1/2 HARD | |
| 10000398 | - | CRES | 416 | 3/8" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. H | |
| 10000399 | - | Brass | BRASS | 1/2 | DIA | BRASS ROD ASTM B16 COMP. B 1/2 HARD | |
| 10000401 | - | Copper | COPPER MANGANESE | 3/4 | DIA | COPPER MAG. 3/4 C180 000 362 | |
| 10000402 | - | Misc | RULON | .015 x 2" | T x W | FOR 200 012 498 WEAR STRIP | |
| 10000404 | - | Nickel Iron | NICKEL IRON 49 | .529-.530" | DIA | GRD FROM 10 000 820 | |
| 10000409 | - | Cobalt | COBALT 17% | .5595 | DIA | COBALT STEEL 17% | |
| 10000410 | - | CRES | 416 | 3/16" | DIA | HEX STAINLESS STEEL ROD TYPE 416 | |
| 10000412 | - | Steel | STEEL DRILL ROD | .250 | DIA | .250 DRILL ROD | |
| 10000413 | - | Steel | STEEL DRILL ROD | .188 | DIA | .188 DRILL ROD | |
| 10000414 | - | Steel | STEEL DRILL ROD | .1874 | DIA | .1874 DRILL ROD | |
| 10000415 | - | Brass | BRASS 360 | 2" | DIA | ASTM B16 ALLOY 360 TEMPER 1/2 H | |
| 10000416 | - | CRES | 416 | .2497-.2500" | DIA | TYPE 416 COND H | |
| 10000417 | - | CRES | 303 | .2457-.2460" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000424 | - | Copper | COPPER, LEADED | 1/2" | DIA | COPPER ROD ALLOY 187 1/2 HARD 99% CU 1% PB | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|-------------------|--------|---|-------|
| 10000427 | - | CRES | 303 | .234/.233" | DIA | C'LESS GROUND FROM .250 57 K P/N 10000304 | |
| 10000432 | A | Copper | COPPER, LEADED | .3750/.3747 | DIA | COPPER ROD ALLOY 187, FULL HARD IAW ASTM-B301 | 80417 |
| 10000434 | - | Cobalt | COBALT 17% | 9/16 | DIA | COBALT STEEL 17% | |
| 10000436 | - | CRES | 420 | 3/4" | DIA | QQ-S-763 CLASS 420 COND A | |
| 10000441 | - | Silver | 180 ALLOY | 1 1/2 | DIA | ALLOY 180 1 1/2 DIA (23% NICKEL, REMAINDER COPPER) | |
| 10000445 | - | CRES | 416 | 9/32" | DIA | ASTM A582 TYPE 416 COND A | |
| 10000446 | - | CRES | 416 | .2810 | DIA | .2810+ .0003- .0000 GRD FROM 5/16 DIA P/N 10000176 | |
| 10000447 | - | Nickel | NICKEL SILVER | | | POWDERED NICKEL SILVER 25 PERCENT NICKEL | |
| 10000448 | - | CRES | 416 | .1875+0-.0005 | DIA | QQ-S-764 CLASS R/C 28-38 C;LESS GRD. FROM 10000317 ASTM A484 & ASTM A582 | |
| 10000449 | - | Bronze | BRONZE, PHOSPHOR | 5/8 | DIA | ASTM B139 COMP. HAND BOOK CODE 10240 | |
| 10000450 | - | CRES | 416 | 1 7/16" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000452 | - | CRES | 416 | .4330-.4327" | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND A | |
| 10000453 | - | CRES | 303 | .3760+0-.0003 | DIA | ASTM A582 TYPE 303 COND. A | |
| 10000456 | - | CRES | 416 | .2787-.2790 | DIA | (10000176) C'LESS GRD TO .2787/.2790 RC 32- 36 | |
| 10000458 | - | Aluminum | 2024 | .5000+0-.0005 | DIA | TYPE C'LESS GROUND FROM 10000246 ALUM 2024 T4 | |
| 10000459 | - | CRES | 303 | .2497-.2500 | DIA | ASTM A582/582M COND. A | |
| 10000462 | - | CRES | 416 | .4370+.0-.0005 | DIA | C'LESS GROUND FROM 17/32 DIA 10000040 | |
| 10000463 | - | Brass | BRASS 360 | 3/32" | DIA | ASTM B16 ALLOY 360 TEMPER 1/2H | |
| 10000465 | - | Brass | BRASS | .025"±.002 x 3/4" | T x W | ASTM B36 COMP. C 1/2 FLAT STOCK | |
| 10000466 | - | Cobalt | COBALT 17% | 3/4 | DIA | TYPE COBALT STEEL 17% | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------------|---------------|--------|--|------|
| 10000467 | - | CRES | 416 | 1 13/16" | DIA | TYPE 416 OR 416SE COND. A ASTM A582/A582M | |
| 10000468 | - | Brass | BRASS 360 | 11/16 | DIA | ASTM B16 COMP. #22 1/2 HARD FED SPEC | |
| 10000470 | - | CRES | 303 | .6087-.6090" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000471 | - | Silver | 135 ALLOY SILVER | | | SILVER PLATED 30 GAUGE SINGLE CONDUCTOR | |
| 10000473 | - | Silver | 180 ALLOY SILVER | | | SILVER PLATED 31 GAUGE SINGLE CONDUCTOR | |
| 10000479 | - | Brass | BRASS | 17/32 | DIA | ASTM B16 COMP B 1/2 HD/106778 HSG NOC #10403 5/23/66 | |
| 10000480 | - | CRES | 416 | .4846/.4842 | DIA | GROUND FROM 10000040 | |
| 10000481 | - | Aluminum | 1100 | .3750-.3747" | DIA | AMS-QQ-A-225/1 OR ASTM B211 TEMPER F | |
| 10000483 | - | Brass | BRASS | 5/32 | HEX | ASTM B16 COMP. B HARD FED. SPEC | |
| 10000484 | - | Aluminum | 2024 | 11/16 | DIA | AMS-QQ-A-225/6 TEMP. T4 | |
| 10000485 | - | Brass | BRASS 360 | 3/16" | DIA | ASTM B16 TEMPER H02 (1/2 HARD) | |
| 10000486 | - | Aluminum | 2024 | 1 1/4 | DIA | AMS-QQ-A-225/6 TEMP. T351 | |
| 10000487 | - | CRES | 303 | .1249"-.1246" | DIA | ASTM-A582 TYPE 303 OR 303SE COND A | |
| 10000488 | - | CRES | 302 | 1.062 | DIA | ASTM A240, ASTM A666, ASTM A693 CLASS 302 AISI 302 COND. A TO MAKE 200022985 | |
| 10000489 | - | Aluminum | 2024 | 1 5/16 | DIA | AMS-QQ-A-225/6 TEMP. T351 FOR FLANGE TYPE CU9611 | |
| 10000490 | - | Iron | IRON | 21/32 | DIA | ELECTROLETIC IRON | |
| 10000491 | - | Brass | BRASS | 11/16 | DIA | ASTM B16 COMP B 1/2 HD | |
| 10000492 | - | CRES | 416 | .3280/.3277 | DIA | TYPE 416 OR 416SE COND. H (RC 31-38) | |
| 10000493 | - | Aluminum | 2024 | 1 3/16" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10000494 | - | Aluminum | 2024 | 13/16 | DIA | AMS-QQ-A-225/6 TEMP. T4 | |
| 10000495 | - | CRES | 416 | 11/16" | DIA | ASTM A582/A582M TYPE 416 COND. A (RC 27 MAX) | |
| 10000496 | - | Brass | BRASS | 1 1/8 | DIA | ASTM B16 COMP. B 1/2 HARD FED. SPEC. | |
| 10000497 | - | Brass | BRASS 360 | 3/16" | HEX | ASTM B16 COMP/22 TEMP 1/2 H | |
| 10000500 | - | Bronze | BRONZE, PHOSPHOR | 5/16 | DIA | S A E 660 PHOSPHOR BRONZE | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------------|-----------------|---------|--|-------|
| 10000501 | - | CRES | 416 | .3720/.3717 | DIA | FROM 10000177 3/8 DIA FOR 200019427 & 428 GEAR BLANKS | |
| 10000502 | - | CRES | 416 | .4494-.4497" | DIA | TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000503 | - | CRES | 416 | 1/8" x 1/4" | T x W | CRESS. 416 COND. A (AISI 416) FOR BILLS OF MAT. P/N | |
| 10000504 | - | CRES | 416 | 2 1/2" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000505 | - | CRES | 416 | 1 3/8" | DIA | TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000506 | - | CRES | 416 | 1 5/8 | DIA | ASTM A484 / ASTM A582 CLASS 416 COND. A RC 27 MAX | |
| 10000508 | - | Aluminum | 6061 | .250" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 | |
| 10000509 | - | CRES | 303 | 9/32 | DIA | ASTM A582 TYPE 303 COND. A | |
| 10000510 | - | Nylon | NYLON 6/6 | 7/8 | DIA | NYLON ROD 6/6 LP 410 - DO NOT REORDER | |
| 10000511 | - | Nylon | NYLON | 3/4 | DIA | NYLON ROD #101 - DO NOT REORDER | |
| 10000512 | - | Nylon | NYLON | 1 3/8 | DIA | NYLON ROD #101 - DO NOT REORDER | |
| 10000513 | - | Cobalt | COBALT 36% | 5/8 | DIA | COBOLT STEEL (35%) | |
| 10000514 | - | Nylon | NYLON 6/6 | .166" x.133" | OD x ID | 6/6 NYLON TUBING L-P-410 | |
| 10000515 | - | CRES | 416 | 1/2" | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000516 | - | Iron | SILICON CORE IRON | 2 1/2" | DIA | B-FM SPEC. 190000380 | |
| 10000517 | - | Iron | SILICON CORE IRON | 4 1/4" | DIA | B-FM SPEC 190000380 | |
| 10000518 | - | Steel | 1015 | 2 1/4"x2.060 | DIA | QQ-S-830 TYPE SMLS COMP. MT 1015 COND. AHL | |
| 10000519 | - | CRES | 304 | 1 1/4" x 1.120" | OD x ID | AMS-T-8506 TYPE 1 OR 2 | |
| 10000520 | - | Aluminum | 2024 | 7/8 | DIA | ALUMINUM TEMPER 2024-T4 A 225/6 | |
| 10000521 | - | Aluminum | 2024 | 13/16 | DIA | AMS-QQ-A-225/6 ALUM. TEMPER 2024-T4 | |
| 10000522 | - | Aluminum | 2024 | 1/2" | DIA | AMS-QQ-A-225/6 | |
| 10000524 | - | CRES | 440C | 1/8 ±.005 | DIA | 440 C S/S DIGITAL INDICATOR | |
| 10000525 | A | Aluminum | 1100 | 1 1/8" | DIA | ASTM B221 ALLOY 1100 TEMPER F OR ASTM B211 ALLOY 1100 TEMPER F | 87780 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|---------------------|-----------------|--------------|--|-------|
| 10000527 | - | Copper | COPPER MANGANESE | 1 1/16 | DIA | PER C180000362 | |
| 10000528 | - | CRES | 416 | .1884/.1881 | DIA | GROUND FROM 10000317 STOCK | |
| 10000529 | - | Aluminum | ALUM | 3/4" | DIA | E.C. GRADE 99.45+ % PURE PER D.E.I. #01623/T CROOK | |
| 10000530 | - | CRES | 304 | 1 1/4" x 1.010" | OD x ID | AMS-T-8506 | |
| 10000531 | - | Aluminum | 6061 | 1/4" x .058" | OD x WALL | WW-T-700/6 TYPE 1 T6 (6061-T6) | |
| 10000532 | - | CRES | 416 | 17/32" | DIA | TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000533 | - | Nylon | NYLON | 1" | DIA | SYTEL 103 NYLON FOR 506012117 FORM COIL | |
| 10000534 | - | CRES | 416 | 2" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10000535 | - | Nylon | NYLON 6/6 | .136" x .106" | OD x ID | L-P-410 NYLON 6/6 308022123 SPAC. | |
| 10000536 | - | Brass | BRASS 360 | 9/32" | DIA | ASTM B16 TEMPER H02 (1/2 HARD) | |
| 10000537 | A | Nickel Iron | NICKEL IRON 49 | 13/16" | DIA | IAW Y202A014-101, 102, OR -105 OR MIL-N-14411 COMP. 3 | 76892 |
| 10000539 | - | CRES | 303 | 9/16" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000540 | - | Aluminum | 2024 | 1 13/16" | DIA | ALUMINUM AMS-QQ-A-225/6 TEMP 351 (2024 T351) | |
| 10000541 | - | Aluminum | 2024 | 1 11/16" | DIA | AMS-QQ-A-250/4 TEMP. T4 (2024-T351) | |
| 10000542 | - | Copper | COPPER, ETP | .009" x 5/8" | T x W | ASTM B152 TYPE ETP TEMP. ANNEALED ETP | |
| 10000544 | - | Nylon | NYLON 6/10 | 5/8 | DIA | MIL-P-17091 TYPE 11 (ZYTEL 31) | |
| 10000545 | - | CRES | 304 | 1 1/2" x .035" | OD x WALL | TYPE 304 S.S. TUBING | |
| 10000546 | - | CRES | 410 | .010" | T | TYPE 410 STRIP MATERIAL .010 THICK | |
| 10000547 | - | Aluminum | ALUM | .025" x 5/32" | T x W | THICK ALUMINUM STRIP STOCK | |
| 10000548 | - | Nickel Iron | NICKEL IRON 49 | 1 1/16" | DIA | ASTM-A753 TYPE 2 | |
| 10000549 | - | Nickel Iron | NICKEL IRON 49 | 9/16" | DIA | ASTM-A753 TYPE 2 | |
| 10000550 | - | CRES | 416 | .3647/.3650 | DIA | GROUND FROM 10000177 AISI 416 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|--------------------|--------|---|------|
| 10000551 | - | Aluminum | 2024 | 1 1/8" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10000552 | - | Steel | 1212 | 1 1/8" | DIA | CARBON STEEL AISI 1212 | |
| 10000553 | - | Nylon | NYLON 6/6 | 7/16" | DIA | NYLON LP 410 6/6 | |
| 10000554 | - | Brass | BRASS 360 | 1/8" | HEX | ASTM B16 COMP. 22 TEMPER 1/2 H | |
| 10000556 | - | CRES | 321 | 3/32" | DIA | AMS-QQ-S-763 CLASS 321 COND. A | |
| 10000557 | - | CRES | 321 | 3/16" | DIA | AMS-QQ-S-763 CLASS 8 COND. A AISI TYPE 321 | |
| 10000558 | - | CRES | 416 | 1 3/16" | DIA | TYPE 416 OR 416SE COND A | |
| 10000560 | - | CRES | 416 | .2445/.2450 | DIA | CENTERLESS GROUND FROM 10000029 AISI 416 | |
| 10000561 | - | Brass | BRASS 360 | 1/8" | DIA | ASTM B16 COMP. 22 TEMPER 1/2 H AISI B16 | |
| 10000562 | - | CRES | 416 | .1492-.1495 | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND. A | |
| 10000563 | - | CRES | 302 | .029/.033" x 15/16 | T x W | AMS-QQ-S-763 CLASS 4 TYPE A AISI 302 | |
| 10000564 | - | Cobalt | COBALT 36% | 1" | DIA | MMPA 0100 | |
| 10000565 | - | CRES | 416 | .1871-.1873" | DIA | TYPE 416 OR 416SE COND. H (RC31-38) | |
| 10000566 | - | CRES | 416 | .1492/.1495 | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND A | |
| 10000567 | - | CRES | 416 | .5156/.5152 | DIA | C'LESS GROUND FROM 10000040 | |
| 10000568 | - | Misc | ELGILOY | .0125 ±.0005 | T | ELGILOY 85% COLD ROLLED STRIP STOCK | |
| 10000569 | - | CRES | 410 | .012"±.001 x .500" | T x W | ASTM A240, ASTM A666, ASTM A693 CLASS 410 COND. A CRES. | |
| 10000570 | - | CRES | 416 | 1/2" x 1" | T x W | ASTM A484 ASTM A582 CLASS 416 COND. H PRE-HARDENED RC 34-38 | |
| 10000571 | - | CRES | 416 | 1 1/2" | DIA | TYPE 416 OR 416SE COND. H (RC 31-38) | |
| 10000572 | - | CRES | 416 | .2027/.2030 | DIA | C'LESS GROUND FROM 10000317 (ASIS 416) | |
| 10000573 | - | Steel | 1212 | 1 1/2" | DIA | CARBON STEEL (AISI 1212) | |
| 10000574 | - | Silver | SILVER, COIN | .050" | T | MIL-S-13282A CLASS C, TEMP HARD 85HR15-T MIN | |
| 10000575 | - | CRES | 303 | 2 1/2" | DIA | AMS-QQ-S-763 (AISI 303) | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|----------------|--------|--|-------|
| 10000576 | - | Copper | BERYLLIUM | | | BERYLLIUM COPPER (FOR 343002374) TEMP. STOCK | |
| 10000577 | B | Aluminum | 6061 | 1 1/4" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | 87143 |
| 10000578 | B | Aluminum | 6061 | 1 5/16" | DIA | SAE AMS-QQ-A-200/8 TEMPER T6511 | 87420 |
| 10000579 | - | CRES | 303 | 1 1/4" | DIA | ASTM A582 TYPE 303 COND A | |
| 10000580 | - | Nickel Iron | NICKEL IRON 49 | .3955/.3950 | DIA | C'LESS GRD FRM 1/2" #10000236-ALTECH 905L-CARPENTER 49 | |
| 10000581 | - | Misc | PERMALLOY 65 | 2" | DIA | PERMALLOY #65 B101 291 032 | |
| 10000582 | - | CRES | 416 | .1250/.1248 | DIA | AISI 416 GRD. FRM. 10000027-5/32" DIA | |
| 10000583 | - | CRES | 416 | .2517/.2520 | DIA | AISI 416 GRD. FRM. 10000031-9/32" DIA | |
| 10000584 | - | CRES | 303 | .1552/.1555 | DIA | AISI 303 C'LESS GRD. FRM. 10000277-5/32" DIA | |
| 10000585 | - | CRES | 416 | .1552/.1555 | DIA | TYPE 416 COND. H | |
| 10000586 | - | Nickel Iron | HY MU 80 | 2 3/16" | DIA | IAW Y059A005-236 | |
| 10000587 | - | CRES | 303 | 11/16" | DIA | ASTM A582 TYPE 303 COND. A | |
| 10000588 | - | CRES | 416 | 7/8" | DIA | ASTM-A-582/A 582M TYPE 416 OR 416SE COND. A | |
| 10000589 | - | Copper | BERYLLIUM | .067" x 1.000" | T x W | BERI-COPPER STRIP SOUTHERN TOOL & DIE | |
| 10000590 | B | Nickel Iron | NICKEL IRON 49 | 1 1/2" | DIA | NICKEL IRON ALLOY IAW Y202A014-101, -102 OR -105 OR MIL-N-14411 COMP.3 | 75768 |
| 10000591 | - | CRES | 416 | 1/4" | DIA | TYPE 416 COND. H | |
| 10000592 | - | CRES | 416 | .2460/.2457 | DIA | R/C 32-38 GROUND FROM 10000591 | |
| 10000593 | - | Nylon | NYLON 6/6 | 1/2" | DIA | NYLON LP 410 6/6 | |
| 10000594 | - | CRES | 303 | .4265/.4260 | DIA | AISI 303 GRD. FRM. 7/16" DIA 10000360 | |
| 10000595 | - | CRES | 416 | .5867-5870" | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND. H | |
| 10000596 | - | Copper | BERYLLIUM | 1" | DIA | ASTM B196 OR B197 OR B194 BERYLLIUM COPPER COND. 1/2 HARD | |
| 10000597 | - | Nylon | NYLON 6/10 | 1/2" | DIA | NYLON LP 410 6/10 ZYTEL 31 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|----------------|-----------------------|---------|---|-------|
| 10000598 | - | Copper | BERYLLIUM | 3/8" | DIA | ASTM B196 OR B197 OR B194 BERYLLIUM COPPER COND. HARD | |
| 10000599 | - | Nylon | NYLON | 3/4" | DIA | MIL-P-20693 NYLON COMP. B TYPE IV A | |
| 10000600 | C | Nickel Iron | NICKEL IRON 49 | 1 1/8" ALT. 1 1/4" | DIA | IAW ASTM A753 ALLOY TYPE 2 (CARPENTER 49) | 91279 |
| 10000601 | A | CRES | 416 | .624-.625" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. H CENTERLESS GROUND | 73199 |
| 10000602 | - | Nickel Iron | HY MU 80 | 1/4" | DIA | HY-MU80 FOR B508 001 002-1 | |
| 10000604 | - | CRES | 416 | .780" x .730" | OD x ID | CLASS 416 COND. A SEAMLESS TUBING - COMMERCIALY | |
| 10000606 | - | Misc | TEFLON | 1/2" | DIA | ASTM D1710 | |
| 10000607 | - | Aluminum | 2024 | 3/8" x 1 1/2" | T x W | ASTM B241 OR B221 TEMPER T4 | |
| 10000608 | A | Steel | C1018 | 5/16" | DIA | C1018 IAW ASTM A108 | 76496 |
| 10000609 | - | Steel | 1018 | 1/8" | SQ | CARBON STEEL AISI C1018 | |
| 10000610 | - | CRES | 416 | 1.165" x 1.025" | OD x ID | CLASS 416 COND. A SEAMLESS TUBING C'LESS GRD TO 1.156 | |
| 10000611 | - | Aluminum | 5052 | .020"±.002 x 1/2" | T x W | AMS-QQ-A-250/8 TEMP. H 32 5052-H32 | |
| 10000612 | - | Iron | IRON | .018"±.002 x 1/2" | T x W | STOCK PER Y059A003-104 FOR 200052991 RN #95625 | |
| 10000613 | - | CRES | 410 | 1" | DIA | AMS-QQ-S-763 CLASS 410 COND. A AISI 410 | |
| 10000614 | A | Nickel Iron | NICKEL IRON 49 | 1" | DIA | Y202A014-101, -102, OR -105 OR MIL-N-14411 COMP.3 | 75768 |
| 10000615 | - | Steel | 1212 OR 1213 | 1/8 ±.002 | DIA | QQ-S-637 STEEL C1212 OR C1213 | |
| 10000616 | A | Nylon | NYLON | 5/16 | DIA | PLOYPENCO NYLON 6,6 ROAD, WHITE, L-P-410 OR ASTM-D4066, PA0114 | 72648 |
| 10000617 | - | Brass | BRASS 360 | 13/16" | DIA | ASTM B16 ALLOY 360 TEMPER 1/2 H | |
| 10000618 | - | CRES | 303 | .1520/.1517 | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000620 | - | Copper | COPPER, STP | 11/16" | DIA | SILVER BEARING 10-1602/TON MS400-1 TYPE 1 | |
| 10000621 | - | CRES | 416 | .1403/.1400 | DIA | GROUND FROM 10000027 RC 28-35 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|-------------|--------|---|-------|
| 10000622 | - | CRES | 416 | 49/64" | DIA | CRES. COND.H RC 28-35 FOR GEARS CV05708003 | |
| 10000623 | - | Bronze | BRONZE, PHOSPHOR | 3/4" | DIA | ASTM B139, O COMP. A TEMP. H CASTM B 139 ALY A C51000 | |
| 10000624 | - | CRES | 416 | .4000/.3995 | DIA | CRES. 416 RC 28-35 GRD. FROM 10000037 | |
| 10000625 | - | Aluminum | 2024 | 2 1/2" | DIA | AMS-QQ-A-225/6 TEMPER T351 (ALUM 2024 T351) | |
| 10000626 | - | CRES | 440C | .251-.252" | DIA | QQ-S-763 CLASS 440C COND A | |
| 10000627 | B | Steel | 8620 | 1/4" | DIA | PER ASTM A108 | 78293 |
| 10000628 | - | Steel | 12L14 | 7/8" | DIA | ASTM A108 GRADE 12L14 | |
| 10000629 | - | Steel | 41L40 | 15/16" | DIA | 203-2 TYPE 6 AISI 41L40 COLD DRAWN | |
| 10000631 | - | Steel | 12L14 | 7/16 | DIA | 205-1 TYPE 2 AISI C12L14 COLD DRAWN | |
| 10000632 | - | Bronze | BRONZE, ALUM | 7/16 | DIA | ALUMINUM BRONZE ROD D340 261 00 | |
| 10000633 | B | Steel | 8620 | 7/16 | DIA | PER ASTM A108 | 78293 |
| 10000634 | - | Steel | 41L40 | .4255/.4265 | DIA | 203-2 TYPE 6 C'LESS GRD. TO .4244/.4265 | |
| 10000635 | C | Bronze | BRONZE | 3/4" | DIA | OIL IMPREGNATED SINTERED BRONZE IAW SAE AMS4805 OR ASTM B438 DESIGNATION CODE CT-1000-K26 | 90307 |
| 10000636 | - | Steel | 1018 | 1/4 | DIA | ASTM A108 GRADE 1018 | |
| 10000637 | - | Misc | TEFLON | 7/8" | DIA | ASTM D1710 TYPE 1 | |
| 10000638 | - | Misc | TEFLON | 1" | DIA | MIL-P-19468 FOR SOA A-400 & A-401 | |
| 10000639 | - | CRES | 416 | 1 3/4" | DIA | ASTM A582/A582M COND. H | |
| 10000640 | - | Aluminum | 2017 | 3 3/4 | DIA | TYPE 2017-T451 ALUM. ALLOY BAR | |
| 10000641 | - | CRES | 17-4 PH | .625 | DIA | AMS-5643 COND H1075 | |
| 10000642 | - | Aluminum | 2011 | 2" | DIA | 2011T3 ALUM. MS 404-3 TYPE 1 | |
| 10000644 | - | Steel | 4140 | 7/8 | DIA | AISI 4140 COLD DRAWN STEEL | |
| 10000645 | - | Steel | 12L14 | 3/4 | DIA | AISI C12L14 STEEL COLD FINISHED | |
| 10000646 | - | Aluminum | 2017 | 3 1/8 | DIA | TYPE 2017-T-451 ALUM. ALLOY | |
| 10000647 | - | Aluminum | 2017 | 2 1/2" | DIA | TYPE 2017-T451 ALLOY BAR 404-1 TYPE 1 D55140301 REF. | |
| 10000648 | - | Steel | 1018 | 3 1/4" | DIA | 1018 PER ASTM A108, GRADE 1018 COLD DRAWN STEEL | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|--------|--------------|------------------------|-----------|--|------|
| 10000649 | - | CRES | 416 | .3115-.3120 | DIA | TYPE 416 OR 416SE COND. H | |
| 10000650 | - | Steel | 1015 | 3/4" x .219" | OD x WALL | MT1015C SEAMLESS TUBING STEEL | |
| 10000651 | - | Steel | 41L40 | 9/16 | DIA | AISI 41L40 COLD DRAWN MS 203-2 TYPE 6, REF. 10000629 | |
| 10000652 | - | Steel | 12L14 | 3/8 | DIA | AISI C12L14 COLD DRAWN MS 205-1 TYPE 2 | |
| 10000653 | - | Brass | BRASS | .030 | T | BRASS SHIM STOCK | |
| 10000655 | - | Cobalt | COBALT 17% | 1 1/8 | DIA | PER C190000208 TABLE 1 CLASS 1 | |
| 10000656 | - | Steel | CARBON STEEL | 1 1/2 | DIA | SINTERED CARBON STEEL ASTM B310 TYPE 4 CLA | |
| 10000657 | - | CRES | 303 | .3100/.3097 | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000658 | - | Misc | 811B | 1 1/2 | DIA | AISI 811B | |
| 10000659 | - | Steel | 4140 | 3/16" | DIA | ASTM A331 GRADE 4140 COLD DRAWN, ANNEALED | |
| 10000660 | - | Steel | 4140 | 3/8 | DIA | AISI 4140 ALLOY STEEL MS 203-2 TYPE 3 | |
| 10000661 | - | Steel | 1113 | 1 1/2" | DIA | ASTM A108 GRADE 1117 | |
| 10000662 | - | Iron | IRON | .031"±.002 x 1 1/8" | T x W | COIL(NO SUBSTITUTE PERMISSIBLE) SEE ENG. BEFORE ORDER | |
| 10000663 | - | Brass | BRASS 360 | .250 | DIA | M.S. 401-1 TYPE 1 | |
| 10000664 | - | CRES | 17-4 PH | 3/8 | DIA | PRE-CIPITATION HARDING PH17-4 COND. A | |
| 10000665 | - | CRES | 17-4 PH | .3735/.3730 | DIA | PRE-CIPITATION HARD C'LESS GRD FROM 3/8 DIA 10000664 | |
| 10000666 | - | Steel | 4140 | 3/16" | DIA | ASTM A331 GRADE 4140 | |
| 10000667 | - | Steel | 4140 | 13/16" | DIA | ASTM A331 GRADE 4140 | |
| 10000668 | - | CRES | 416 | 11/32 | DIA | COND T | |
| 10000669 | - | Iron | IRON | 1.000 | DIA | CARPENTER ELECTRICAL IRON Y117A017-102 | |
| 10000670 | - | Steel | 41L40 | 3/8 | DIA | AISI 41L40 COLD DRAWN MS 203-2 TYPE 6 | |
| 10000671 | - | CRES | 416 | .3420/.3417 | DIA | AISI 416 C'LESS GRD FROM 11/32 DIA 10000668 | |
| 10000672 | - | CRES | 416 | 2 3/4" | DIA | ASTM-A582 TYPE 416 OR 415SE COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|-----------------------------|-----------|--|------|
| 10000673 | - | CRES | 416 | .3730-.3735" | DIA | TYPE 416 OR 416SE COND. A ASTM A 582/A582M | |
| 10000674 | - | CRES | 303 | 2 1/4" | DIA | ASTM A484 & A582 CLASS 303 OR 303 SE COND.A | |
| 10000675 | - | CRES | 416 | .1270/.1275 | DIA | C'LESS GROUND FROM 5/32 DIA 10000027 | |
| 10000676 | - | CRES | 416 | .4683/.4687 | DIA | ASTM A484 & ASTM A582 CLASS 416 COND. H RC 28-38/FROM 10000040 | |
| 10000678 | - | CRES | 416 | 1.062" | DIA | TYPE 416 COND A | |
| 10000679 | - | Steel | 8740 | .184/.188 | DIA | C'LESS GROUND TO .184/.188 COMM. | |
| 10000680 | - | Steel | 1215 | 1/2" | DIA | ASTM-A108 GRADE 1215 | |
| 10000682 | - | Plastic | VINYL | 0.166 | ID | NO.6 POLYVYNYL TUBING BLACK MS 523-1 TYPE 1(0-252306-13) | |
| 10000683 | - | Silver | SILVER | .125" x 3 1/4" | T x W | COIN SILVER | |
| 10000684 | - | CRES | 17-4 PH | .1865/.1860 | DIA | GROUND FROM 10000298 | |
| 10000685 | - | CRES | 416 | .2657/2570 | DIA | GROUND FROM 10000031 | |
| 10000686 | - | CRES | 416 | .5295-.5290 | DIA | TYPE 416 OR 416SE COND. H | |
| 10000687 | - | Bronze | BRONZE, ALUM | 4" x .237" | OD x WALL | ALUMINUM PIPE 4" OD .237 WALL THICKNESS 6063-T6 | |
| 10000688 | - | Copper | COPPER, OXYGEN FREE | .148 ±.001 | DIA | OXYGEN-FREE WIRE CABRA #102, 1/2 HARD MS 430-3 TYPE 2 | |
| 10000689 | - | Copper | COPPER, OXYGEN FREE | .081 ±.001 | DIA | OXYGEN-FREE WIRE CABRA #102 1/2 HARD MS 430-3 TYPE 2 | |
| 10000690 | - | Steel | STEEL, COLD ROLLED | .0359±.002 x 1 1/2 x 12' LG | | BY 1 1/2" WIDE BY 12' COLD ROLLED SHEET STEEL | |
| 10000691 | - | Steel | 4140 | 13/16 | DIA | COLD DRAWN ANNEALED MS 203-2 TYPE 1 | |
| 10000692 | - | Steel | 4140 | .8064/.8060 | DIA | C'LESS GROUND FROM 10000691 | |
| 10000693 | A | CRES | 416 | .1865-.1860" | DIA | ASTM A582/582M COND H | |
| 10000694 | - | Aluminum | 2024 | 3/8 | DIA | AMS-QQ-A-225/6D MS 404-2 TYPE 1 ROUND COLD FINISHED | |
| 10000695 | - | CRES | 416 | .3123/.3117 | DIA | C'LESS GROUND FROM 10000176 | |
| 10000696 | - | Steel | 1215 | 1" | DIA | ASTM-A-108 GRADE 1215 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|--------------------------|-----------|--|------|
| 10000697 | - | Copper | COPPER | .1018 | DIA | ASTM B3, #10 AWG, BARE COPPER WIRE ANNEALED | |
| 10000698 | - | Aluminum | 2024 | 2 1/8" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10000699 | - | Brass | BRASS 360 | 2 1/8" | DIA | ASTM B16 COMP. 22 TEMP. 1/2 HARD ASTM B16 | |
| 10000700 | - | Copper | COPPER | .162 | DIA | BARE COPPER WIRE MS 430-1 TYPE 1 #6 AWG. | |
| 10000701 | - | Bronze | BRONZE, PHOSPHOR | .057 | DIA | CABRA #510 1/4 HARD TEMPER MS 432-2 TYPE 2 | |
| 10000702 | - | Brass | BRASS 270 | .057 | DIA | CABRA #270 1/4 HARD TEMPER MS 431-1 TYPE 2 | |
| 10000703 | - | Copper | COPPER, OXYGEN FREE | .057 | DIA | CABRA #102 1/2 HARD TEMPER MS 430-3 TYPE 2 | |
| 10000704 | - | Bronze | BRONZE, JEWELRY | .057 | DIA | CABRA #226 1/4 HARD TEMP MS 432-3 TYPE 2 87.5% | |
| 10000705 | - | Aluminum | 6061 | 2 1/4" x 1/4" | OD x WALL | ASTM B241 OR ASTM B221 TEMPER T6510 (TUBING) | |
| 10000706 | - | Aluminum | 6061 | 2.625" x 2.125" | OD x ID | ALUMINUM TUBING 6061-T6 | |
| 10000707 | - | Aluminum | 6061 | 3.500" x 2.750" | OD x ID | ALUMINUM TUBING 6061-T6 | |
| 10000708 | - | Aluminum | 6061 | 3.000" x 2.250" | OD x ID | ALUMINUM TUBING 6061-T6 | |
| 10000709 | - | Copper | COPPER, ETP | .032" x .500" | T x W | ASTM B152 0-341001-08 TYPE ETP MS 410-1 | |
| 10000711 | - | Aluminum | 6061 | 3.500"±.010 x 3.300±.015 | OD x ID | ALUMINUM TUBING SPEC. | |
| 10000712 | - | Aluminum | 2024 | 3 1/2" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10000713 | - | Cobalt | COBALT 36% | 25/32" | DIA | COBALT 37% | |
| 10000714 | - | Copper | COPPER, OXYGEN FREE | .072 ±.001 | DIA | CABRA #102 1/2 HARD TEMP. MS 430-3 TYPE 2 | |
| 10000715 | - | Copper | COPPER, OXYGEN FREE | .0808 ±.001 | DIA | CDA #102 HARD TEMP. #12 AWG BARE MS 430-3 TYPE 3 | |
| 10000716 | - | Brass | BRASS 270 | .0808 | DIA | ASTM B134 ALLOY 7 AWG #12 BARE | |
| 10000717 | - | CRES | 303 | 2 1/16" | DIA | AISI TYPE 303 MS 202-1 TYPE 1 | |
| 10000718 | - | CRES | 416 | .3400/.3397 | DIA | AISI C'LESS GROUND FROM 10000668 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------------------|-----------------------------|---------|---|------|
| 10000719 | - | CRES | 416 | .5605/.5600 | DIA | TYPE 416 COND. T | |
| 10000720 | - | CRES | 303 | 1 7/8" | DIA | ASTM A582 TYPE 303 COND A | |
| 10000721 | - | CRES | 303 | .5070-.5065 | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000722 | - | Copper | COPPER, OXYGEN FREE | .0359 | DIA | COBRA #102 1/2 HARD TEMP MS 430-3 TYPE 2 | |
| 10000723 | - | Steel | 1113 | 1 3/8" | DIA | AISI B1113 STEEL COLD DRAWN MS 200-1 TYPE 1 | |
| 10000724 | - | Steel | 4140 | 3/8" | DIA | AISI 4140 STEEL COLD DRAWN ANNEALED MS 203-2 TYPE 1 | |
| 10000725 | - | Steel | 4140 | .3735/.3730 | DIA | AISI 4140 STEEL C'LESS GRD. FROM 10000724 | |
| 10000726 | - | Steel | 1018 | 2.385/2.375" x 2.24/2.25 | OD x ID | AISI C1018 SEAMLESS STEEL TUBING COLD DRAWN | |
| 10000727 | - | Steel | 1015 | 2.875" x 2.312" | OD x ID | AISI MT MS 220-3 TYPE 2 SEAMLESS 1015 | |
| 10000728 | - | Steel | 1018 | 1/2" | DIA | ASTM A108 GRADE 1018 | |
| 10000729 | - | CRES | 303 | 2 9/16 | DIA | ASTM A484 & 582 CRES CLASS 303 COND. A | |
| 10000730 | - | Steel | 1018 | 3 1/4" | DIA | QQ-S-634 C1018 | |
| 10000731 | - | CRES | 416 | 1/2" | DIA | TYPE 416SS OR 416SE COND. H | |
| 10000732 | - | CRES | 416 | .2490-.2495 | DIA | TYPE 416 OR 416SE COND. H | |
| 10000733 | - | Steel | 4140 | 1" | DIA | ASTM-A-331 GRADE 4140 | |
| 10000734 | - | Bronze | BRONZE, PHOSPHOR | .114 | DIA | CABRA #510 1/4 HARD TEMP. MS 432-2 TYPE 2 | |
| 10000735 | - | Brass | BRASS 270 | .114 | DIA | CABRA #270 1/4 HARD TEMP. MS 431-2 TYPE 2 | |
| 10000736 | - | Copper | COPPER, OXYGEN FREE | .114 | DIA | CABRA #102 1/2 HARD TEMP. MS 430-3 TYPE 2 | |
| 10000737 | - | Bronze | BRONZE, JEWELRY | .114 | DIA | CABRA #226 1/4 HARD TEMP. MS 432-3 TYPE 2 87.5% | |
| 10000738 | - | Aluminum | 6061 | 3/8" x 3 13/32 | T x SQ | ALUMINUM PLATE 6061-T6 | |
| 10000739 | - | CRES | 303 | .3735/.3730 | DIA | ASTM A582 TYPE 303 COND. A | |
| 10000740 | - | CRES | 302 | .010" x 1" | T x W | HARD SPRING TEMP. SLIT EDGE ANNEALED MS 212-2 TYPE 3 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------------|-----------------|------------|--|-------|
| 10000741 | - | Steel | 12L14 | 2 7/8" | DIA | AISI TYPE C12L14 STEEL ROUND LEADED GOLD FINISHED | |
| 10000742 | A | Copper | COPPER | 1 1/8 | DIA | PER ASTM B187 TEMPER 060 | 80251 |
| 10000743 | - | Misc | LEDLOY | 1 1/4 | DIA | QQ-S-637 DF STEEL LEDLOY AX | |
| 10000744 | - | Aluminum | 6061 | 1.750" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10000745 | - | Copper | COPPER, OFS | .900" | DIA | ASTM B187 ALLOY NO. C10500 TEMPER H04 (HARD) | |
| 10000746 | - | CRES | 304 | 3.500" x .250" | OD x WALL | TUBING SEAMLESS STAINLESS COLD DRAWN | |
| 10000747 | - | Iron | SILICON CORE IRON | 3" | DIA | IAW B190000380 | |
| 10000748 | - | Steel | STEEL, COLD ROLLED | 1/32" x 4" | T x W | 55-75 HRB 30/45 MICRO" SURF. FIN. FOR ZINC PHOS. PS 230 | |
| 10000749 | - | CRES | 416 | .980-.984" | DIA | TYPE 416 OR 416SE COND. H | |
| 10000750 | - | CRES | 416 | .3546/.3542 | DIA | TYPE 416 COND. H RC 28-38 S.S. ROD | |
| 10000751 | - | Misc | LEDLOY | 1 1/8 | DIA | LEAD LOY AX SIZE 35 ROTOR CORE | |
| 10000752 | - | Aluminum | 6061 | 1 7/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 | |
| 10000753 | - | Steel | STEEL, COLD ROLLED | 1/32" x 2 1/4" | T x W | COLD ROLL SHT SLIT EDGE COMMERCIAL QTY. 0-321025-00 | |
| 10000754 | - | CRES | 416 | .1860" - .1855" | DIA | ASTM-A582/A582M COND H | |
| 10000755 | A | CRES | 17-4 PH | .1860-.1855" | DIA | SAE AMS5643, OR SAE AMS5604, CONDITION H1075 PER SAE AMS2759/3 | 85770 |
| 10000756 | A | Aluminum | 2024 | 1 1/16 | DIA | SAE AMS-QQ-A-225/6 TEMPER T4 OR SAE AMS-QQ-250/4 | 83660 |
| 10000757 | - | Brass | BRASS 360 | 0-340106-03 | BAL. STRIP | CONTROL DRAW/VC/301/MS 401-1 TYPE 41/D893731-01,02 | |
| 10000758 | - | CRES | 416 | .2502-.2499 | DIA | GROUND FROM 10000031 | |
| 10000759 | - | Misc | LEDLOY | 5/16" | DIA | LEDLOY AX | |
| 10000760 | - | CRES | 416 | .3100/.3097 | DIA | ASTM A555, ASTM A581 COND. A PROJECT 70 BRINNEL .187/.212 | |
| 10000761 | - | Misc | LAMINATION | | | MATERIAL FOR C552 002 529 LAMINATION | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|------------------------|------------------------------|---------|--|-------|
| 10000762 | - | Bronze | BRONZE, PHOSPHOR | .0585-.0655" x .230-.250" | T x W | CABRA #510 ANNEALED 0.050 MM GRAIN MS 412-1 TYPE 1 | |
| 10000763 | - | Brass | BRASS 268 | .0585-.0655" x .230-.250" | T x W | CABRA #268 ANNEALED 0.050 MM GRAIN MS 411-1 TYPE 7 | |
| 10000764 | - | Copper | COPPER, OXYGEN FREE | .0585-.0655" | T | CABRA #102 COLD ROLLED STRIP 1/2 HARD MS 410-3 TYPE 2 | |
| 10000765 | - | Bronze | BRONZE, JEWELRY | .0585-.0655" x .230-.250" | T x W | CABRA #226 ANNEALED 0.050 MM GRAIN MS 412-2 TYPE 7 | |
| 10000766 | A | Nickel Iron | NICKEL IRON 49 | 1 3/8" | DIA | IAW Y202A014-101, -102, OR -105 OR MIL-N-14411 COMP.3 | 75768 |
| 10000767 | - | Iron | SILICON CORE IRON | 1 3/8" | DIA | IAW B190 000380 CLASS 1 | |
| 10000768 | - | Aluminum | 2024 | 2 1/16" | DIA | AMS-QQ-A-225/6 T351 EXCEPT IN MILL RUN QTY USE 10000698 | |
| 10000769 | - | Steel | 1018 | 2 1/16" | DIA | COLD FINISHED ROUND MS 200-3 TYPE 1 | |
| 10000770 | - | Steel | 1015 | 1.750" x 1.125" | OD x ID | STEEL MS 220-3 TYPE 2 | |
| 10000771 | - | CRES | 304 | 1.625" x 1.125" | OD x ID | AMS-T-8506 TUBING OR ASTM A511 GRADE MT304 | |
| 10000775 | - | CRES | 416 | 9/16" | DIA | ASTM-A582 TYPE 416 OR 416SE COND T | |
| 10000776 | - | Misc | LEDLOY | 9/16" | DIA | LEDLOY SUPER TULL | |
| 10000777 | - | Aluminum | 2024 | 2 1/4" | DIA | AMS-QQ-A-225/6 TEMPER T4 | |
| 10000778 | - | CRES | 416 | .2502"-.2499" | DIA | TYPE 416 COND H | |
| 10000779 | - | Misc | LEDLOY | 21/32" | DIA | C-1113 .099±.001 NOW .097±.002 PER R/N 100257 LEDLOY AX | |
| 10000780 | - | CRES | 416 | | | OBSOLETE SEE 10000534 | |
| 10000782 | - | CRES | 416 | 2.250" | DIA | QQ-S-764 COND. A | |
| 10000783 | - | Copper | COPPER | 2 7/8" | DIA | COPPER 206 COND HARD FOR #A343A039 RETAINER | |
| 10000784 | - | Copper | BERYLLIUM | 2 3/8" | DIA | ASTM B196 OR B197 OR B194 ASTM B196 COND HARD A333A145 | |
| 10000785 | - | Misc | BERYLLIUM | 3" | DIA | BERYLLIUM, B101 001 009 GRADE 11 #A333A143-01 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------------|---------------------------------|--------|--|-------|
| 10000786 | A | Misc | TITANIUM 6AL4V | 2 1/2" | DIA | AMS 4928 ANNEALED | 76719 |
| 10000787 | - | Aluminum | 2024 | 2" | DIA | FOR END BELL C554 002 865 & 864 T-4 | |
| 10000788 | - | Iron | IRON | 2 5/8 | DIA | VACUMET CONSUMET PURE IRON SPECIAL ENG. EVAL. | |
| 10000789 | - | Steel | STEEL T-908 | .010" ±.001" x 1.1875" | T x W | TEMPER #1 C500002141&150 IN STOCK AT ESTUL TOOL 7 MFG | |
| 10000790 | B | Aluminum | 6061 | 1 5/16 | DIA | T6 OR T651 IAW SAE AMS 4117 OR ASTM B211 OR ASTM B221 | 87206 |
| 10000791 | - | Aluminum | 6061 | 7/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10000792 | - | Brass | BRASS | .156-.159" ID x .500-.503 ID | DIA | WITH .285 DIA SPRING HOLE | |
| 10000793 | - | Aluminum | 2024 | 2 1/2" x 2 1/2" | SQ | AMS-QQ-A-225/6 TEMPER T361 | |
| 10000794 | - | Aluminum | 2011 | 9/32 | DIA | ALUMINUM PER MS 404-3 TYPE 1 T-3 | |
| 10000795 | - | Aluminum | 1100 | 1 1/2" | DIA | AMS-QQ-A-225/1 OR ASTM B211 TEMPER F | |
| 10000796 | - | Aluminum | 2024 | 1 7/16" | DIA | AMS-QQ-A-225/6 TEMPER T351 FOR C553013061 | |
| 10000797 | - | Aluminum | 2024 | 4 23/32" | DIA | ALUMINUM 2024-T351 FOR D636305-02 | |
| 10000798 | - | Nickel | TEMP COMPENSATOR 31 | | | NICKEL IRON 31% | |
| 10000799 | - | Aluminum | ALUM | .040" x 2.750" | T x W | MS 414-2 TYPE 2 D630 175 03 | |
| 10000801 | - | Steel | 1141 | .1877/.1874 | DIA | C-1141 STEEL FREE CUTTING | |
| 10000802 | - | Misc | TEFLON | .250 | DIA | ASTM D1710 | |
| 10000803 | - | Steel | SILICON STEEL, M19 | .018" ±.001 | T | FULLY PROCESSED M19 TYPE C5 CORE PLATE | |
| 10000804 | - | CRES | 416 | .843/.842 | DIA | ASTM A484 & ASTM A582 CRES CLASS 416 COND. A | |
| 10000805 | - | CRES | 302 | .032" ±.002 x .431±.003 | T x W | AST, A240, ASTM A666, ASTM A693 CRES CLASS 302 COND A | |
| 10000806 | - | CRES | 303 | .1860-.1857 | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|--------------------|--------------------|--------|---|-------------------|
| 10000807 | - | Iron | IRON | 11/16" | DIA | CARPENTER ELECTRICAL IRON Y117A017-102 | |
| 10000809 | - | CRES | 416 | 1" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000810 | - | CRES | 416 | 1 1/2" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000811 | - | CRES | 416 | 3/16" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. H | |
| 10000812 | - | CRES | 416 | .1760/.1757 | DIA | CENTERLESS GRD. STAINLESS STEEL ROD FROM 10000811 | |
| 10000813 | - | Copper | COPPER, ETP | .014"±.002 x 1 3/4 | T x W | TYPE ETP 1/2 HARD ASTM B-152 TYPE ETP | |
| 10000814 | - | Steel | STEEL, COLD ROLLED | .093" x 3.500" | T x W | COLD ROLLED STRIP STOCK PER MS-210-1 TYPE 4 | |
| 10000815 | - | Aluminum | 380 | | INGOT | QQ-A-591 ALLOY 380 ALUM USED FOR DIE CASTING | |
| 10000816 | - | Iron | IRON | 15/16 | DIA | INGOT IRON DIEHL NO. D320 601-09 | |
| 10000817 | - | CRES | 416 | 2 3/8" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. A | |
| 10000818 | - | CRES | 303 | 1/2" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000819 | - | Nickel Iron | NICKEL IRON 49 | 3/4" | DIA | Y202A014-201, -202, OR -205 | |
| 10000820 | E | Nickel Iron | NICKEL IRON 49 | 5/8" | DIA | ASTM A753 ALLOY TYPE 2 | 83154 9/4/2012 |
| 10000821 | - | Aluminum | 2024 | 7/16" | DIA | AMS-QQ-A-225/6 TEMPER T4 | |
| 10000822 | - | CRES | 416 | 1 1/16" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000823 | A | Nickel Iron | NICKEL IRON 49 | 1 1/8" | DIA | ASTM A753 ALLOY TYPE 2 (CARPENTER 49) | 87301 |
| 10000824 | - | CRES | 416 | 15/16" | DIA | TYPE 416 OR 416SE COND. A IAW ASTM A582/A582M | |
| 10000825 | - | CRES | 416 | 1/8" | DIA | TYPE 416 COND. H IAW ASTM A582/A582M | |
| 10000828 | - | CRES | 416 | 11/16" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. H | |
| 10000829 | - | CRES | 416 | .6820/.6815 | DIA | AISI 416 C'LESS GRD. FROM 10000828 | |
| 10000830 | - | Steel | STEEL, COLD ROLLED | .093" x 2 9/16" | T x W | STOCK COMMERCIAL QTY. PER MS 210-1 TYPE 4 STEEL | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|---------------------|----------------------------------|-----------|--|-------|
| 10000831 | - | Nickel Iron | NICKEL IRON 33 | .015" x 1 1/4" | T x W | NICKEL IRON COIL 33% | |
| 10000832 | - | Steel | 1113 | 3/16" | DIA | AISI B-1113 STEEL COLD DRAWN PER MS-200-1 TYPE 1 | |
| 10000833 | - | CRES | 416 | 3/4" | DIA | ASTM-A582 TYPE 416 COND A | |
| 10000834 | - | Brass | BRASS 360 | 1 1/16" | DIA | ASTM B16 TEMPER H02 (1/2 HARD) | |
| 10000835 | - | CRES | 416 | 11/16" x 19/32" | OD x ID | TYPE 416 COND A TUBING | |
| 10000836 | - | CRES | 416 | 1 1/4" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000837 | - | Brass | BRASS 360 | 7/16" | DIA | ASTM B16 TEMPER H02 (1/2 HARD) | |
| 10000838 | - | CRES | 416 | .2790-.2795" | DIA | TYPE 416 OR 416SE COND. H | |
| 10000839 | - | CRES | 416 | 1/8" | DIA | TYPE 416 OR 416SE COND. A | |
| 10000840 | - | Iron | IRON | .031"±.002 x 1" | T x W | | |
| 10000841 | - | CRES | 302 OR 304 | .0162" x 1" | T x W | 302/304 TYPE C.R. MS 212-2 TYPE 4 STRIP STOCK | |
| 10000842 | - | Aluminum | 2024 | 5" | DIA | AMS-QQ-A-225/6 TEMP T351 ALUM 2024 | |
| 10000843 | - | Misc | DENSALLOY | 1.200"±.030 x .500+.05-0 | DIA x L | DENSALLOY | |
| 10000844 | - | Steel | STEEL, COLD ROLLED | .125" x 1.000" | T x W | C.R. STEEL STRIP | |
| 10000845 | - | Steel | 1215 | 2 3/8" | DIA | A108 GRADE 1215 | |
| 10000846 | - | Plastic | FIBER TUBING | 1.900 +/- .125 x 1.500 +0/- .250 | OD x ID | VULCANIZED FIBER TUBING ASTM D710 | |
| 10000847 | - | Brass | BRASS 330 | 2.3750" x .065" | OD x WALL | ASTM B135 ALLOY C33000 TEMPER 050 | |
| 10000849 | - | Brass | BRASS 360 | 1 1/2"±.0025 | DIA | BRASS ROD SAE NO. 72 | |
| 10000850 | A | Steel | STEEL, COLD ROLLED | .500 +/- .007 X .093 +/- .007 | WXT | COMM. CR SHEET STEEL | 76852 |
| 10000851 | - | Copper | COPPER, OXYGEN FREE | .125" x .625" | T x W | ASTM-B152 TYPE C10200 TEMPER H02 | |
| 10000852 | - | CRES | 302 | .062" x 7/8" | T x W | AISI 302 ST. STEEL STRIP PER MS 212-2 TYPE 2 | |
| 10000855 | - | Steel | 1018 | 5/16" | DIA | ASTM A108 GRADE 1018 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------------|---------------------|----------------|--|------|
| 10000856 | - | Bronze | BRONZE | 1.062 ±.003 | DIA | TOBIN BRONZE COLD DRAWN MS 402-3 TYPE 2 | |
| 10000857 | - | Iron | SILICON CORE IRON | 3 1/4" | DIA | IAW B190000380 | |
| 10000858 | - | Steel | STEEL, COLD ROLLED | 1/16" x 2 11/16" | T x W | STRIP STOCK COMM. COLD ROLLED STEEL | |
| 10000859 | - | Copper | COPPER, ETP | .062" x 1 3/8" | T x W | AISI B152 TYPE ETP COPPER COLD ROLLED MS 410-1 TYPE 1 | |
| 10000860 | - | CRES | 416 | .2501/.2499" | DIA | TYPE 416 OR 416SE COND. H | |
| 10000861 | - | Aluminum | 2024 | 1" | T | FLAT ALUMINUM 2024 STOCK | |
| 10000862 | - | Iron | SILICON CORE IRON | 2 3/16" | DIA | SILICON CORE IRON B FM PER B190000380 | |
| 10000863 | - | Misc | MONEL | 7/8" | DIA | QQ-N-286 ALLOY 502 CLASS B FOR B333001560 | |
| 10000864 | - | CRES | 416 | 1" x 1" | SQ | CLASS 416 COND A AISI 416 ST. ST. | |
| 10000865 | - | CRES | 416 | 11/16 x .590 x .049 | OD x ID x WALL | ASTM A484,ASTM A582 CRES TYPE 416 TUBING | |
| 10000866 | - | Steel | 4140 | 9/16" | DIA | AISI TYPE 4140 STEEL COLD DRAWN REF MS 203-2 TYPE 1 | |
| 10000867 | - | Steel | 1018 | 2 1/8 | DIA | QQ-S-634 C1018 | |
| 10000868 | - | CRES | 416 | .0628/.0626 | DIA | ASTM A484 OR 582 CRES TYPE 416 PREHARDENED TO RC 28-38 | |
| 10000869 | - | Plastic | PLEXIGLASS | 1/8" x 2" | T x W | ACRYLIC STRIP PLEXIGLASS BEST COMMERCIAL QTY. | |
| 10000870 | - | CRES | 302 | .078"±.007 x 3/8" | T x W | ASTM A240, ASTM A666, ASTM A693 CRES FED SPEC CLASS 4 COND A AISI TYPE 302 | |
| 10000871 | - | Plastic | PLASTIC | 1 3/8" x 7/32" | OD x WALL | TUBING CONFORMING TO MIL-P-18177 FED TYPE GEE NEMA G10 | |
| 10000872 | - | CRES | 416 | .1249/.1246" | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND T | |
| 10000873 | - | Steel | 1010 | 2 5/8" | DIA | QQ-S-634 C1010 | |
| 10000874 | - | Brass | BRASS 360 | 1 1/4" | DIA | BRASS ROD S.A.E. #72 REF MS 401-1 TYPE 1 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|--------------------|-----------------------------|-----------|---|-------|
| 10000875 | - | Steel | 1018 | 3.875 x .375 | OD x WALL | ASTM-A108 GRADE 1018 | |
| 10000877 | - | CRES | 416 | .3760/.3757 | DIA | ASTM A484 & ASTM A582 CRES FED SPEC CLASS 416 COND A RC 28-38 | |
| 10000878 | - | Aluminum | 2024 | 2.000" x .083" | OD x WALL | ALUMINUM TUBING 2024 T3 | |
| 10000879 | A | Nickel Iron | HY MU 80 | 1" | DIA | ASTM A 753 ALLOY TYPE 4 (HYMU 80) | 83822 |
| 10000880 | - | Nickel Iron | HY MU 80 | 9/16" | DIA | Y059A005-236 | |
| 10000881 | - | Nickel Iron | HY MU 80 | 1 1/16" | DIA | Y059A005-236 | |
| 10000882 | - | Steel | SILICON STEEL, M19 | .018" x 2 7/8" | T x W | STRIP MATERIAL M-19-C5 CORE PLATE | |
| 10000883 | - | Steel | 1018 | .250"±.005 | SQ | C1018 STEEL | |
| 10000884 | - | CRES | 416 | .6250-.6247 | DIA | TYPE 416 COND. H OR 416SE COND. H | |
| 10000885 | - | Aluminum | 2024 | 1/8" | DIA | ALUMINUM ROD 2024-T4 | |
| 10000886 | - | CRES | 416 | .5097/.5100 | DIA | GRD. FROM 17/32 10000040 AISI 416 28-38 D4 OP. #23 | |
| 10000887 | - | CRES | 303 | .4995-.5000" | DIA | ASTM A582 TYPE 303 COND A | |
| 10000888 | - | Aluminum | 2024 | 4" | DIA | ALUMINUM BAR 2024 T351 | |
| 10000890 | - | CRES | 416 | .3140/.3155 | DIA | C'LESS GRD. FROM 10000668 D4-OPER #80 AISI 416 26-32 | |
| 10000891 | - | Aluminum | 6061 | 9/16 | DIA | AMS-QQ-A-225/8 OR ASTM B211 ALUM 6061-T6 | |
| 10000892 | - | Aluminum | 6061 | 1 3/8 x 1 3/8 | SQ | ALUMINUM BAR 6061-T651 | |
| 10000893 | A | CRES | 416 | 2" | DIA | ASTM A582/A582M COND. H | 86529 |
| 10000894 | - | CRES | 416 | 1" | DIA | TYPE 416 COND H | |
| 10000895 | - | CRES | 416 | 1/2 x 1 1/2 x 2 1/2 +1/32-0 | T x W x L | TYPE 416 COND A CRES STOCK THICK PLATE | |
| 10000896 | - | CRES | 416 | 1/8 x 1 1/2 x 2 1/2 +1/32-0 | T x W x L | TYPE 416 COND A CRES STOCK THICK STRIP | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|---------------------|-------------------------|-----------|---|------|
| 10000897 | - | Steel | 1018 | 1 9/16" | DIA | QQ-S-634 1018 | |
| 10000898 | - | CRES | 303 | .3527/.3530 | DIA | ASTM A-582 COND A, C'LESS GRD FROM 10000274 TYPE 303 | |
| 10000899 | - | Steel | 1018 | 1 1/8" | DIA | ASTM A108 GRADE 1018 | |
| 10000900 | - | Aluminum | 2024 | 1 3/8" | DIA | AMS-QQ-A-225 ALUM 2024-T351 | |
| 10000901 | - | Steel | 4140 | 1 1/2" | DIA | STEEL ROD 4140 NOC #26575 | |
| 10000902 | - | Aluminum | 6061 | 2 1/2" | SQ | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10000903 | - | Nickel Iron | HY MU 80 | 2 3/16" | DIA | HY-MU 80/Y059A005-236 FOR A314A048 GRYOFLEX HSG | |
| 10000904 | - | CRES | 17-4 PH | 1 1/4" | DIA | AMS-5643 COND H1075 | |
| 10000905 | - | CRES | 17-4 PH | 1 3/8" | DIA | ARMCO 17-4PH | |
| 10000906 | - | CRES | 17-4 PH | 5/8" | DIA | AMS-5643 COND. H1075 | |
| 10000907 | - | CRES | 17-4 PH | 1 1/2" | DIA | ARMCO 17-4PH RC 28-37 COMMERC. C'LESS GRD | |
| 10000908 | - | CRES | 17-4 PH | 2 1/8" | DIA | AMS 5643 COND H1150 | |
| 10000909 | - | Steel | 4140 | 1 1/8" | DIA | MIL-S-5626 COND F2, HT TO 29-33 HRC | |
| 10000911 | - | CRES | 17-4 PH | 2 7/16" | DIA | AMS 5643 COND A MIL-H-6875 HEAT TREAT COND H1150 | |
| 10000912 | - | Bronze | BRONZE, PHOSPHOR | 1/2" | DIA | ASTM B139 ALLOY C51000 TEMPER H04 (HARD) | |
| 10000913 | - | Bronze | BRONZE, PHOSPHOR | 3/4" | DIA | ASTM B139 COMP. B C54400 | |
| 10000914 | - | Bronze | BRONZE, PHOSPHOR | .015" x 1.250" x 10' | T x W x L | ASTM B139 COMPSN-A TEMPER SPRING ASTM B103 | |
| 10000915 | - | Steel | 4140 | 1 1/2" | DIA | MIL-S-5626 B2 HT RC29-33 OR LASALLE TYPE EDD 15o STEEL | |
| 10000916 | - | Misc | TEFLON | 2 3/16" | DIA | TEFLON BAR | |
| 10000917 | - | Misc | TEFLON | 1 5/8" | DIA | ASTM D1710 | |
| 10000918 | - | Misc | TEFLON | 1/8" | T | TEFLON SHEET | |
| 10000919 | - | Nylon | NYLON | 3/8" | DIA | NYLON BAR | |
| 10000920 | - | CRES | 304 | 1 1/8" x .995" | OD x ID | AMS-T-8506 SEAM;ESS TUBING CRES | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|--------------|---------|--|-------|
| 10000921 | - | Aluminum | 6061 | 2" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10000922 | - | CRES | 320 | 7/8 | DIA | ASTM A240, ASTM A666, ASTM A693 COND A FED SPEC FOR 200099255 | |
| 10000923 | - | Steel | 1018 | 2 1/4" | DIA | ASTM A108 GRADE 1018 | |
| 10000924 | - | Steel | 1015 | 2 5/8" x 2" | OD x ID | MTX1015 SEAMLESS TUBING PER ASTM A519 | |
| 10000925 | B | Aluminum | 6061 | 3/8" | DIA | T6 OR T651 IAW SAE AMS4117, ASTM B211 OR ASTM B221 | 87206 |
| 10000926 | - | Misc | MONEL | 3/4" | DIA | T6 OR T651 IAW SAE AMS4117, ASTM B211 OR ASTM B222 | |
| 10000927 | - | Steel | 1018 | 1 1/16" | DIA | ASTM A 108 C1018 | |
| 10000928 | - | Copper | COPPER, STP | 1 3/16" | DIA | COPPER PER MS400-1 TYPE 1 | |
| 10000929 | - | HY MU 80 | HY MU 80 | 1 1/2" | DIA | ASTM A753/A753M ALLOY TYPE 4 | |
| 10000930 | - | CRES | 304L | 3 5/8 | DIA | ASTM A276 304L COND A | |
| 10000931 | - | Bronze | BRONZE, PHOSPHOR | 5/8" | DIA | ASTM B139 COMP A TEMP HD PHOSPHOR BRONZE | |
| 10000932 | B | Aluminum | 6061 | 1 3/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 6061 T651 | 87207 |
| 10000933 | - | Aluminum | 6061 | 1 1/2" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10000934 | - | CRES | 416 | .2824/.2814" | DIA | AMS-QQ-S-763 COND A AISI 416 | |
| 10000935 | - | CRES | 17-4 PH | 13/16" | DIA | AMS 5643 COND H 1075 (17-4PH) | |
| 10000936 | B | Aluminum | 6061 | 5/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER 6061- T651 | 87206 |
| 10000937 | A | Steel | 1018 | 1 3/8" | DIA | ASTM A108 GRADE 1018 | 79123 |
| 10000938 | B | Aluminum | 6061 | 1 1/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | 87206 |
| 10000939 | - | CRES | 303 | 4 15/16" | DIA | ASTM-A582 TYPE 303 COND A CRES | |
| 10000940 | - | CRES | 303 | 2 7/16" | DIA | ASTM-A582 TYPE 303 COND A | |
| 10000941 | - | CRES | 303 | 5 1/8" | DIA | ASTM-A582 TYPE 303 COND A | |
| 10000942 | - | CRES | 303 | 2 1/8" | DIA | ASTM A582 TYPE 303 OR 303SE COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------------|----------------|-----------|--|-------|
| 10000943 | - | CRES | 416 | 1 7/8" | DIA | TYPE 416 COND. A OR 416SE COND. A | |
| 10000944 | - | CRES | 416 | 6" | DIA | ASTM-A582 TYPE 416 COND A | |
| 10000945 | - | CRES | 416 | 2 7/8" | DIA | ASTM-A582 TYPE 416 COND A | |
| 10000946 | - | Aluminum | 6061 | 2 1/2" x .125" | OD x WALL | ALUMINUM TUBING 6061-T6 | |
| 10000947 | - | CRES | 303 | .3720-.3717 | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000948 | - | Aluminum | 6061 | 2 1/2" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER 6061-T651 | |
| 10000949 | - | CRES | 410 | 1 3/4" | DIA | AMS-QQ-S-763 CLASS 410 COND. A | |
| 10000950 | - | Aluminum | 6061 | 15/16" | DIA | AMS-QQ-A-225/8 OR ASTM B211 T651 | |
| 10000951 | B | Nickel Iron | HY MU 80 | 3/4" | DIA | ASTM A753 ALLOY 4 IAW Y059A005-23X or -24X TABLE V EXCEPTIONS: PERMEABILITY @ 40 GAUSS, MAX COERCIVE FORCE (Hc) FROM 5Kg MANUFACTURE CARPENTER ONLY | 91383 |
| 10000952 | A | Misc | TITANIUM 6AL4V | 1 1/8" | DIA | AMS 4928 ANNEALED | 76719 |
| 10000954 | - | CRES | 17-4 PH | .4335/.4330 | DIA | CRES AMS-5643 COND. H-1025 (17-4PH) | |
| 10000955 | - | Misc | LEDLOY | 1 7/8" | DIA | RYERSON LEDLOY AX C.R.S. | |
| 10000956 | - | Aluminum | 2024 | 1.660" x .140" | OD x WALL | TUBING WW-T-700/3 TEMPER T4 ALUMINUM | |
| 10000957 | - | Cobalt | COBALT 49% | 1 1/4" | DIA | COBALT 49% Y117A004101 VANADIUM PERMENDUR ALLEG LUDLUM | |
| 10000958 | - | CRES | 17-4 PH | 1 7/8" | DIA | AMS 5643 SOLUTION ANNEALED COLD FINISH 17-4PH | |
| 10000959 | - | CRES | 17-4 PH | .5410-.5415 | DIA | AMS-5643 COND. H 1075 | |
| 10000960 | - | CRES | 17-4 PH | 1" | DIA | AMS-5643 COND H1075 | |
| 10000961 | - | CRES | 17-4 PH | 1 3/8" | DIA | AMS 5643 SOLUTION ANNEALED COLD FINISH 17-4PH STAINLESS STEEL | |
| 10000962 | - | CRES | 303 | 1 7/8" | SQ | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10000963 | - | Iron | SILICON CORE IRON | 1 7/8" | DIA | SILICON CORE IRON B-FM B190000380 CLASS 1 H.R. | |
| 10000965 | - | Cobalt | COBALT 49% | 7/8" | DIA | 49% COBALT Y117004-101 VANADIUM PERMENDUR ALLEG. LUDLUM | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------------|-----------------|---------|--|-------|
| 10000966 | - | Cobalt | COBALT 49% | 1 5/8" | DIA | 49% COBALT Y117A004-101 VANADUM PERMENDUR ALLEG LUDLUM | |
| 10000967 | B | Iron | SILICON CORE IRON | 2 1/8" | DIA | IAW B190000380 B-FM | 78404 |
| 10000968 | - | Aluminum | 2024 | 2 5/16" | DIA | AMS-QQ-A-225/6 ALUM 2024T-351 | |
| 10000969 | - | Iron | SILICON CORE IRON | 1 1/4" | DIA | SILICON CORE IRON 9-FM B190000380 CLASS 1 H.R.(10000767) | |
| 10000970 | - | Cobalt | COBALT 49% | 7/8" | DIA | Y117A004-103 | |
| 10000971 | A | Cobalt | COBALT 49% | 1 1/4" | DIA | ASTM 801 ALLOY 1 | 86772 |
| 10000972 | - | Cobalt | COBALT 49% | 1 5/8" | DIA | 49% COBALT Y117A004-103 PER EMI #52700 | |
| 10000973 | - | Iron | SILICON CORE IRON | 1 5/8" | DIA | SILICON IRON IAW B190000380 | |
| 10000974 | - | CRES | 416 | 7/8" | DIA | 416 OR 416SE S/S ASTM-A582 COND. H | |
| 10000975 | - | CRES | 416 | 2" | DIA | ASTM-A582 TYPE 416 COND. T OR 416SE COND. T | |
| 10000976 | - | Aluminum | 2024 | .156" | DIA | ALUMINUM 2024 T4 | |
| 10000977 | - | CRES | 416 | 13/16" | DIA | TYPE 416 COND. A OR 416SE COND. A | |
| 10000978 | - | Iron | SILICON CORE IRON | 2 1/4" | DIA | SILICON CORE IRON 49FM | |
| 10000979 | - | Cobalt | COBALT 49% | 15/16" | DIA | 49% COBALT Y117A004-101 | |
| 10000980 | - | CRES | 416 | .3145-.3130" | DIA | TYPE 416 COND. H OR 416SE COND H | |
| 10000981 | - | Iron | SILICON CORE IRON | 1 1/2" | DIA | SILICON CORE IRON B-FM B190000380 CLAS D H.R. | |
| 10000982 | - | CRES | 17-4 PH | .7498/.7495 | DIA | STAINLESS SOLUTION ANNEALED COLD FINISH 17-4PH | |
| 10000983 | - | CRES | 17-4 PH | 3/4" | DIA | AMS 5643 17-4PH SOLUTION ANNEALED COLD FINISH | |
| 10000984 | - | Aluminum | 6061 | 1" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10000985 | - | CRES | 416 | 1 1/4" x 1.010" | OD x ID | CLASS 416 COND A TUBING AISI 416 | |
| 10000986 | - | CRES | 17-4 PH | 1 3/8" | DIA | AMS 5643 17-4PH ST'LESS COND H | |
| 10000987 | - | CRES | 304 | 1" | DIA | ASTM-A276 TYPE 304 COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|--------------------------------------|--------------|---|------|
| 10000988 | - | Nickel Iron | NICKEL IRON 49 | .330/.340 | DIA | 49FM ROD 375 022 182 | |
| 10000989 | - | Aluminum | 1100 | 1/2" | DIA | AMS-QQ-A-225/1 OR ASTM B211 ALUMINUM | |
| 10000990 | - | Steel | 1020 | .010"±.001 x.719"x 3 1/8"±.010 | | QQ-S-636 COND 1020 FED. SPEC. | |
| 10000991 | - | CRES | 416 | .2498-.2496 | DIA | ASTM A582/A582M TYPE 416 COND. H OR 416SE COND. H | |
| 10000992 | - | | | | | USE 10000044 SAME MATERIAL | |
| 10000993 | - | Steel | 12L13 | 5/8" | DIA | 12L13 STEEL | |
| 10000994 | - | Steel | 1018 | 2 1/8" x 1 3/8" | OD x ID | 1018 TUBING | |
| 10000995 | - | CRES | 416 | 15/16" | DIA | TYPE 416 OR 416SE COND. H | |
| 10000996 | - | Aluminum | 6061 | 1.660" x .140" | OD x WALL | ALUMINUM TUBING 6061 T6 | |
| 10000997 | - | CRES | 303 | .2790-.2787" | DIA | ASTM-A-582/A 582M TYPE 303 OR 303SE COND. A | |
| 10000998 | - | CRES | 410 | 1 1/8 | DIA | AMS 5613 RD-RC 26-32 | |
| 10000999 | - | Aluminum | 2024 | 1 9/16" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001000 | - | CRES | 416 | .1877/.1874 | DIA | TYPE 416 COND T | |
| 10001002 | - | Misc | MONEL | 1.000" | DIA | QQ-N-286 MONEL-CLASS B ALLOY 502 FOR B333001560 | |
| 10001003 | - | CRES | 303 | .3115/.3110 | DIA | GROUND FROM 10000131 | |
| 10001004 | - | Steel | 1095 | .125/.124 | DIA | C1095 ROD | |
| 10001005 | - | CRES | 416 | .3905-.3900 | DIA | TYPE 416 OR 416SE COND. H | |
| 10001006 | - | CRES | 416 | .4970/.4967 | DIA | CRES ASTM A581/A581M TYPE 416 COND A HARDNESS RANGE 17-24 RC | |
| 10001007 | - | CRES | 410 | 1 1/2" | DIA | CRES AMS 5613 TYPE 410 SS ROD RC 26-32 | |
| 10001009 | - | CRES | 416 | .6000/.5995 | DIA | TYPE 416 COND. H | |
| 10001010 | - | CRES | 304 | 1.875" x 1.685" | OD x ID | CRES ASTM A269 OR A511 TUBING AISI 304 ANNEALED | |
| 10001011 | - | CRES | 303 | 2 3/4" | DIA | CRES ASTM A582 TYPE 303 COND A | |
| 10001012 | - | CRES | 303 | 3 1/2" | DIA | CRES ASTM A582 TYPE 303 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------------|------------------------|------------|--|------|
| 10001013 | - | CRES | 304L | 3-3/4 X 1-5/8 +/- 1/16 | D X L SLUG | ASTM A276 304L COND A | |
| 10001014 | - | CRES | 416 | .1249/.1247 | DIA | CRES ASTM A581/A581M TYPE 416 COND H | |
| 10001015 | - | CRES | 416 | 1 1/2" | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND A | |
| 10001016 | - | CRES | 303 | .2812/.2807 | DIA | ASTM A581 TYPE 303 COND A | |
| 10001017 | - | Aluminum | 6061 | 1.625" ±.010 | SQ | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 ALUM. BAR | |
| 10001018 | - | CRES | 416 | 1/2" | DIA | TYPE 416 COND H | |
| 10001019 | - | CRES | 303 | .1571/.1568 | DIA | ASTM A581/A581 M TYPE 303 CRES COND A C'LESS GRD. / 10000293 | |
| 10001020 | - | Aluminum | 6061 | 1.750" ±.010 | SQ | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 6061 ALUM BAR | |
| 10001021 | - | Aluminum | 6061 | 2.000" ±.005 | SQ | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001022 | - | Steel | 1141 | 1/4" | DIA | AISI 1141 | |
| 10001023 | - | CRES | 303 | .5625"-.5620" | DIA | ASTM A582 TYPE 303 OR 303 SE COND A | |
| 10001024 | - | Aluminum | 2024 | 2 3/4" | DIA | ALUMINUM 2024 T351 | |
| 10001026 | - | CRES | 17-4 PH | 3/8" | HEX | AMS-5643 SOLUTION ANNEALED COLD FINISH | |
| 10001027 | - | Aluminum | 2024 | 7/16" | HEX | AMS-QQ-A-225/6 TYPE 2024 ALLOY T351 HEX | |
| 10001028 | - | CRES | 17-4 PH | .6250" x 1.000" | T x W | CRES 17-4PH AMS 5643 SOLUTION ANNEALED COLD FINISH | |
| 10001031 | - | Cobalt | COBALT 17% | 1 3/16" | DIA | 17% COBALT ROD | |
| 10001032 | - | Steel | SILICON STEEL, M43 | .0125" x 1.437" | T x W | COIL STRIP ASTOCK 26 GAGE M43 FULLY PROCESSED | |
| 10001033 | - | CRES | 303 | 2 5/8" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10001034 | - | CRES | 17-4 PH | 5/8" x 2 1/2" | T x W | AMS 5355 17-4PH CRES STRIP COND A HEAT TREATED | |
| 10001037 | - | CRES | 304 | 1 1/8" | DIA | AMS-QQ-S-763 CLASS 304L COND A | |
| 10001038 | - | CRES | 304 | 1.000" ±.010 | SQ | CRES ASTM-A-582 CLASS 304L S.S. BAR | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|---------------|---------|---|-------|
| 10001039 | - | CRES | 304 | .2460/.2457 | DIA | AMS-QQ-S-763 COND. A ALTERNATE CLASS 321 OR 347 304L | |
| 10001040 | - | CRES | 416 | .5505/.5500 | DIA | CRES COND H RC-28-38 C'LESS GRD #10000775 | |
| 10001041 | - | Aluminum | 2024 | 5" | DIA | AMS-QQ-A-225/6 TEMPER T4 2024 | |
| 10001042 | - | Aluminum | 2024 | 3 1/2" | DIA | AMS-QQ-A-225/6 TEMPER T4 2024 | |
| 10001043 | A | Brass | BRASS 360 | 1" | DIA | (DELETE) USE 10000344 | 77051 |
| 10001044 | - | Steel | 1215 | 1/2" | DIA | CD 1215 MILD STEEL ROD | |
| 10001045 | - | CRES | 410 | .171" | DIA | AMS-QQ-S-763 CRES COND A AMS 5613 11/64" CLASS 410 | |
| 10001046 | - | Misc | INCONEL X750 | .2460"-.2457" | DIA | AMS-5667 | |
| 10001047 | - | CRES | 430 FR | 2 3/16" | DIA | Y117A020-102 CHROME-IRON BAR PER 430 FR | |
| 10001048 | - | Aluminum | 2024 | 3 1/2" x 3" | OD x ID | WW-T-700/3 TYPE 1 TEMPER T3 2024 TUBING | |
| 10001049 | - | CRES | 416 | 6" | DIA | CRES ASTM A582 COND A TYPE 416 ORDER IN 2 FT MAX LGTS | |
| 10001050 | - | Aluminum | 2024 | 3 1/4" | DIA | AMS-QQ-A-225/6 TEMPER T4 2024 | |
| 10001051 | - | CRES | 416 | 3 3/4" | DIA | CRES ASTM A582 COND A TYPE A ORDER IN 5- 6 FT MAX LTS | |
| 10001052 | - | CRES | 303 | 5" | DIA | CRES ASTM A582 TYPE 303 COND A ORDER IN 3 FT MAX LTS | |
| 10001053 | - | Aluminum | 2024 | 4" | DIA | AMS-QQ-A-225/6 TEMPER T4 2024 | |
| 10001054 | - | Steel | 52100 | 5/8" | DIA | MIL-S-980 CLASS I (E52100) OR AMS 6440 | |
| 10001055 | - | CRES | 316 | 5/16" | DIA | CRES ASTM A 581/A581M TYPE 316 COND A HARDNESS RC 30 MIN | |
| 10001056 | - | CRES | 416 | 3 1/8" | DIA | CRES ASTM A582 TYPE 416 COND A 7 FT MAX BAR LGTS | |
| 10001057 | - | CRES | 416 | 4" | DIA | CRES ASTM A582 TYPE 416 COND A 5FT MAX NOC 35907 | |
| 10001058 | - | CRES | 416 | 3" | DIA | CRES ASTM A582 TYPE 416 COND A 8FT MAX BAR LTS | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------|----------------|-----------|--|-------|
| 10001059 | - | Aluminum | 6061 | 1 1/2" x .125" | OD x WALL | ALUM. TUBE D6061-T6 | |
| 10001060 | - | CRES | 416 | 2 1/8" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. A | |
| 10001061 | - | CRES | 303 | .2808/.2805 | DIA | TYPE 303 COND A SS ROD C'LESS GRD FROM 10000131 | |
| 10001062 | - | CRES | 15-5 PH | 9/16" | DIA | AMS-5659 COND. A | |
| 10001063 | - | CRES | 416 | 4" | DIA | CRES ASTM A582 TYPE 416 COND A 5FT MAX BAR LENGTHS | |
| 10001064 | - | CRES | 416 | 3 5/8" | DIA | CRES ASTM A582 TYPE 416 COND A 6FT MAX BAR LENGTHS | |
| 10001065 | - | CRES | 17-4 PH | 1 1/8" | DIA | AMS-5643 SOLUTION ANNEALED COLD FINISH | |
| 10001070 | - | CRES | 416 | 2 13/16" | DIA | ASTM-A582 TYPE 416 OR 416SE COND. A (RC27 MAX) | |
| 10001072 | - | CRES | 416 | .812+/- .001 | DIA | TYPE416 OR 416SE COND H | |
| 10001073 | - | CRES | 17-4 PH | 11/16" | DIA | AMS 5643 COND H 1075 | |
| 10001074 | - | CRES | 17-4 PH | 1/2" | DIA | AMS 5643 COND H1075 | |
| 10001075 | - | CRES | 17-4 PH | 15/16" | DIA | AMS-5643 SOLUTION ANNEALED COLD FINISH | |
| 10001076 | - | Aluminum | 6061 | 3 1/2" | DIA | ASTM B241 OR ASTM B221 TEMPER 651 6061-T651 ALUM | |
| 10001077 | - | CRES | 17-4 PH | 7/8" | DIA | AMS 5643 COND. H1075 | |
| 10001078 | - | CRES | 416 | 1 5/16" | DIA | ASTM A582/A582M TYPE 416 OR 416SE COND. A | |
| 10001079 | - | CRES | 15-5 PH | .4950/.4955 | DIA | CENTERLESS GRD TO .495/.4955 FROM 10001062 | |
| 10001080 | - | Cobalt | COBALT 17% | 1 3/4" | DIA | IAW C190000208 CLASS 1 COBALT | |
| 10001081 | - | CRES | 416 | .4682"-.4677" | DIA | TYPE 416 COND H | |
| 10001082 | - | CRES | 17-4 PH | 1 9/16" | DIA | AMS 5643 SOLUTION ANNEALED COLD FINISH | |
| 10001083 | A | CRES | 416 | 1 7/16" | DIA | SAME AS 10000450 | 76247 |
| 10001084 | - | Misc | | | | FOR PART # C340 013 576 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|--------------------------|-----------|---|------|
| 10001085 | - | Aluminum | 2024 | 17/32" | DIA | AMS-QQ-A-225/6 TEMPER T4 ALUM 2024 | |
| 10001086 | - | Plastic | PHENOLIC | 1 1/2" | DIA | WOUND ROUND ROD PHENOLIC NEMA L MIL-P-15035 (BLACK) | |
| 10001087 | - | Misc | INCONEL X750 | 1/4" | DIA | AMS 5667 | |
| 10001088 | - | Aluminum | 2024 | 2 3/4" | DIA | AMS-QQ-A-225/6 TEMPER T351 ALUM 2024 | |
| 10001089 | - | Steel | 1018 | 2 3/8" x .312" | OD x WALL | STEEL TUBING GRADE 1018 CD (1 3/4 ID REF.) | |
| 10001090 | - | CRES | 303 | .3123/.3120 | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10001091 | - | Tungsten | TUNGSTEN | .125 | DIA | TUNGSTEN MIL-T-21014 TYPE 2 | |
| 10001093 | - | Plastic | ACETAL PLASTIC | 5/8" | DIA | ACETAL PLASTIC FED. SPEC L-P 392 TYPE 1 CLASS 1 | |
| 10001095 | - | Misc | DELETED | | | | |
| 10001096 | - | Steel | CARBON STEEL | .030" ±.002 x 1" | T x W | QQ-S-636 LOW CARBON STEEL STRIP SHEETS COLD ROLL | |
| 10001097 | - | CRES | 302 | .100"±.004 x 1/2" | T x W | 302 STRIP | |
| 10001098 | - | CRES | 416 | 1 1/2" | DIA | TYPE 416 COND H | |
| 10001099 | - | Aluminum | 2024 | .063" ±.003 x .625"±.010 | T x W | AMS-QQ-A-250/4 TEMPER T3 ALUM STRIP 2024 | |
| 10001100 | - | Aluminum | 2024 | 1/2" | DIA | AMS-QQ-A-225/6 TEMPER T4 | |
| 10001101 | - | CRES | 416 | 1 5/8" | DIA | TYPE 416 OR 416SE COND. H | |
| 10001102 | - | CRES | 416 | 3/4" | DIA | ASTM A582 TYPE 416 COND H | |
| 10001103 | - | Aluminum | 2024 | .250"±.005 x 4.500±.010 | T x W | AMS-QQ-A-250/4 TEMPER T251 ALUM STRIP 2024 | |
| 10001104 | - | Aluminum | 2024 | 5/8" | DIA | AMS-QQ-A-225/6 TEMPER T4 | |
| 10001105 | - | Aluminum | 2024 | 1" | DIA | AMS-QQ-A-250/4 TEMPER T4 ALUM BAR 2024 | |
| 10001106 | - | Aluminum | 2024 | .250"±.010 x 2.750±.010 | T x W | AMS-QQ-A-250/4 TEMPER T351 ALUM STRIP 2024 | |
| 10001107 | - | Nickel | TEMP COMPENSATOR 31 | .014" x 1 1/4" | T x W | CARPENTER ALLOY #31 COMPENSATING STRIP | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|---------------------------------|---------|---|------|
| 10001108 | - | Aluminum | 6061 | 1 1/2" x 1 1/2" x 1/4" | TEE | ASTM B241 OR ASTM B221 TEMPER T6 | |
| 10001109 | - | CRES | 416 | 1.625 | DIA | 416 COND A S.S. | |
| 10001110 | - | Aluminum | 6061 | 1/4" x 16±.005 | SQ x L | ALUMINUM BAR 6061-T6510 | |
| 10001111 | - | Aluminum | 2024 | .094/.086" x .500/.510" | T x W | ALUMINUM STRIPS 2024 T-3 | |
| 10001112 | - | Aluminum | 2024 | 3 1/8" | DIA | AMS-QQ-A-225/6 TEMP T351 2024 | |
| 10001113 | - | Aluminum | 2024 | .087" x 2 1/4" | T x W | ALUMINUM BAR 2024 T-6 | |
| 10001114 | - | Aluminum | 6061 | .500/.510" x 8 1/4 | T x W | ALUMINUM STRIP 6061 T651 | |
| 10001115 | - | CRES | 303 | 3 1/8" | DIA | ASTM-A582 TYPE 303 OR 303SE COND. A | |
| 10001116 | - | Aluminum | 2024 | .094/.086 x 5.650/ x 6.350/6.37 | | 2024-T3 | |
| 10001117 | - | Tungsten | TUNGSTEN | 1.439/1.437 | DIA | C'LESS GRIND MALLORY 1000 TUNGSTEN ALLOY ROD | |
| 10001118 | - | Cobalt | COBALT 36% | 3/4" | DIA | 35% COBALT STEEL, MMPA 0100 | |
| 10001119 | - | Iron | SILICON CORE IRON | .750 | DIA | B-F-M-ROD SILICON CORE IRON B190000380 | |
| 10001120 | - | Iron | IRON | 2" | DIA | Y117A017-102 | |
| 10001121 | - | CRES | 304L | 3/4" | DIA | ASTM-A-276 TYPE 304L COND. A | |
| 10001122 | - | CRES | 304L | 13/16" | DIA | AMS-QQ-S-763 TYPE 304 L COND A CRES | |
| 10001123 | - | CRES | 410 | 5/8" | DIA | SAE AMS 5613 ANNEALED | |
| 10001124 | - | Tungsten | TUNGSTEN | 3.812" x 3.032" | OD x ID | TUNGSTEN 142 TUBE, OD TOL +.010-.000, ID TOL +.000-.010 | |
| 10001125 | - | Aluminum | 2024 | 1 5/16" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001126 | - | CRES | 410 | 11/16" | DIA | AMS-QQ-S-763 CLASS 410 COND A | |
| 10001127 | - | Nickel | TEMP COMPENSATOR 32 | .015" x 1.250" | T x W | TEMP COMP 32 TYPE (USED ON C200042531 SHUNT RING) | |
| 10001128 | - | Copper | BERYLLIUM | 1.250 | DIA | QQ-C-533 ALLOY 172 1/2 HD COPPER BAR | |
| 10001129 | - | Steel | 12L15 | 2 1/8" | DIA | BARS-12L15 FREE MACHINING STEEL | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|----------------|---------------|--------|---|------|
| 10001130 | - | CRES | 15-5 PH | 2 1/4" | DIA | AMS-5659 COND H1075 | |
| 10001131 | - | Aluminum | 2024 | 1/2" x 13/16" | T x W | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001132 | - | CRES | 15-5 PH | 1 3/8" | DIA | AMS 5659 COND.A | |
| 10001133 | - | CRES | 15-5 PH | 4" | DIA | AMS-5659 COND. H1075 | |
| 10001134 | - | CRES | 15-5 PH | 3 5/8" | DIA | AMS-5659 COND. H1075 | |
| 10001135 | - | CRES | 303 | 4" | DIA | BAR CRES TYPE 303 COND A PER ASTM A582 5FT MAX BAR LTH | |
| 10001136 | - | Nickel Iron | NICKEL IRON 49 | 4 3/4" | DIA | BAR CARPENTER 49 FM 3 1/2FT MAX BAR LENGTH | |
| 10001137 | - | CRES | 416 | 3 3/8" | DIA | BAR TYPE 416 COND A PER ASTM A582 6 1/2FT MAX BAR LTH | |
| 10001138 | - | Aluminum | 2024 | 2 7/8" | DIA | AMS-QQ-A-250/4 TEMP T4 BAR ALUM 2024 | |
| 10001139 | - | Aluminum | 2024 | 1/4" | DIA | AMS-QQ-A-225/6 TEMPER T 4 | |
| 10001140 | - | CRES | 303 | .2502"-.2499" | DIA | ASTM A582 TYPE 303 COND A | |
| 10001141 | - | Misc | LEDLOY 12-15 | 1 1/8" | DIA | LEDLOY 12-15 | |
| 10001142 | - | Steel | 1141 | .1874/.1871 | DIA | C1141 FREE CUTTING STEEL BAR | |
| 10001143 | - | Aluminum | 2024 | 1" | DIA | AMS-QQ-A-250/4 TEMPER T351 ALUMINUM BAR 2024 | |
| 10001144 | - | CRES | 430F | 1 3/8" | DIA | ASTM A582 TYPE 430F COND A | |
| 10001145 | - | CRES | 416 | 1/4" x 1/4" | SQ | TYPE 416 COND H | |
| 10001146 | - | CRES | 416 | 1 1/8" | DIA | TYPE 416 OR 416SE COND. H | |
| 10001147 | - | CRES | 416 | 9/16" | DIA | ASTM A582 TYPE 416 COND A | |
| 10001148 | - | CRES | 416 | 5/8" | DIA | ASTM A582 TYPE 416 COND A | |
| 10001149 | - | CRES | 416 | 1 3/8" | DIA | ASTM A582/A582M COND. H | |
| 10001150 | - | CRES | 416 | .5000"-.4995" | DIA | TYPE 416 COND A | |
| 10001151 | - | CRES | 410 | 1 1/4" | DIA | ASTM A582/A 582 M TYPE 410 | |
| 10001152 | - | CRES | 410 | 1 3/8" | DIA | ASTM-A-276 TYPE 410 COND. T | |
| 10001153 | - | Aluminum | 6061 | 3 5/8" | DIA | ASTM B241 OR ASTM B221 ALUM 6061 T6 | |
| 10001154 | - | CRES | 416 | .2499/.2496 | DIA | ASTM A582/A582M COND. A | |
| 10001155 | - | CRES | 304 | 7/8" | DIA | CRES TYPE 304 COND L | |
| 10001156 | - | Copper | BERYLLIUM | 1 1/2" | DIA | QQ-C-553 ALLOY 172 COND TN 1/2 HARD ASTM B196 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------------|-----------------|-----------|--|-------|
| 10001157 | A | CRES | 304 | .1520/.1517" | DIA | SAE AMS-QQ-S-763 | 83862 |
| 10001158 | - | CRES | 17-4 PH | 1 13/16" | DIA | AMS-5643 COND H1075 | |
| 10001159 | - | Aluminum | 2024 | 3 1/4" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001160 | - | Iron | SILICON CORE IRON | 2 3/4" | DIA | SILICON CORE IRON B-FM PER B190 000 380 | |
| 10001161 | - | Iron | SILICON CORE IRON | 1 3/4" | DIA | SILICON CORE IRON B-FM PER B190 000 380 | |
| 10001162 | - | Aluminum | 6061 | 2 7/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001163 | - | Steel | 12L14 | 1 7/16" | DIA | C12214 COLD ROLLED STEEL | |
| 10001164 | - | CRES | 304 | .286-.276 x.040 | OD x WALL | AMS-T-8506 TUBING | |
| 10001165 | - | CRES | 410 | 1 1/8" | DIA | ASTM-A276 TYPE 410 COND. A | |
| 10001166 | A | CRES | 17-4 PH | .1249/.1246 | DIA | SAE AMS5643, OR SAE AMS5604, CONDITION H1075 PER SAE AMS2759/3 | 85772 |
| 10001167 | - | Aluminum | 6061 | 3/4" x 1 1/4" | T x W | AMS-QQ-A-225/8 OR ASTM B211 TEMPER 651 ALUMINUM 6061 | |
| 10001168 | - | Aluminum | 6061 | .3900/.3905" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 (6061-T6) | |
| 10001169 | - | Misc | DELETED | | | SAME AS 10001074 | |
| 10001170 | - | CRES | 17-4 PH | 13/32 | DIA | AMS-5643 COND. H1075 | |
| 10001171 | - | CRES | 17-4 PH | 1 7/16" | DIA | AMS-5643 COND. H 1075 | |
| 10001172 | - | Aluminum | 6061 | 1/8" x 2" | T x W | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 (6061-T6) | |
| 10001173 | - | CRES | 17-4 PH | 3 1/2" | DIA | AMS-5643 COND H1075 | |
| 10001174 | - | Nylon | NYLON 6/6 | 1 1/4" | DIA | 30% GLASS FILLED ASTM D4066 TYPE 1 CLASS 2 GRADE B | |
| 10001175 | - | Aluminum | 6061 | 1 5/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001176 | - | CRES | 17-4 PH | 2 1/4" | DIA | AMS-5643 COND. H 1075 | |
| 10001177 | - | CRES | 17-4 PH | .3060/.3055" | DIA | AMS-5643 COND. H 1075 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------|---------------|--------|--|-------|
| 10001178 | A | Aluminum | 1100 | 1" | DIA | AMS-QQ-A-225/1 OR ASTM B211 TEMPER 0 (1100-T0) ALT.ASTM B221 | 80545 |
| 10001179 | - | CRES | 416 | .300 | SQ | TYPE 416 OR 416SE COND. A (RC 27 MAX) | |
| 10001180 | - | CRES | 17-4 PH | 2 5/8" | DIA | AMS-5643 COND H1075 | |
| 10001181 | - | CRES | 416 | .218" ±.004 | SQ | TYPE 416 COND A | |
| 10001182 | - | CRES | 17-4 PH | 9/16" | DIA | AMS-5643 COND. H 1075 (17-4PH) | |
| 10001183 | - | CRES | 17-4 PH | .2180/.2177 | DIA | AMS-5643 COND. H1075 | |
| 10001184 | - | CRES | 302 | 1 5/16" | DIA | ASTM-A276 TYPE 302 COND. A | |
| 10001185 | - | CRES | 17-4 PH | 1" | DIA | AMS-5643 COND. H 1075 | |
| 10001186 | - | CRES | 17-4 PH | .2460-.2457 | DIA | DO NOT USE! (SAME AS 10000170) AMS-5643 COND. H 1075 (17-4PH) | |
| 10001187 | - | CRES | 17-4 PH | 1 3/8" | DIA | AMS-5643 COND. H1075 | |
| 10001188 | - | CRES | 17-4 PH | 1 1/16" | DIA | AMS-5643 COND. H 1075 | |
| 10001189 | - | CRES | 17-4 PH | 3 1/4" | DIA | AMS-5643 COND. H 1075 | |
| 10001190 | - | CRES | 17-4 PH | 1 11/16" | DIA | AMS-5643 COND. H 1075 | |
| 10001191 | - | Misc | BERYLLIUM | 2 15/16" | DIA | B101001009 GRADE 11 TYPE 1 MAX MULT LTH OF 17.73 INCHES | |
| 10001192 | - | Steel | 4140 | 13/16" | DIA | ASTM A331 GRADE 4140 CD HEAT TREAT 260-320 HB STRESS REL | |
| 10001193 | - | Steel | 1117 | .2330"-.2325" | DIA | ASTM A108 GRADE 1117 | |
| 10001194 | - | Brass | BRASS 360 | 1 1/4" | DIA | ASTM B16 ALLOY 360 TEMP 1/2 HARD | |
| 10001195 | - | CRES | 416 | 3 1/2" | DIA | CRES ASTM A582 TYPE 416 COND A 6FT MAX BAR SENGTHS | |
| 10001196 | - | CRES | 416 | .340" x .400" | T x W | TYPE 416 OR 416SE COND A | |
| 10001197 | - | Aluminum | 2024 | 4.250" | DIA | AMS-QQ-A-250/4 PER ALUM 2024-T351 | |
| 10001198 | - | CRES | 303 | 3" | DIA | CRES ASTM-A-582 TYPE 303 COND A 8FT MAX BAR LENGTH | |
| 10001199 | - | Iron | IRON | 1 3/16" | DIA | IAW Y117A107-102 | |
| 10001200 | - | Iron | IRON | 9/16" | DIA | Y117A017-102 & INSPEC. PER EMI 52705 | |
| 10001201 | A | Misc | TITANIUM 6AL4V | 1" | DIA | AMS 4928 ANNEALED | 76719 |
| 10001202 | - | Brass | BRASS 360 | 1/4" x 1/2" | T x W | ASTM B36 BAR BRASS HALF HARD | |
| 10001203 | - | CRES | 416 | .3110"-.3105" | DIA | TYPE 416 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|----------------|-----------------------------|--------|--|-------|
| 10001204 | - | Steel | 4140 | 15/16" | DIA | AISI TYPE 4140 COLD DRAWN ANNEALED MS 203-2 TYPE 1 | |
| 10001205 | - | CRES | 17-4 PH | 11/16" | DIA | AMS-5643 COND H1075 | |
| 10001206 | - | Aluminum | 2024 | 6 1/2" | DIA | MS 404-2 TYPE 11 ALUM 2024-T4 | |
| 10001207 | B | Aluminum | 2024 | .040/.030 X 2.290/2.285 | T X W | AMS-QQ-A-250/4 TEMPER T3 (2024-T3) PURCHASED IN 12' LENGTHS | 86724 |
| 10001208 | A | Misc | GOLD | .0100 ±.0005" | DIA | GOLD ALLOY WIRE PER ASTM-B-541 CONDITION A (SOLUTION ANNEALED) | 73234 |
| 10001209 | - | CRES | 416 | 2 9/16" | DIA | CRES ASTM-A582 TYPE 416 COND A | |
| 10001210 | - | Aluminum | 2024 | 4 1/4" | DIA | AMS-QQ-A-225/6 TEMPER T4 2024 | |
| 10001211 | - | Misc | TORLON | 5/16 | DIA | TORLON 4203 or 4203L GEN PURPOSE GRD AVAIL FROM AMOCO CHEM CORP | |
| 10001212 | - | CRES | 416 | 1 1/2" | DIA | AMS-QQ-S-763 COND H RC-26-32 MS 202-2 TYPE 4 CRES | |
| 10001213 | - | Brass | BRASS 360 | 13/16" | DIA | ASTM B16 ALLOY 360 TEMP 1/2 HARD BRASS ROD | |
| 10001214 | - | Brass | BRASS 360 | 1 1/8" | DIA | ASTM B16 ALLOY 360 TEMP 1/2 HARD BRASS ROD | |
| 10001216 | A | CRES | 416 | 1 3/4" | DIA | USE 10000639 | 75103 |
| 10001217 | - | Aluminum | 2024 | .062"±.005 x 1.500"±.010 | T x W | AMS-QQ-A-250/4 TEMPER T3 (2024-T3) | |
| 10001218 | - | Nickel Iron | NICKEL IRON 49 | 1/2" | DIA | NICKEL IRON Y202A014-1 COMPOSITION A | |
| 10001219 | - | CRES | 416 | .155-.154" | DIA | TYPE 416 OR 416 SE COND H | |
| 10001220 | A | Aluminum | 6061 | 1 1/2" | DIA | SAE AMS-QQ-A-200/8, SAE AMS 4117, SAE AMS 4150, SAE AMS 4173, T6, T62, T651, T6510 OR T65111 | 83774 |
| 10001221 | - | Brass | BRASS 360 | 3/8" x 1/2" | T x W | BAR FREE CUTTING BRASS ASTM B36 HALF HARD | |
| 10001222 | - | CRES | 440C | .3120"-.3115" | DIA | QQ-S-763 CLASS 440C COND A | |
| 10001223 | B | Nickel Iron | NICKEL IRON 49 | 3/4" | DIA | ASTM A 753 TYPE 2 GRADE 2 OR MIL-N-14411 COMP 3 (PER RN 5M917-1) | 77490 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|--------------------|-----------|---|-------|
| 10001224 | - | CRES | 416 | 1 11/16 | DIA | ASTM A484, ASTM A582 416SS | |
| 10001225 | - | Nickel Iron | NICKEL IRON 49 | 13/16" | DIA | NICKEL IRON PER Y202A014-201 & INSPEC PER EMI-52705 | |
| 10001226 | A | CRES | 416 | 2 3/8" | DIA | ASTM A582/A582M COND. H OR 416SE COND. H | 86685 |
| 10001227 | - | Nickel Iron | NICKEL IRON 49 | 1/2" | DIA | NICKEL IRON PER Y202A014-201 & INSPEC PER EMI-52705 | |
| 10001228 | - | Aluminum | 6061 | 2 1/4" x .125" | OD x WALL | ALUMINUM TUBING 6061-T6510 | |
| 10001229 | - | Misc | POWDER ALLOY | 1 1/4" x 3/4" | DIA x L | MPIF 0000S LONG SLUG | |
| 10001230 | - | CRES | 416 | 1 13/16 | DIA | RC 26-38 416SS | |
| 10001231 | - | CRES | 17-4 PH | .3110/.3105 | DIA | ASE-AMS-5643 COND H 1075 17-4PH RC 31-39 CRES | |
| 10001232 | - | Steel | 4130 | 3 3/8" | DIA | MIL-S-6758 COND. D (NORMALIZED) | |
| 10001233 | A | Bronze | BRONZE, ALUM | 3 3/8" | DIA | AMS-4640 | 78115 |
| 10001234 | - | Steel | 4130 | 1/2" | DIA | MIL-S-6758 COND D-4 4130 ALY. ST. | |
| 10001235 | - | Steel | 12L14 | 1 1/2" | DIA | C12L14 COLD ROLLED STEEL | |
| 10001236 | - | Misc | TORLON | 5/16" | DIA | TORLON GRADE 4203 OR 4203L | |
| 10001238 | - | CRES | 303 | 4 3/4" | DIA | TYPE 303 COND A PER ASTM-A582 3FT MAX LENGTH | |
| 10001239 | - | CRES | 303 | 3 5/8 | DIA | TYPE 303 COND A PER ASTM-A582 5 1/2" MAX LENGTH | |
| 10001240 | - | Aluminum | 6061 | 3 1/4" | DIA | AMS-QQ-A-225/8 OR ASTM B211 ALUM 6061-T651 | |
| 10001241 | - | Aluminum | 2024 | 3/8" x 1" | T x W | AMS-QQ-A-225/6 ALUM 2024-T4 STRIP | |
| 10001242 | - | Aluminum | 2024 | 1/2" x 1 1/2" | T x W | AMS-QQ-A-225/6 ALUM 2024-T351 | |
| 10001243 | - | Nickel Iron | NICKEL IRON 49 | 5 3/16 +3/16 - .00 | DIA | ASTM-A753 ALLOY 2 | |
| 10001244 | - | Nickel Iron | NICKEL IRON 49 | 4 3/4" | DIA | ASTM-A753 ALLOY 2 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-------------------|--------------------|--------|---|-------|
| 10001245 | - | Nickel Iron | NICKEL IRON 49 | 4 1/4" | DIA | ASTM-A753 ALLOY 2 | |
| 10001246 | - | Aluminum | 2024 | 3" | DIA | AMS-QQ-A-225/6 ALUM 2024-T4 | |
| 10001247 | - | Bronze | BRONZE, ALUM | 3/4" | DIA | SAE AMS4640 | |
| 10001248 | - | Aluminum | 2024 | 1 3/8" x 1 3/8" | SQ | ALUMINUM BAR 2024-T351 | |
| 10001251 | - | CRES | 304 | 1/4" | DIA | AMS-QQ-S-763 CLASS 304 COND A | |
| 10001252 | - | CRES | 347 | 1 1/16" | DIA | ASTM-A276 TYPE 347 COND. A | |
| 10001253 | - | CRES | 418 | 9/16" | DIA | 418 SS, AMS-5616 | |
| 10001254 | B | Nickel Iron | NICKEL IRON 49 | 1 1/16" | DIA | PER Y202A014-101, -102, OR -105 OR CAPABLE OF MIL-N-14411 COMP. 3 | 76863 |
| 10001255 | - | Iron | SILICON CORE IRON | 4 1/2" | DIA | I.A.W. B190000380 | |
| 10001256 | - | Misc | TITANIUM | 2 1/2" | DIA | TITANIUM MIL-T-9047 CMPSM 1 | |
| 10001257 | - | Misc | TITANIUM | 1 3/4" | DIA | MIL-T-9047 COMP Ti-CP-70 | |
| 10001258 | - | CRES | 304 | .2460/.2455 | DIA | AMS-QQ-S-763 CLASS 304 COND. A | |
| 10001259 | - | CRES | 416 | .3590/.3585 | DIA | RC 20-25 416SS | |
| 10001260 | - | Misc | INVAR 36 | 5 1/2" x 5 3/4" | T x SQ | BILLET-INVAR36-FREE MACHINING | |
| 10001261 | - | CRES | 416 | 3/16" | DIA | ASTM A582 TYPE 416 COND A | |
| 10001263 | - | Plastic | PLASTIC | .062"±.005 x .500± | T x W | STRIPS LAMINATED PLASTIC MIL-P-15047 TYPE NPG | |
| 10001264 | - | CRES | 410 | 13/16" | DIA | ASTM-A276 TYPE 410 COND. A | |
| 10001265 | - | CRES | 410 | 1 3/8" | DIA | AMS-QQ-S-763 CLASS 410 COND. A | |
| 10001266 | A | Nickel Iron | NICKEL IRON 49 | 1 1/4" | DIA | Y202A014-102 COMP A NICKEL IRON PER OR MIL-N-14411 COMP.3 | 75768 |
| 10001267 | - | Nickel Iron | NICKEL IRON 49 | 2 1/8" | DIA | Y202A014-102 COMP A NICKEL IRON PER | |
| 10001268 | - | CRES | 17-4 PH | 2 1/2" | DIA | AMS-5643 17-4PH SS | |
| 10001269 | - | CRES | 17-4 PH | .2505/.2500 | DIA | AMS-5643 COND. A | |
| 10001270 | - | CRES | 410 | .3438" ±.0003 | DIA | 410 SS COND A | |
| 10001271 | A | CRES | 17-4 PH | 13/16" | DIA | USE 10000935 | 75089 |
| 10001272 | - | Aluminum | 3003 | .016" x 2 3/8" | T x W | AMS-QQ-A-250/2 TEMPER H14 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-----------|--------------------|---------|--|-------|
| 10001273 | - | Aluminum | 6061 | 4" | DIA | AMS-QQ-A-225/8 OR ASTM B211 ALUM 6061 TEMPER T651 | |
| 10001274 | - | Aluminum | 6061 | 5 1/2" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651, 6 FT. MAX LENGTHS | |
| 10001275 | - | CRES | 416 | 1 1/2 x 2" | L x W | TYPE 416 COND H RECTANGULAR BARSTOCK | |
| 10001276 | - | CRES | 410 | 1 1/2" | DIA | TYPE 410 COND. A | |
| 10001277 | - | CRES | 418 | 1/4" | DIA | 418 SS, AMS 5616 | |
| 10001278 | - | CRES | 303 | 1 1/4" x 1.010" | OD x ID | CRES TUBING AMS-T-8506 TYPE 303 ANNEALED | |
| 10001279 | - | Aluminum | 2024 | 5/16" | DIA | AMS-QQ-A-225/6 TEMPER T4 (20240T4) | |
| 10001280 | A | Aluminum | 7075 | 1" | DIA | AMS-QQ-A-225/9 OR ASTM B211 | 78595 |
| 10001281 | - | Aluminum | 2024 | 3/4" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001282 | - | CRES | 416 | 3/4" | DIA | ASTM A582/A582M COND. T | |
| 10001283 | - | CRES | 304 | .1252/.1249 | DIA | AMS-QQ-S-763 CLASS 304 COND. A | |
| 10001284 | - | Steel | 1018 | 1 7/8" | DIA | ASTM-A108 GRADE 1018 | |
| 10001285 | - | CRES | 418 | 5/32" | DIA | 418 SS, AMS 5616 RC 42-50 | |
| 10001286 | - | CRES | 440C | 1/2" | DIA | CRES QQ-S-763 CL 440C COND A | |
| 10001287 | - | CRES | 321 | .120/.130 x 3.740/ | T x W | ASTM A240, ASTM A660, ASTM A693 COND A | |
| 10001288 | - | Misc | DENSALLOY | 15/16 x 2 13/16 LG | | MIL-T-21014 TYPE 11 CLASS 1 | |
| 10001289 | - | CRES | 416 | .240 x .240 | SQ | COND A | |
| 10001290 | - | CRES | 17-4 PH | 3" | DIA | AMS 5643 SOLUTION ANNEALED COLD FINISH | |
| 10001291 | - | CRES | 303 | 3 3/4" | DIA | ASTM A582 COND A 5FT MAX | |
| 10001292 | - | CRES | 440C | 5/8" | DIA | QQ-S-763 CLASS 440C COND A | |
| 10001293 | - | CRES | 321 | 1/8" x 4" | T x W | ASTM A240,ASTM A666, ASTM A693 COND A CRES | |
| 10001294 | - | CRES | 416 | 15/16" | DIA | TYPE T | |
| 10001295 | - | CRES | 430 FR | 1 5/8" | DIA | IAW Y117A020-102 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------------|---------------------------|-----------|--|-------|
| 10001296 | - | Bronze | BRONZE, PHOSPHOR | 3/4" | DIA | ASTM B139 COMP A COND SPG | |
| 10001297 | - | CRES | 430 FR | 1 3/4 | DIA | CHROMIUM-IRON ALLOY IAW Y117A020-101 | |
| 10001298 | - | Misc | TITANIUM 6AL4V | 3/4" | DIA | SAE AMS4928 Titanium 6Al - 4V Annealed | |
| 10001299 | - | CRES | 302 | 2 5/8" | DIA | AMS-QQ-S-763 TYPE 302 COND B | |
| 10001300 | - | CRES | 302 | 2" | DIA | QQ-S-763 TYPE 302 COND B | |
| 10001301 | - | CRES | 302 | 1 1/4" | DIA | AMS-QQ-S-763 TYPE 302 COND B | |
| 10001302 | - | CRES | 302 | 9/16" | DIA | AMS-QQ-S-763 TYPE 302 COND B | |
| 10001303 | - | Aluminum | 6061 | 2 1/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T 651 | |
| 10001304 | A | CRES | 416 | 3 1/2" | DIA | ASTM A582/A582M TYPE 416 COND. T OR 416SE COND. T | 86686 |
| 10001305 | A | CRES | 416 | 7/8" | DIA | ASTM A582/A582M TYPE 416 COND. T OR 416SE COND. T | 86686 |
| 10001306 | - | Aluminum | 2024 | .2429/.2426 | DIA | AMS-QQ-A-225/6 TEMP 4 2024-T4 | |
| 10001307 | - | Copper | BERYLLIUM | 7/16" | DIA | ASTM B196 OR B197 OR B194 ALLOY 172 T H | |
| 10001308 | - | Aluminum | 6061 | 5/8" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001309 | - | CRES | 17-4 PH | 2" | DIA | AMS 5643 COND H1075 | |
| 10001310 | - | CRES | 17-4 PH | 1.5" | DIA | AMS-5643 COND. H 1075 | |
| 10001311 | - | Aluminum | ALUM 2024 OR 6061 | 1/2" x 3 1/8" x 6 1/2" | T x W x L | ALUM 2024-T4 OR ALUM 6061-T6 | |
| 10001312 | - | Bronze | BRONZE, PHOSPHOR | 1/2" | DIA | ASTM B139 COMP A TEMP H | |
| 10001313 | - | CRES | 17-4 PH | 3 5/8" | DIA | AMS-5643 COND H 1075 | |
| 10001314 | - | CRES | 430F | 3 1/4" | DIA | ASTM-A582 TYPE 430F OR 430FSE COND. A | |
| 10001315 | - | CRES | 304 | 2 5/16" | DIA | ASTM-A276 TYPE 304 COND. A | |
| 10001316 | - | CRES | 304 | 1/2" | DIA | AMS-QQ-S-763 CLASS 304 COND. A | |
| 10001317 | - | CRES | 304 | 1 1/8" | DIA | ASTM-A276 TYPE 304 COND. A | |
| 10001318 | - | CRES | CRES | 0.020" | DIA | SAFETY LOCK WIRE 8860K61 | |
| 10001319 | - | Misc | POLYIMIDE, SP | 5/8" | DIA | VESPER 211 RESIN | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|-----------------|-----------|---|-------|
| 10001320 | - | Aluminum | 6061 | .093" x 4" x 4" | T x W x L | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 (6061-T6) | |
| 10001321 | - | Nylon | NYLON 6/6 | 1" | DIA | ASTM-D-4066 30% GLASS FIBER 6/6 NYLON | |
| 10001322 | A | CRES | 416 | 2 1/8" | DIA | ASTM A582/A582M COND. H OR 416SE COND. H | 86685 |
| 10001323 | - | Bronze | BRONZE, PHOSPHOR | 11/16" | DIA | ASTM B139 COMPSN-A-TEMP H | |
| 10001324 | - | Aluminum | 6061 | 1/2" x 1 3/8" | DIA | AMS-QQ-A-250/11 OR ASTM B209 ALUMINUM 6061-T651 | |
| 10001325 | - | CRES | 17-4 PH | 3/32" x 3/16" | T x W | STRIP STOCK AMS-5643 | |
| 10001326 | - | CRES | 17-4 PH | 1/4" x 1" | T x W | STRIP STOCK AMS-5643 | |
| 10001327 | - | CRES | 17-4 PH | 5/64" x 1" | T x W | AMS-5643 COND. A | |
| 10001328 | - | Aluminum | 7075 | 1/8" x 5/16" | T x W | AMS-QQ-A-225/9 OR ASTM B211 TEMPER T6 (7075 ALUM) | |
| 10001329 | - | CRES | 17-4 PH | 3/32" | DIA | AMS 5643 RC 31-39 | |
| 10001330 | - | CRES | 302 | 2" | DIA | QQ-S-763 TYPE 302 COND A | |
| 10001331 | - | CRES | 302 | 2 5/8" | DIA | QQ-S-763 TYPE 302 COND. A | |
| 10001332 | - | CRES | 17-4 PH | 3/32" x 3/8" | T x W | AMS 5643 COND H1075 | |
| 10001333 | - | Steel | 4340 | 1 3/4 | DIA | AMS-6415 | |
| 10001334 | - | CRES | 302 | 1 7/16 | DIA | QQ-S-763 TYPE 302 COND. B | |
| 10001335 | - | Aluminum | 6061 | 7/16" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 (6061-T6) | |
| 10001337 | - | Misc | POLYIMIDE, SP | 3/4" | DIA | VESPEL 211 RESIN | |
| 10001338 | - | CRES | 17-4 PH | 1/16" | DIA | AMS 5643 COND H RC 31-39 | |
| 10001339 | - | CRES | 302 | 1 5/16" | DIA | AMS 5640 ANNEALED 302 | |
| 10001340 | - | CRES | 303 | 5 5/8" | DIA | ASTM A582 COND A 303 | |
| 10001341 | - | Misc | INVAR 36 | 1 1/8" | DIA | CARPENTER INVAR #36 | |
| 10001342 | - | CRES | 303 | 3/16" | DIA | ASTM A581/A581M HEX | |
| 10001343 | - | CRES | 302 | 3/16" | DIA | ASTM A276 TYPE 302 COND A | |
| 10001344 | - | Steel | 1118 | 1 1/2" | DIA | GRADE 1118 ASTM A108 | |
| 10001345 | A | Steel | 1045 | 9/16" | DIA | GRADE 1045 ASTM A108 HARDENED TO Rc 30-35 | 80935 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------------|--------------------|---------|--|-------|
| 10001346 | - | Aluminum | 5052 | .020" x 1 1/4" | T x W | AMS-QQ-A-250/8 5052-H32 | |
| 10001347 | - | Steel | 1018 | 1" | DIA | ASTM-A108 GRADE 1018 COLD FINISHED STEEL | |
| 10001348 | - | CRES | 17-4 PH | 7/16" | DIA | AMS 5643 SOLUTION ANNEALED COLD FINISH | |
| 10001349 | A | Aluminum | 6061 | 5/8" x 1.000" | T x W | SAE AMS4117 T6, T651 OR SAE AMS QQ-A-200/8 T6, T651, T6511 | |
| 10001350 | - | Aluminum | 2024 | 1" | DIA | AMS-QQ-A-225/6 2024 T-351 | |
| 10001351 | - | CRES | 303 | 2 3/8" | DIA | ASTM A582 COND A | |
| 10001352 | - | CRES | 17-4 PH | 3/4" | DIA | AMS 5643 COND H1075 | |
| 10001353 | - | CRES | 410 | 1/4" | DIA | AMS-QQ-S-763 CLASS 410 COND A | |
| 10001354 | - | CRES | 17-4 PH | 1 1/8" | DIA | AMS-5643 COND. H1075 | |
| 10001355 | - | CRES | 17-4 PH | 2 3/8" | DIA | AMS 5643 COND H RC 31-39 | |
| 10001356 | - | CRES | 304 | 1 5/16" | DIA | AMS-QQ-S-763 COND A | |
| 10001357 | - | CRES | 410 | 3/8" | DIA | COND T RC 25-31 | |
| 10001358 | - | CRES | 410 | 9/16" | DIA | COND T RC 25/31 | |
| 10001359 | - | CRES | 410 | 7/32" | DIA | COND A | |
| 10001360 | - | Aluminum | 2017 | 3 1/8" x 1/2"+ 1/8 | DIA x L | TYPE 2017-T-451 | |
| 10001361 | - | Steel | 1117 | 1/2" | DIA | ASTM-A108 GRADE 1117 | |
| 10001362 | - | Aluminum | 2024 | 2 3/4" | DIA | AMS-QQ-A-225/6 ALUM 2024-T4 | |
| 10001363 | - | Iron | SILICON CORE IRON | 3 1/4" x 5/8" | DIA x L | SILICON CORE IRON B-FM IAW B190000380 | |
| 10001364 | - | Iron | SILICON CORE IRON | 4 1/4" x 1 1/8"+1/ | DIA x L | SILICON CORE IRON B-FM IAW B190000380 | |
| 10001365 | - | Aluminum | 2024 | 5" x 1 1/8"+1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMP 2024 T-351 | |
| 10001366 | - | Aluminum | 2024 | 5" x 2 1/2"+1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMP 2024 T351 | |
| 10001367 | - | Aluminum | 2024 | 5" x 1" | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001368 | A | CRES | 416 | 3 1/2" x 1 3/4" | DIA x L | ASTM A582/A582M COND. H OR 416SE COND. H | 86685 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------|----------------------|-------------|---|------|
| 10001369 | - | Aluminum | 2024 | 3 1/2" x 2 1/8" | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001370 | - | Aluminum | 2024 | 3 1/2" x 3" x 1 1/4" | OD x ID x L | WW-T-700/3 TYPE 1 TEMP T3 | |
| 10001371 | - | CRES | 17-4 PH | 1 9/16" | DIA | AMS-5643 COND. H1075 | |
| 10001372 | - | CRES | 410 | 1/4" | DIA | AMS-QQ-S-763 CLASS 410 COND A | |
| 10001373 | - | Misc | INCONEL 718 | 5/8" | DIA | AMS 5662 | |
| 10001374 | - | CRES | 17-4 PH | 5/8" | DIA | ASM 5643 COND H1075 | |
| 10001375 | - | Misc | TEFLON | 5/8" | DIA | GRAPHITE FILL PER DIXON INDUST SPEC #101565 | |
| 10001376 | - | Iron | IRON | 9/32" | DIA | PER Y117A017-102 | |
| 10001377 | - | CRES | 304 | 3 3/8" x 2 1/2"+1/ | DIA x L | AMS-QQ-S-763 CLASS 304 COND. A | |
| 10001378 | - | CRES | 304 | 3 3/8" x 3/4"+1/8- | DIA x L | AMS-QQ-S-763 TYPE 304 COND A | |
| 10001379 | - | Aluminum | 2024 | 3 3/4" x 1" +1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMP T351 | |
| 10001380 | - | Aluminum | 2024 | 3 1/4" x 1 5/8" | DIA x L | AMS-QQ-A-225/6 TEMPER T 351 | |
| 10001381 | - | Aluminum | 2024 | 3 1/4" x 1/2" +1/8 | DIA x L | AMS-QQ-A-225/6 TEMP T351 | |
| 10001382 | - | Aluminum | 2024 | 3 1/4" x 1" | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001383 | - | Aluminum | 2024 | 4" x 2"+1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMP T4 2024 | |
| 10001384 | - | CRES | 416 | 3 1/8" x 1/2" + 1/ | DIA x L | ASTM-A-582 COND A | |
| 10001385 | - | CRES | 416 | 4" x 1 3/4"+ 1/8-0 | DIA x L | ASTM-A-582 COND A | |
| 10001386 | - | Aluminum | 6061 | 5 1/2" x 5 1/2" | DIA x L | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001387 | - | Aluminum | 2024 | 3 3/4" x 4" +1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMP T4 2024 | |
| 10001388 | - | Aluminum | 2024 | 3 3/4" x 1" +1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMP T4 2024 | |
| 10001389 | - | Aluminum | 6061 | 3 1/2" x 1 3/8" +1 | DIA x L | ASTM B241 OR ASTM B221 6061-T651 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------------|--------------------|--------------|--|------|
| 10001390 | - | CRES | 15-5 PH | 4" x 1/4"+1/8-0 | DIA x L | AMS 5659 COND H 1075 | |
| 10001391 | - | CRES | 15-5 PH | 4" x 3/8"+1/8-O | DIA x L | AMS 5659 COND H1075 (15-5PH) | |
| 10001392 | - | CRES | 15-5 PH | 3 5/8" x 1/2" +1/8 | DIA x L | AMS 5659 COND H 1075 | |
| 10001393 | - | Aluminum | 2024 | 4 1/4" x 1/2"+1/8- | DIA x L | AMS-QQ-A-225/6 2024-T351 | |
| 10001394 | - | CRES | 17-4 PH | 3 1/4" x 2 1/4" | DIA x L | AMS 5643 COND H 1075 | |
| 10001395 | - | Aluminum | 6061 | 3 3/4 x 3/4" | DIA x L | ASTM B241 OR ASTM B221 TEMPER T6 | |
| 10001396 | - | Aluminum | 2024 | 2 7/8" | DIA | AMS-QQ-A-225/6 2024-T351 | |
| 10001397 | - | Aluminum | 6061 | 4" x 3/4" | DIA x L | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T 651 | |
| 10001398 | - | CRES | 17-4 PH | 3 1/2" x 3/16" | 5 DIA x L | AMS 5643 COND H1075 3 1/2 DIA X 5 3/16" LONG | |
| 10001399 | - | Misc | TEFLON | 1/4" | DIA | TEFLON, GRAPHITE FILLED, DIXON IND. RULON 123 ROD | |
| 10001400 | - | CRES | 303 | 3 1/2" x 2 3/4" | DIA x L | CRES ASTM-A-582 TYPE 303 COND. A. | |
| 10001401 | - | CRES | 416 | 1/4" x 3/4" | T x W | CRES TYPE 416 COND. A | |
| 10001402 | - | CRES | 416 | 3 1/2" x 3 1/2" | DIA x L | CRES TYPE 416 COND. A(ASTM A 582) | |
| 10001403 | - | CRES | 416 | 3 1/2" x 3/4" | DIA x L | CRES TYPE 416 COND. A ASTM-A-582/A 582M | |
| 10001404 | - | Aluminum | 2024 | 6 1/2" x 1 3/8" | DIA x L | AMS-QQ-A-225/6 TEMP T4 (2024-T4) | |
| 10001405 | - | Aluminum | 2024 | 4 1/4" x 5/8" | DIA x L | AMS-QQ-A-225/6 TEMP T4 (2024-T4) | |
| 10001406 | - | Aluminum | 2024 | 4 1/4" x 1 1/4" | DIA x L | AMS-QQ-A-225/6 TEMP T4 (2024-T4) | |
| 10001407 | - | Aluminum | 6061 | 3 1/4" x 1/2" | DIA x L | AMS-QQ-A-225/8 OR ASTM B211 TEMP T6 (6061-T6) | |
| 10001408 | - | Iron | SILICON CORE IRON | 4 1/2" x 1 1/8" | DIA x L | SILICON CORE IRON CARPENTER B-FM C190000380 | |
| 10001409 | - | CRES | 303 | 3 1/2" x 2" | DIA x L | CRES TYPE 303 COND. A.(ASTM A 582) | |
| 10001410 | - | CRES | 416 | 3/4" x 2" | T x W | ASTM A582 TYPE 416 COND A | |
| 10001411 | - | Aluminum | 6061 | .125" x 1.880" | T x W | IAW AMS-QQ-A-250/11 OR ASTM B209 (6061 TEMPER T6) | |
| 10001412 | - | CRES | 416 | 1/4" x 2" | T x W | TYPE 416 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------|-------------------------|-----------|---|-------------|
| 10001413 | - | Aluminum | 2024 | 1" | DIA | IAW AMS-QQ-A-225/6 (2024 TEMPER T4) | |
| 10001414 | - | CRES | 15-5 PH | 4" x 8" | DIA x L | AMS - 5659 COND. H1075 (15-5PH) | |
| 10001415 | - | Plastic | ACETAL PLASTIC | 1/4" | DIA | IAW L - P - 392, TYPE 1, CLASS 1, ACETAL ROD. | |
| 10001416 | - | Aluminum | 6061 | 1/2" x 7" x 3" | T x W x L | AMS-QQ-A-250/11 OR ASTM B209 (6061-T.651) | |
| 10001417 | - | CRES | 304 | 1/16" | DIA | ASTM A 5801A580M TYPE 302 OR TYPE 304 COND B | |
| 10001418 | - | CRES | 17-4 PH | 9/16" | DIA | IAW AMS-5643 COND. A | |
| 10001419 | - | CRES | 17-4 PH | 1 5/8" | DIA | IAW AMS-5643 COND. A | |
| 10001420 | - | CRES | 440C | 15/16" | DIA | QQ-S-763-CLASS 440C COND. A | |
| 10001421 | A | CRES | 17-4 PH | 1 1/4" | DIA | AMS-5643 COND. H 1150 | 77136 |
| 10001422 | - | Aluminum | 2024 | .190" x 1 3/8" x6" | T x W x L | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001423 | - | CRES | 17-4 PH | 1" | DIA | IAW AMS-5634 COND. A | |
| 10001424 | - | CRES | 416 | 3" x 3" | SQ | ASTM A582 TYPE 416 COND A | |
| 10001425 | - | CRES | 303 | 2" | DIA | ASTM A - 582 COND. A | |
| 10001426 | - | CRES | 303 | .4885-.4875" | DIA | ASTM-A-582 TYPE 303 COND. A | |
| 10001427 | - | CRES | 303 | .1250-.1253" | DIA | CRES ASTM-A-582 COND. A GRD. | |
| 10001428 | A | Aluminum | 2024 | 3/4" X 1.500" X 4.5" | T x W x L | AMS-QQ-A-250/4 TEMPER T-351 (2024-T351) | KH 79456 |
| 10001429 | - | Aluminum | 6061 | 1 3/4" x 1 1/4" | OD x ID | QQA/200/8 ALUM TUBING 6061 T651 | |
| 10001430 | - | Aluminum | 6061 | 3/8" x 1.00" | T x W | SAE-AMS-QQ-A-250 OR SAE AMS4115, TEMPER T6 | |
| 10001431 | - | Aluminum | 2024 | 3.625" x 2.500" | DIA x L | AMS-QQ-A-225/6 TEMPER T4 | |
| 10001432 | - | Aluminum | 6061 | 1 3/4" x 1" | OD x ID | ASTM B241 OR ASTM B221 TEMPER T 651 | |
| 10001433 | - | Aluminum | 6061 | 2 1/2"x3/8" | DIA | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T 6511 | |
| 10001434 | - | CRES | 410 | 13/16" | DIA | AMS 5613 CRES | |
| 10001435 | - | CRES | 303 | .7500"-.7495" | DIA | ASTM A582 TYPE 303 COND A | |
| 10001436 | - | CRES | 303 | 1.000"-.9995" | DIA | ASTM A582 TYPE 303 COND A | |
| 10001437 | - | CRES | 303 | 1.3750-1.3745" | DIA | ASTM A582 TYPE 303 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-----------|---------------------------|-----------|---|------|
| 10001438 | - | Aluminum | 6061 | 1 1/2" x 1 1/8" x .125" | TEE | ASTM B241 OR ASTM B221 TEMPER T4 | |
| 10001439 | - | Aluminum | 2024 | .125±.005 x 3 1/8 x 6 1/2 | | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001440 | - | Aluminum | 2024 | 3/8" | DIA | AMS-QQ-A-225/6 AL ALLOY 2024-T4 | |
| 10001441 | - | CRES | 303 | .375" | SQ FT | CRES TYPE 303 COND A AS PER ASTM A582 OR ASTM A484 X 5 FT. MAX | |
| 10001442 | - | Aluminum | 2011 | 5/16" | HEX | IAW AMS-QQ-A-225/3 ALLOY 2011-T3 | |
| 10001443 | - | Aluminum | 7075 | 5/8" | DIA | SAE AMS-QQ-200/11, T6, T6510 OR T6511 OR SAE AMS-QQ-A-225/9, T6 OR T651, OR SAE AMS 4122 (AL7075-T6 OR 7075-T651) | |
| 10001444 | - | Aluminum | 2024 | 4 1/2" | DIA | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001445 | - | Aluminum | 2024 | .125" x 1 3/4" | T x W | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001446 | - | Aluminum | 6061 | .375" x 3 1/2" | T x W | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T651 | |
| 10001447 | - | Aluminum | 2024 | .125"±.005 x 3 1/2 | T x W | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001448 | - | Aluminum | 2024 | 1 1/4" x 2 1/2" | T x W | AMS-QQ-A-250/4 TEMPER T351 | |
| 10001449 | - | Aluminum | 6061 | 1 1/4" x 15" x 17 3/4" | T x W x L | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001450 | - | Brass | BRASS 464 | 2 3/4" | DIA | QQ-B-637 ALLOY 464 TEMPER 1/2 H | |
| 10001451 | - | Misc | OPEN | | | | |
| 10001452 | - | Misc | OPEN | | | | |
| 10001453 | - | Copper | COPPER | .500"±.0036 x 2.00 | T x W | IAW ASTM B152 COLD ROLLED LIGHT | |
| 10001454 | - | CRES | 303 | 1.2480-1.2470 | DIA | C'LESS GROUND 303 ASTM A 582 COND A | |
| 10001455 | - | Aluminum | 2024 | 4 1/2" x 4" | DIA x L | AMS-QQ-A-225/6 T351 ALUM SLUGS | |
| 10001456 | - | CRES | 303 | 1.060/1.0590 | DIA | COND A C'LESS GROUND 303 ASTM A 582 | |
| 10001457 | - | CRES | 303 | 1.123/1.1220 | DIA | COND A C'LESS GROUND 303 ASTM A582 | |
| 10001458 | - | Tungsten | TUNGSTEN | .125 | DIA | TUNGSTEN ALLOY 1AW Y117A001-102 | |
| 10001459 | - | CRES | 416 | 1 3/16" | DIA | IAW COND. H | |
| 10001460 | - | Steel | 8630 | 7/16" | DIA | MIL-S-6050 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-----------|---|-----------|---|------|
| 10001461 | - | Aluminum | 6061 | .063" x 1/2" x 3 1/16" | T x W x L | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001462 | - | CRES | 303 | .3740"-.3747" | DIA | ASTM A582 TYPE 303 COND A | |
| 10001463 | - | CRES | 15-5 PH | .498"-.499" | DIA | ASTM A564 / A564M TYPE XM-12 SOLUTION ANNEALED COLD FINISH | |
| 10001464 | - | Aluminum | 2024 | 3 1/4" x 2" | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001465 | - | CRES | 303 | 3 1/8" x .850" | DIA x L | ASTM A582 TYPE 303 COND. A | |
| 10001466 | - | CRES | 416 | 2 1/4 x 1 1/8 | DIA | STEEL TUBING COND. A | |
| 10001467 | - | Aluminum | 7075 | 3 1/8 | DIA | AMS-QQ-A-225/9 OR ASTM B211 ALUM ALLOY T7351 | |
| 10001468 | - | Aluminum | 7075 | 2 1/8 | DIA | AMS-QQ-A-225/9 OR ASTM B211 ALUM ALLOY T7351 | |
| 10001469 | - | Aluminum | 7075 | 2 3/4 x 3 1/4 x 3 1/2 | T x W x L | AMS-QQ-A-225/9 OR ASTM B211 T7351 | |
| 10001470 | - | Aluminum | 7075 | 3 1/8" x 2 13/16" | DIA x L | AMS-QQ-A-225/9 OR ASTM B211 ALUM ALLOY T7351 | |
| 10001471 | - | Aluminum | 7075 | 2 1/4" | DIA | AMS-QQ-A-225/9 OR ASTM B211 ALUM ALLOY T7351 | |
| 10001472 | - | Brass | BRASS 360 | 3/4" x 1" x 3" | T x W x L | ASTM B36 (1/2 HD) | |
| 10001473 | - | Brass | BRASS 360 | 1/4 | DIA | ASTM B16 (1/2 HD) | |
| 10001474 | - | Aluminum | 2024 | 1.375±.030x 2.000±.030 x 2.500±.030 | | AMS-QQ-A-250/4 OR AMS-QQ-A-250/5, TEMPER T351 | |
| 10001475 | - | Aluminum | 2024 | 1.625 ±.030 x.625+-.030 | SQ x T | AMS-QQ-A-250/4 OR AMS-QQ-A-250/5, TEMPER T351 | |
| 10001476 | - | Aluminum | 2024 | .750±.030 x .875±.030 x 1.250±.030 | | AMS-QQ-A-250/4 OR AMS-QQ-A-250/5, TEMPER T351 | |
| 10001477 | - | Aluminum | 2024 | .375±.030 x 1.125±.030 x 2.125±.030 | | AMS-QQ-A-250/4 OR AMS-QQ-A-255/5, TEMPER T351 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|-----------------------------|---------|--|------|
| 10001478 | - | CRES | 304 | .1254/.1251" | DIA | AMS-QQ-S-763 CLASS 304 COND A | |
| 10001479 | - | CRES | 17-4 PH | 5/8" x 1/2" | DIA | CRES 17-4PH COND H1050 AMS 5643 | |
| 10001480 | - | CRES | 416 | .3590/.3585 | DIA | COND T | |
| 10001481 | - | Bronze | BRONZE, ALUM | 5/8" | DIA | ASTM B150 ALLOY C61900 OR C62300 | |
| 10001482 | - | CRES | 410 | 1 1/16" | DIA | CRES CL410 COND A | |
| 10001483 | - | Aluminum | 7075 | 1 1/4" x 18" | SQ x L | AMS-QQ-A-250/12 OR ASTM B209 TEMPER T7351 | |
| 10001484 | - | CRES | 302 OR 304 | .031±.0015 x 1 1/2 x 48" LG | | QQ-S-766 CLASS 302 OR 304 COND A | |
| 10001485 | - | Aluminum | 6061 | .020" x 1" | T x W | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 ALUMINUM | |
| 10001486 | - | Aluminum | 7075 | 3 1/16" x 1 9/16" | DIA x L | AMS-QQ-A-225/9 OR ASTM B211 TEMPER T651 ALUMINUM | |
| 10001487 | - | Aluminum | 7075 | 2 1/4" | DIA | AMS-QQ-A-225/9 OR ASTM B211 TEMPER T651 ALUMINUM | |
| 10001488 | - | CRES | 303 | .250 ±.001 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001489 | - | CRES | 303 | .375 ±.0015 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001490 | - | CRES | 303 | .500 ±.002 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001491 | - | CRES | 303 | .625 ±.002 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001492 | - | CRES | 303 | .750 ±.002 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001493 | - | CRES | 303 | .812 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001494 | - | CRES | 303 | .875 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001495 | - | CRES | 303 | 1.000 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|----------------------------|-----------|--|-------|
| 10001496 | - | CRES | 303 | 1.0625 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001497 | - | CRES | 303 | 1.125 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001498 | - | CRES | 303 | 1.250 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001499 | - | CRES | 303 | 1.375 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001500 | - | CRES | 303 | 1.500 ±.0025 | DIA | ASTM A582 TYPE 303 COND. A CARPENTER PROJ 70 OR EQUIV. | |
| 10001501 | - | Bronze | BRONZE, ALUM | 3/4" | DIA | ALUM BRONZE, ASTM-B-150, ALLOY C62300 | |
| 10001502 | - | CRES | 17-4 PH | 7 1/4 x 2 3/8 | DIA x L | 17-4PH COND H1075 AMS 5643 | |
| 10001503 | - | Steel | 4130 | 3/8" | DIA | MIL-S-6758 | |
| 10001504 | - | Aluminum | 7075 | 2 1/4" | DIA | AL 7075-T7351 PER SAE AMS4078 | |
| 10001505 | - | CRES | 302 | 7/8" | DIA | CLASS 302 AMS-QQ-S-763 COND. A | |
| 10001506 | - | Aluminum | 6061 | 5/8" x 2 1/2" x 8' | T x W x L | ALUM 6061 ASTM B241 OR ASTM B221 TEMPER T6 (8 TO 12 FEET LONG) | |
| 10001507 | A | Aluminum | 6061 | 3/4" x 2 1/2" x 8' | T x W x L | SAE AMS-QQ-A-200/8, T6, T6510 OR T6551 OR ASTM-B221 T6, T6510 OR T6551 | 83993 |
| 10001508 | A | Aluminum | 6061 | 1 3/8" x 2 3/4" x 8' | T x W x L | ALUM 6061 ASTM B221 TEMPER T6511 | 76791 |
| 10001509 | - | Aluminum | 2024 | 1/2" x 1" x 8' | T x W x L | ALUM 2024 AMS-QQ-A-225/6 T4 | |
| 10001510 | - | Aluminum | 2024 | 5/8" x 1 1/2" x 8' | T x W x L | ALUM 2024 T4 | |
| 10001511 | - | Aluminum | 2024 | 5/16" x 1" x 8' | T x W x L | ALUM 2024 AMS-QQ-A-225/6 TEMPER T4 | |
| 10001512 | - | Aluminum | 2024 | 5/16" x 1 1/2" x 8' | T x W x L | ALUM 2024 T4 | |
| 10001513 | - | CRES | 302 OR 304 | .032"±.002 x2 1/8" x 4' | T x W x L | QQ-S-763 TYPE 302 OR 304 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|------------------|---------|---|------|
| 10001514 | - | Aluminum | 6061 | .125" x 1.00" | T x W | ALUM 6061 AMS-QQ-A-250/11 OR ASTM B209 T6 | |
| 10001515 | - | Aluminum | 7075 | 3 1/4" x 1 3/8" | DIA x L | ALUM 7075 T651 AMS-QQ-A-225/9 OR ASTM B211 | |
| 10001516 | - | CRES | 15-5 PH | 7 1/2" x 2 3/8" | DIA x L | 15-5PH COND. H AMS-5659 + 1/8" LONG SLUG | |
| 10001517 | - | CRES | 440C | 13/16" | DIA | 440 C AMS-5630 | |
| 10001518 | - | Aluminum | 7075 | .032" x 2 1/8" | T x W | ALUMINUM 7075-T651 AMS-QQ-A-250/12 OR ASTM B209, 4' LEN, .015 +/- .015 FLAT | |
| 10001519 | - | CRES | 416 | 4 3/4" x 2 3/16" | DIA x L | ASTM A582 TYPE 416 COND A | |
| 10001520 | - | CRES | 17-4 PH | 5/8" | DIA | CRES AMS 5643 COND. A (17-4PH) CONFIGURATION CONTROL | |
| 10001521 | - | CRES | 15-5 PH | 3/4" | DIA | CRES 15-5PH ASTM A564 | |
| 10001523 | - | Aluminum | 2024 | 1/2" x 9/16" | T x W | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001524 | - | Aluminum | 2024 | 1/4" x 3/8" | T x W | ALUM ALLOY 2024 T-4 AMS-QQ-A-250/4 | |
| 10001525 | - | Aluminum | 2024 | 5/16" x 5/8" | T x W | ALUM ALLOY 2024 T-4 AMS-QQ-A-225/6 | |
| 10001526 | - | Aluminum | 2024 | 3/8" x 3/4" | T x W | ALUM ALLOY 2024 T-4 AMS-QQ-A-225/6 | |
| 10001527 | - | Aluminum | 2024 | 1/4" x 1" | T x W | ALUM ALLOY 2024 T-4 AMS-QQ-A-225/6 | |
| 10001529 | - | Aluminum | 2024 | 1/2" x 1/2" | SQ | AMS-QQ-A-250/4 OR AMS-QQ-A-225/6 T-351 | |
| 10001530 | - | Aluminum | 2024 | 1/4" x 1 1/8" | T x W | ALUM ALLOY 2024 T-4 AMS-QQ-A-250/4 | |
| 10001531 | - | Aluminum | 2024 | 5/8" x 3/4" | T x W | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001532 | - | Aluminum | 2024 | 3/16" x 5/8" | T x W | ALUM ALLOY 2024 T-4 AMS-QQ-A-225/6 | |
| 10001533 | - | Aluminum | 6061 | 1/4" x 1/4" | SQ | ALUM ALLOY 6061 T-6 ASTM B241 OR ASTM B221 | |
| 10001534 | - | Aluminum | 2024 | .062" x 1/2" | SQ | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001535 | - | Aluminum | 2024 | .063" x 1/2" | SQ | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001537 | - | Aluminum | 2024 | 5/16" x 3/4" | T x W | ALUM ALLOY 2024 T351 AMS-QQ-A-250/4 | |
| 10001538 | - | Aluminum | 2024 | 1/4" x 1/2" | T x W | AMS-QQ-A-250/4 OR AMS-QQ-A-225/6 T-351 | |
| 10001539 | - | Aluminum | 2024 | 5/8" x 1 1/8" | T x W | ALUM ALLOY 2024 T351 AMS-QQ-A-250/4 | |
| 10001540 | - | Plastic | ACETAL RESIN | 1/8" x 1/4" | T x W | ACETAL RESIN (BLACK) ASTM D4181 TYPE POM 111 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|----------------|---|-----------|---|---------------|
| 10001541 | - | Plastic | ACETAL RESIN | 1/2" | DIA | ACETAL RESIN (BLACK) ASTM D4181 TYPE POM 111 | |
| 10001542 | - | Aluminum | 2024 | .090" x 4" | T x W | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001543 | - | Aluminum | 2024 | .063" x 1" | T x W | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001544 | - | Aluminum | 2024 | .063" x 1 1/8" | T x W | ALUM ALLOY 2024 T-3 AMS-QQ-A-250/4 | |
| 10001545 | - | Aluminum | 2024 | 3/4" x 4"+1/32-0 | T x W | AMS-QQ-A-250/4 TEMPER T351 | |
| 10001546 | - | Aluminum | 7075 | 3/64"±.005 x 2 1/8" x 4' | x L | ALUM ALLOY 7075 T6 AMS-QQ-A-250/12 OR ASTM B209 | |
| 10001547 | - | Aluminum | 6061 | 5/8" x 1" | T x W | ALUM ALLOY 6061 T651 AMS-QQ-A-250/11 OR ASTM B209 ALUMINUM STRIP | |
| 10001548 | - | CRES | 304 | .1875" x .148"+.003 | OD x ID | TUBING (.020" WALL) MS-T-6845 | |
| 10001549 | A | Nickel Iron | NICKEL IRON 49 | 3/16" | DIA | ASTM A753, ALLOY TYPE 2 | NOC- 80960 |
| 10001550 | - | CRES | 321 | 9/16" | DIA | AMS-QQ-S-763 CLASS 321 COND A | |
| 10001551 | - | Misc | HIPERNOM | .015±.002 x30"x120 | T x W x L | Y059A005-222 | |
| 10001554 | - | CRES | 416 | 3" x 1/2" +1/16 -0 | SQ x L | ASTM A582 TYPE 416, COND A | |
| 10001555 | - | CRES | 303 | 2 3/16" | DIA | ASTM A582 TYPE 303 COND A | |
| 10001556 | - | CRES | 416 | 3" +1/16 / -0 x 3" +1/16 / -0 x 1 7/8"+1/16-0 | SQ x L | ASTM-A-582 TYPE 416, COND A LG. SLUG | |
| 10001557 | - | Steel | 1018 | 3" | DIA | ASTM-A-108 GRADE 1018, 6' MAX LENGTH | |
| 10001558 | - | CRES | 303 | .499 +0000 - .0005 | DIA | CRES 303 ASTM A582 TYPE 303- GROUND | |
| 10001559 | - | Nickel Iron | HY MU 80 | .084 ±.002 x 1.125 | T x W | HYMU 80 FLAT SHEET PER Y059A005-222 | |
| 10001560 | - | Aluminum | 2024 | 3 1/4" x 1 1/8" | DIA x L | ALUM 2024 QQ-Q-225/6 TEMPER T351 | |
| 10001561 | - | Nickel Iron | NICKEL IRON 49 | 2" | DIA | CARPENTER 49FM , COMMERCIAL | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|------------------|---------------------------------------|-----------|--|------|
| 10001562 | - | CRES | 304L | 9/64" | DIA | 304L AMS-QQ-S-763 COND A | |
| 10001563 | - | CRES | 13-8 MO | 3/8" | DIA | PH 13-8 MO PER AMS 5629 | |
| 10001564 | - | CRES | 321 | .1875" x .020" | OD x WALL | CRES TUBING TYPE 321 IAW MIL-T-8808 | |
| 10001565 | - | CRES | 321 | 3/16" | DIA | CRES AMS-QQ-S-763 CL 321 COND A | |
| 10001566 | - | CRES | 13-8 MO | 3/4" | DIA | AMS 5629 COND A | |
| 10001567 | - | CRES | 13-8 MO | 9/16" | DIA | PH 13-8 MO PER AMS 5629 ANNEALED | |
| 10001568 | - | CRES | 321 | 1/2" | DIA | CL 321 PER AMS-QQ-S-763 COND A | |
| 10001569 | - | Misc | NITRONIC 60 | 1/4" | DIA | NITRONICS 60 , ASTM A276 UNS S21800 COND A | |
| 10001570 | - | Aluminum | 2024 | 1 3/8" | DIA | ALUM 2024 AMS-QQ-A-225/6 TEMPER T351 | |
| 10001571 | - | CRES | 17-4 PH | 3 1/2" x 2" | DIA x L | CRES AMS 5643 H1075, 17-4PH | |
| 10001572 | - | Aluminum | 7075 | 2" x 4" x 4' | T x W x L | ALUM 7075 T651 | |
| 10001573 | - | Aluminum | 7075 | 4" x .500 +1/16 -0 | DIA x L | ALUM 7075 T651 | |
| 10001574 | - | Aluminum | 7075 | 4" x 5/16" +1/16-0 | DIA x L | ALUM 7075 T651 | |
| 10001575 | - | Nickel | TEMP COMPENSATOR | .015" x 2" | T x W | Y117A014-101 NiFe ALLOY | |
| 10001576 | - | CRES | 416 | 2 1/4" | DIA | ASTM-A582 TYPE 416 COND. A | |
| 10001577 | - | Aluminum | 6061 | .250"±.008 x 2 1/2 | T x W | ALUM 6061 ASTM B241 OR ASTM B221 TEMPER T651 | |
| 10001578 | - | Aluminum | 2024 | .090±.003 x 4.0±.0 x 4.4375"±.0 | | AMS-QQ-A-250/4 TEMPER T3 (1 SIDE FLAT WITHIN .003) | |
| 10001579 | - | CRES | 303 | 5 5/16 x 1+1/32-1/ | DIA x L | CRES ASTM A582 TYPE 303 COND A | |
| 10001580 | - | Nickel Iron | NICKEL IRON 49 | 15/16" | DIA | NICKEL IRON IAW Y202A014-1 COMP A | |
| 10001581 | - | CRES | 17-7 PH | .062"±.002 x .625" | T x W | AMS 5528 SOLUTION ANNEALED COLD FINISH | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-----------------|--------------------------|-----------|---|-------|
| 10001582 | - | CRES | 321 | 1/8" | DIA | AMS-QQ-S-763 CLASS 321 COND A | 86355 |
| 10001583 | C | CRES | 410 | 3/8" | DIA | ASTM A276/A276M COND. A | 90307 |
| 10001584 | - | CRES | 321 | 3/8" | DIA | AMS-QQ-S-763 CLASS 321 COND A | |
| 10001585 | - | CRES | 321 | 1 1/8" | DIA | AMS-QQ-S-763 COND A | |
| 10001586 | - | CRES | 321 | .125" x .010" | OD x WALL | MIL-T-8808 | |
| 10001587 | - | Steel | NITRIDING STEEL | 5/8" | DIA | SPEC MIL-S-6709 COMP A COND C2 | |
| 10001588 | - | Nickel Iron | NICKEL IRON 49 | .095" +.000 -.001 | DIA | Y202A014-105 NICKEL IRON 49 C'LESS GROUND 10001549 | |
| 10001589 | - | CRES | 321 | .099" ±.0005 | DIA | CRES AMS-QQ-S-763 CL 321 COND A C'LESS GROUND 10001582 | |
| 10001590 | - | CRES | 321 | .110" ±.0005 | DIA | CRES AMS-QQ-S-763 CL 321 COND A C'LESS GROUND 10001582 | |
| 10001591 | - | CRES | 303 | 3 1/4" x 1 1/8" | DIA x L | ASTM A582 TYPE 303 COND A | |
| 10001592 | - | CRES | 416 | .3100-.3097" | DIA | TYPE 416 COND T | |
| 10001593 | - | CRES | 321 | .1070" ±.0005 | DIA | CRES AMS-QQ-S-763 CL 321 COND. A - C'LESS GROUND 10001582 | |
| 10001595 | - | CRES | 321 | .500" x .065" | OD x WALL | MIL-T-8808 | |
| 10001596 | - | Aluminum | 2024 | 1/4" x 1/4" | SQ | AMS-QQ-A-225/6 TEMPER T4 | |
| 10001597 | - | Aluminum | 6061 | 2 3/4" | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001598 | - | Steel | 1018 | 9/16" | DIA | ASTM A108 GRADE 1018 | |
| 10001599 | - | Aluminum | 6061 | .040"±.005 x 1.825"±.050 | T x W | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001600 | - | CRES | 410 | 1/2" | DIA | CL 410 AMS-QQ-S-763 COND A | |
| 10001601 | - | CRES | 302 OR 304 | 3/64"±.005 x 2 1/8 | T x W | ASTM A666 TYPE 302 OR 304 COND. A, FLAT STRIP PACKAGE TO | |
| 10001602 | - | CRES | 13-8 MO | 1/4" | DIA | AMS 5629 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------|---------------------------------------|-----------|--|------|
| 10001603 | - | Aluminum | 2024 | .090"±.0005 x 4"±. x4.438"±.062 | T x W x L | AMS-QQ-A-250/4 TEMPER T3 ONE SIDE FLAT WITHIN .001" | |
| 10001604 | - | Aluminum | 2024 | 1/2" | DIA | AMS-QQ-A-225/6 TEMPER T3 | |
| 10001605 | - | Aluminum | 7075 | 1 1/4" x 1 1/2" | T x W | AMS-QQ-A-225/9 OR ASTM B211 TEMPER T7351 | |
| 10001606 | - | CRES | 304 | .060"±.005 x 2 3/4 | SQ | ASTM A240, ASTM A693,ASTM A666 CLASS 304 COND A | |
| 10001607 | - | Aluminum | 2024 | .090"±.005 x 2 3/4 x 3 3/8" | | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001608 | - | Misc | NITRONIC 60 | 3/4" | DIA | ASTM A276 UNS S21800 COND A | |
| 10001609 | - | Aluminum | 2024 | 3/8" x 4" | T x W | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001610 | - | Aluminum | 2024 | .090"±.005 x 3 3/8 x 4 7/8" | | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001611 | - | Aluminum | 2024 | 1/2" x 4" | T x W | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001612 | - | Aluminum | 6061 | 7/8±1/16 x 5 1/4 ± x 5 1/2±1/16 | | ALUM 6061-T651 AMS-QQ-A-250/11 OR ASTM B209 PLATE | |
| 10001613 | - | Aluminum | 2024 | 7 1/2" x 1 1/4"±1 | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001614 | - | Aluminum | 2024 | 2 1/4" x 4 3/8" x 5 1/8" | T x W x L | AMS-QQ-A-250/4 TEMPER T351 | |
| 10001615 | - | Aluminum | 6061 | 1/4"±1/64 x 3/4"±1/64 | T x W | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001616 | - | CRES | 17-4 PH | 15/16" | DIA | AMS 5643 COND H1075 | |
| 10001617 | - | Aluminum | 7075 | 3 3/4" x 4 1/2" | DIA x L | AMS-QQ-A-225/9 OR ASTM B211 TEMPER T7351 | |
| 10001618 | - | Steel | 4130 | 5/16" | DIA | MIL-S-6758 | |
| 10001619 | - | Steel | 12L14 | .125" | HEX | ASTM A108 GRADE 12L14 | |
| 10001620 | - | Steel | 4140 | 1 1/8" | DIA | MIL-S-5626 COND C4 (COLD DRAWN ANNEALED) | |
| 10001621 | - | Steel | 4130 | 3 1/4" x 5 3/8+1/8 | DIA x L | MIL-S-6758 4130 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|--------------------|-----------|--|-------|
| 10001622 | - | CRES | 321 | .250" x .020" | OD x WALL | MIL-T-8808 TYPE 1 | |
| 10001623 | - | CRES | 321 | .234" | DIA | AMS-QQ-S-763 CLASS 321 COND A | |
| 10001624 | - | CRES | 304L | 1/4" | DIA | AMS-QQ-S-763 CLASS 304L COND A | |
| 10001625 | - | CRES | 440C | 5/8" | DIA | QQ-S-763 CLASS 440C COND A | |
| 10001626 | - | Aluminum | 6061 | 7"±1/16 x 5/8±1/16 | DIA x L | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 | |
| 10001627 | - | CRES | 304 | 5/16" x .010" | OD x WALL | TYPE 304 SS TUBING AMS 5566 | |
| 10001628 | - | CRES | 17-4 PH | 1 1/2" x 3" | SQ x L | AMS 5643 COND H1075 | |
| 10001629 | - | Steel | 4130 | 1/4" | DIA | AMS-S-6758 | |
| 10001630 | - | Steel | 1018 | 3/4" | DIA | ASTM A108 GRADE 1018 | |
| 10001631 | - | CRES | 440C | 3/8" | DIA | QQ-S-763 CL 440C COND A | |
| 10001632 | - | Steel | 4130 | 5/8" | DIA | MIL-S-6758 | |
| 10001633 | - | Steel | 4130 | 1 5/8" | DIA | MIL-S-6758 | |
| 10001634 | A | Aluminum | 6061 | 5" x 3" +1/8 -0 | DIA x L | ASTMB241 OR ASTMB241M OR AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | 73071 |
| 10001635 | - | Aluminum | 2024 | 5" x 3" +1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001636 | - | Steel | 1006 | 3 3/4" x 1 1/4"+1/ | DIA x L | ASTM A29 GRADE 1006 | |
| 10001637 | - | Steel | 4140 | 13/16" | DIA | MIL-S-5626 COND C4 (CF ANNEALED) | |
| 10001638 | - | Brass | BRASS 360 | 1 13/16 | DIA | BRASS TYPE 360 1/2 HARD IAW AMS 4610, ASTM B16 | |
| 10001639 | - | Brass | BRASS 260 | .016" | T | AMS 4507 OR ASTM B36 ALLOY C26000 TEMPER H02 (1/2 HARD) | |
| 10001640 | - | Aluminum | 2024 | 5" x 1" +1/8-0 | DIA x L | AMS-QQ-A-225/6 TEMPER T351 | |
| 10001641 | - | Steel | 4130 | 1 3/8" | DIA | MIL-S-6758 COND D4 (CD, NORMALIZED) | |
| 10001642 | - | CRES | 304 | 3/8" x .028" | OD x WALL | TYPE 304 SS TUBING AMS 5566 | |
| 10001643 | - | Nickel Iron | NICKEL IRON 49 | .2190 ±.0005 | DIA | Y202A014-105 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------|--------------------------|-----------|---|-------|
| 10001644 | - | CRES | 304 | 1.0" x .120" | OD x WALL | TYPE 304 SS TUBING MIL-T-8504 | |
| 10001645 | - | Steel | 1018 | 4" x 1/2" +1/8-0 | DIA x L | ASTM A108 GRADE 1018 COLD FINISHED | |
| 10001647 | - | Steel | 1018 | 2 11/16" ±1/16" | DIA | ASTM A108 GRADE 1018 | |
| 10001648 | - | CRES | 304 | 7/16" | DIA | AMS-QQ-S-763 CL 304 COND A | |
| 10001649 | - | Steel | 4140 | 9/32" | DIA | MIL-S-5626 COND C4 (CF ANNEALED) | |
| 10001650 | - | CRES | 416 | 3/8" | DIA | ASTM A582 TYPE 416 COND A | |
| 10001651 | - | Plastic | PHENOLIC | 3/16" x .096" | OD x ID | PHENOLIC IMPREGNATED PAPER TUBING PER MIL-P-79 TYPE PBG | |
| 10001652 | - | Steel | 4130 | 1 1/8" | DIA | MIL-S-6758 COND D4 (CD, NORMALIZED) | |
| 10001653 | - | Steel | 12L14 | 2 9/32" | DIA | ASTM A108 GRADE 12L14 | |
| 10001654 | A | Steel | 8620 | .3125+.0000/- .0005 | DIA | ANNEAL COLD FINISH PER SAE AMS6274 OR ASTM A108 | 86773 |
| 10001655 | - | Steel | 1215 | 2" | DIA | ASTM A108 GRADE 1215 ANNEALED | |
| 10001656 | - | Steel | 1010 | 2" | DIA | ASTM A108 GRADE 1010 ANNEALED | |
| 10001657 | - | Iron | IRON | 1 3/4" | DIA | ASTM A48 CLASS NO. 40C | |
| 10001658 | - | Steel | MARAGING STEEL | 33/64" | DIA | 18% NICKEL MARAGING STEEL MIL-S-46850 TYPE 3 GRADE 250 | |
| 10001659 | - | Steel | MARAGING STEEL | 35/64" | DIA | 18% NICKEL MARAGING STEEL MIL-S-46850 TYPE 3 GRADE 250 | |
| 10001660 | - | Steel | 4130 | 3/64" | DIA | MIL-S-6758 | |
| 10001661 | - | Steel | 4340 | 1/16" | DIA | 4340 MOLYBDENUM ST'L MIL-S-5000 COND. C AMS 6415 | |
| 10001662 | - | Steel | 12L14 | 5" | DIA | ASTM A108 GRADE 12L14 | |
| 10001663 | - | Steel | 1005 | 3 5/8" | DIA | 1005 MILD STEEL ASTM-A29 SMOOTH FORGED TO FINISH 3 5/8" | |
| 10001664 | - | Steel | 4140 | .750 | DIA | MIL-S-5626 COND C4 (CF ANNEALED) | |
| 10001665 | - | Steel | 4130 | .375 ±.0005 | DIA | MIL-S-6758 | |
| 10001666 | - | Aluminum | 6061 | 1.250" ±.005 x 1.194" | OD x ID | ALUM 6061-T6 TUBING PER ASTM B241 OR ASTM B221 | |
| 10001667 | - | Misc | A-286 | 1/4" | DIA | AMS 5737 | |
| 10001668 | - | Aluminum | 6061 | 3/8" x 1 1/4" | T x W | ASTM B241 OR ASTM B221 TEMP T6510 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------|-----------------------------|---------|--|------|
| 10001669 | - | Steel | 6150 | .373" +.0000- .0005 | DIA | COLD DRAWN ANNEALED AND GROUND, MIL-S-8503 OR AMS 6448 | |
| 10001670 | - | Plastic | EPOXY ROD | 3/32" | DIA | BLACK EPOXY ROD HYSOL #4278 OR EQUIV. | |
| 10001671 | - | Steel | 4130 | .5620 ± .005 | DIA | MIL-S-6758 | |
| 10001672 | - | Steel | 4340 | .780" ± .0005 | DIA | AMS 6415 COLD DRAWN, GROUND, AND ANNEALED | |
| 10001673 | - | Aluminum | 2024 | 3" | DIA | AMS-QQ-A-225/6 TEMP T351 | |
| 10001674 | - | Aluminum | 2024 | 3/4" x 2 1/4" | T x W | AMS-QQ-A-250/4 TEMP T351 | |
| 10001675 | - | Steel | 4140 | .1873 - .1878 | DIA | MIL-S-5626 | |
| 10001676 | - | CRES | 15-5 PH | 13/16" | DIA | AMS 5659 COND H1100 | |
| 10001677 | - | Brass | BRASS 260 | .020"±.00065 x 2 5/8" | T x W | ASTM B36 ALLOY C26000 TEMPER H02 (1/2 HARD), 100 LB ROLL | |
| 10001678 | - | Steel | 1215 | 1 9/16" | DIA | ASTM A108 GRADE 1215 | |
| 10001679 | - | Steel | 4130 | .780 ±.0005 | DIA | COLD DRAWN, NORMALIZED MIL-S-6758 | |
| 10001680 | - | Steel | 4340 | .250 +.0000 - .0005 | DIA | 4340 MOLYBDENUM IAW MIL-S-5000 COND. C AMS 6415 | |
| 10001681 | - | Aluminum | 7075 | 1/2" X 2" | T x W | SAE AMS 4078 7075-T7351 | |
| 10001682 | - | Copper | COPPER, ETP | .051 (16 GA.) | DIA | COPPER TYPE 110 SOFT TEMPER, BARE IAW ASTM B-3 | |
| 10001683 | - | Steel | 4130 | 3/8" | DIA | AMS-S-6758 | |
| 10001684 | - | Steel | 1095 | .060-.064" x 2" x 48" LG | | CARBON STEEL 1095 RB 88 MAX | |
| 10001685 | - | Aluminum | 6061 | 1/2" x 1" | T x W | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001686 | - | Steel | 6150 | 13/32" | DIA | MIL-S-8503 | |
| 10001687 | - | CRES | 304 | .750 | DIA | AMS-QQ-S-763 CL 304 COND A | |
| 10001688 | - | Misc | | | | | |
| 10001689 | - | Aluminum | 2024 | .025"±.003 x .615± | T x W | AMS-QQ-A-250/4 TEMPER T3 | |
| 10001690 | - | CRES | 416 | 3 3/4" x 1"+1/8-0 | DIA x L | ASTM A582 TYPE 416 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-----------|-----------------------|-----------|--|-------|
| 10001691 | C | CRES | 321 | .250" x .035" | OD x WALL | IAW MIL-T-8808 TYPE 1 MATERIAL TO BE SELECTED TO MEET I.D. REQUIREMENTS OF .187/.179, MOOG APPROVED SUPPLIER REQUIRED | 86190 |
| 10001692 | - | Aluminum | 6061 | 1/8" x 1/2" | T x W | ASTM B241 OR ASTM B221 TEMPER T6 | |
| 10001693 | - | Aluminum | 7075 | 1/2" x 1/2" | SQ | AMS-QQ-A-225/9 OR ASTM B211 TEMPER T651 | |
| 10001694 | - | Aluminum | 6061 | 1" x 1" | SQ | ALUM 6061 T6 IAW ASTM B241 OR ASTM B221 | |
| 10001695 | - | Steel | 4130 | 1 7/8" | DIA | MIL-S-6758 | |
| 10001696 | - | Steel | 4140 | 3/8" | DIA | MIL-S-5626 OR AMS 6382 | |
| 10001697 | - | Steel | 4130 | 7/16" | DIA | MIL-S-6758 | |
| 10001698 | - | Steel | 4130 | 2 1/2" | DIA | MIL-S-6758 | |
| 10001699 | - | Brass | BRASS 360 | 5/16" | DIA | BRASS 360 ALLOY PER ASTM B16 | |
| 10001700 | - | Aluminum | 2024 | 1/4 ±1/64 x 1/2" ± | T x W | AMS-QQ-A-250/4 TEMPER T351 | |
| 10001701 | - | Aluminum | 2024 | 1/2 ±1/64 x 5/8" ± | T x W | AMS-QQ-A-250/4 TEMPER T351 | |
| 10001702 | - | CRES | 321 | 5/16" x .010" | OD x WALL | MIL-T-8808 TYPE 1 | |
| 10001703 | - | Steel | 1095 | 1 1/4" | DIA | 1095 STEEL | |
| 10001704 | - | Steel | 4130 | 5/16" | DIA | CD, NORMALIZED, MIL-S-6758 COND. D4 | |
| 10001705 | - | CRES | 15-5 PH | 11/16" | DIA | 15-5PH IAW AMS 5659 H1025 | |
| 10001706 | - | CRES | 304L | 5/8" | DIA | CL 304L IAW AMS-QQ-S-763 COND. A | |
| 10001707 | - | CRES | 321 | 1.00" x 0.120" | OD x WALL | MIL-T-8808 TYPE 1 | |
| 10001708 | - | Aluminum | 6061 | 3 1/8 x 5" +1/8 -0 | DIA x L | ALUM 6061 T651 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001709 | - | Brass | BRASS 260 | .025±.005 x 3/4" | T x W | ASTM B36 ALLOY C26000 ANNEALED TEMPER, BRASS | |
| 10001710 | - | Steel | 1215 | 3 1/8 x 4 1/2±1/8 | DIA x L | STEEL 1215 ALLOY, COLD FINISHED PER ASTM A108 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|--------------------|---------|--|------|
| 10001711 | - | Aluminum | 7075 | 1 1/4" | DIA | ALUMINUM 7075 T7351, AMS-QQ-A-225/9 OR ASTM B211 | |
| 10001712 | - | Steel | 1215 | 5/16" | DIA | 1215 CF STEEL, ASTM A108 | |
| 10001713 | - | Aluminum | 2024 | 1 3/4" | DIA | ALUMINUM 2024 T351, AMS-QQ-A-225/6 | |
| 10001714 | - | Aluminum | 6061 | 1/2 x 3/8 | T x W | ALUMINUM 6061-T6 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001715 | - | Aluminum | 6061 | 6 3/4 x 5/8 ±1/8 | DIA | ALUM 6061, TEMPER T651, AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001716 | - | Misc | 4620 | 3/4" | DIA | 4620 ALLOY PER ASTM A-331 | |
| 10001717 | - | Aluminum | 6063 | 1/2" x 1/2 x 1/16 | L SHAPE | ALUMINUM 6063 T-52 EXTRUDED STRIP, ASTM B241 OR ASTM B221 L-SHAPED | |
| 10001718 | - | Aluminum | 6061 | .063 x 2 3/8 x 4' | T x W | ALUMINUM 6061-T6, AMS-QQ-A-250/11 OR ASTM B209 STRIP STOCK | |
| 10001719 | - | Aluminum | 2024 | 1 1/4 x 2 3/8 x 4' | T x W | ALUMINUM 2024-T351, AMS-QQ-A-250/4 STRIP STOCK | |
| 10001720 | - | Aluminum | 2024 | .250 ±.003 | HEX | ALUMINUM 2024-T4, QQ-A-225/6 | |
| 10001721 | - | CRES | 17-4 PH | .3765-.3762 | DIA | 17-4PH CRES AMS-5643 COND. H-1025 C'LESS GROUND | |
| 10001722 | - | Aluminum | 7075 | 3/8" x 5/8" | T x W | ALUMINUM 7075-T6511, ASTM B241 OR ASTM B221 | |
| 10001723 | - | Steel | 4340 | 1 1/2" | DIA | 4340 CHROME MOLY STEEL PER MIL-S-5000 | |
| 10001724 | - | Steel | 4340 | 7/8" | DIA | 4340 CHROME MOLY STEEL PER MIL-S-5000 COND. C4 | |
| 10001725 | - | Steel | 1020 | 1 5/8" | DIA | 1020 COLD ROLLED STEEL PER AISI-1020 | |
| 10001726 | - | CRES | 303 | 5 mm | DIA | CRES 303 COND. A, ASTM A582 | |
| 10001727 | - | CRES | 17-4 PH | 5/8" x 1/2 x 4' | T x W | 17-4PH CRES COND. A | |
| 10001728 | - | Nylon | NYLON | 3/8" | DIA | NYLON L-P-410 | |
| 10001729 | - | Steel | 4340 | 13/16" | DIA | 4340 CHROME MOLY STEEL PER MIL-S-5000 | |
| 10001730 | - | Aluminum | 7075 | 2 3/4" | DIA | ALUMINUM 7075-T651, AMS-QQ-A-225/9 OR ASTM B211 | |
| 10001731 | - | CRES | 347 | .750 | DIA | CL 347 COND. A, IAW AMS-QQ-S-763 | |
| 10001732 | - | CRES | 304L | .3125 | DIA | CL 304L COND. A, IAW AMS-QQ-S-763 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|---------------------|--------------------|------------|--|------|
| 10001733 | - | CRES | 304 | 1" x .870 | OD x ID | CRES 304 TUBING PER MIL-T-8504 | |
| 10001734 | - | Nickel Iron | NICKEL IRON 49 | .3125 | DIA | CARPENTER 49 IAW MIL-N-14411 COMP 3 | |
| 10001735 | - | CRES | 321 | .3125 x .016 | OD x WALL | TYPE 321 TUBING IAW MIL-T-8808, COND A, TYPE 1, SEAMLESS | |
| 10001736 | - | CRES | 347 | 1.250 | DIA | CL 347 COND. A, IAW AMS-QQ-S-763 AND C200111489 | |
| 10001737 | - | CRES | 321 | .875 x .065 | DIA | CL 321 COND. A, IAW MIL-T-8808 .875 X .065 NOM. WALL | |
| 10001738 | - | Brass | BRASS | .010 x 5/8" | T x W | BRASS STRIP, ASTM B36 ALLOY 260, 1/2 HARD | |
| 10001739 | - | Aluminum | 6061 | 1/2" | DIA | ALUMINUM 6061 PER AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | |
| 10001740 | - | Aluminum | 2024 | .025 ±.003 x 1.12 | T x W | ALUMINUM 2024 T3, AMS-QQ-A-250/4 .025 ±.003 X 1.12 ±.01 WD | |
| 10001741 | - | Steel | STEEL | .028-.032 x 1 1/4" | T x W | COLD ROLL CARBON STEEL, .13 MAX CARBON, ASTM A-366 6'LG | |
| 10001742 | - | CRES | 347 | 7/8 x .049 | DIA x WALL | CL 347 COND A, MIL-T-8808 | |
| 10001743 | - | Aluminum | 5052 | 1" x 6" | T x W | ALUMINUM 5052-H32, AMS-QQ-A-250/8 FLAT BAR | |
| 10001744 | - | Steel | STEEL | 3/4" | DIA | VNADIUM STEEL 6150 | |
| 10001745 | - | CRES | 303 | 1 5/8" | DIA | 303 SS PER ASTM A-582 COND. A | |
| 10001746 | - | Aluminum | 6061 | 1/2" x 1 1/4" | T x W | ALUMINUM 6061 PER ASTM B241 OR ASTM B221 TEMPER T6510 | |
| 10001747 | - | Nickel | TEMP COMPENSATOR 30 | .017 x 1.100 | T x W | TEMP COMPENSATOR #30 TYPE 2 CARPENTER ALLOY - STRIP | |
| 10001748 | - | Aluminum | 6061 | 5/16" x 1 1/4" | T x W | ALUMINUM 6061 PER AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001749 | - | CRES | 17-4 PH | 1 3/4" x 1 3/4" | T x W | 17-4PH PER CRES AMS 5643, COND. H1075 | |
| 10001750 | - | CRES | 17-4 PH | 1" x 1 3/4" | T x W | CRES AMS 5643 COND. H1075 , 17-4PH | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|----------------|------------------------------------|-----------|--|-------|
| 10001751 | - | Misc | A-286 | 3/8" | DIA | A-286 CRES IAW AMS 5737 | |
| 10001752 | - | CRES | 304L | 1" | DIA | 304L IAW AMS-QQ-S-763 | |
| 10001753 | - | CRES | 17-4 PH | 2 7/8" | DIA | 17-4PH IAW CRES AMS 5643 COND. H1075 | |
| 10001754 | - | Steel | 4130 | 1.250 x .049 | OD x WALL | AMS 6360 OR MIL-T-6736 SEAMLESS TUBING 4130 STEEL | |
| 10001755 | - | Aluminum | 6061 | 1/4" x 5" x 8" | T x W | ALUMINUM 6061 PLATE PER AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001756 | - | Aluminum | 6061 | 4" x 5" x 8" | T x W | ALUMINUM 6061 PLATE PER AMS-QQ-A-250/11 OR ASTM B209 TEMPER T651 | |
| 10001757 | - | Aluminum | 6061 | .090 x 2.500± .010 | T x W | ALUMINUM 6061 STRIP PER AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001758 | A | Aluminum | 6061 | 1.00" X 1/2" | T x W | SAE AMS4027 T651 | 87946 |
| 10001759 | - | Aluminum | 6061 | 1 3/4" x 1/2" | T x W | ALUMINUM 6061 RECT. BAR PER AMS-QQ-A- 250/11 OR ASTM B209 TEMPER T651 | |
| 10001760 | A | Steel | 1215 | 3 1/4" x 4 1/2" | D X L | PER ASTM A108 COLD FINISHED | 78159 |
| 10001761 | - | CRES | 416 | .312 ±.003 | T x W | 416 COND. A, CRES SQUARE STOCK | |
| 10001762 | B | CRES | 347 | .875+/-0.005 X .811+.002/-0.000 | OD x ID | IAW MIL-T-8808 LENGTH 6' TO 8' | 77706 |
| 10001763 | - | Brass | BRASS | .020±.00065 x 2 1/16 | T x W | ASTM B36 ALLOY 260(UNS C26000)ROCK B 60- 65,100 LB ROLL | |
| 10001764 | - | CRES | 416 | 5/16" | DIA | 416 SS COND. A, ASTM-A-582 | |
| 10001765 | - | Nickel Iron | NICKEL IRON 49 | 4.050 +.250/.000 | DIA | ASTM-A-753 ALLOY 2, STOCK IS FORGED & IS IN 6" LONG PIECES | |
| 10001766 | - | Nickel Iron | NICKEL IRON 49 | 5.75 + 3/4 - .00 | DIA | ASTM A 753 ALLOY 2 | |
| 10001767 | - | Aluminum | 6061 | 1" x 1" x .125 | T x W | ALUM 6061 PER AMS-ASTM B241 OR ASTM B221 TEMPER T6, L SHAPE EXTRUSION | |
| 10001768 | - | Steel | 4130 | .032±.005 x 2.125 | T x W | 4130 STEEL PER MIL-S-18729, .032 THK X 2.125 +000/-0.015 | |
| 10001769 | - | CRES | 17-4 PH | 3 3/8 x 4 | DIA | 17-4PH PER AMS 5643 COND. A - CONFIG. CONTROL -IFC PROG. | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------------|-----------------------------------|-----------|---|-------|
| 10001770 | A | CRES | 316 | .016 +/- .002 X 1.125 +/- 1/64 | T x W | PER ASTM A666, ANNEALED | 78434 |
| 10001771 | - | CRES | 347 | 1/4" | DIA | CL 347 SS COND A, IAW C200111489 | |
| 10001772 | - | Misc | TITANIUM | 1 1/8" | DIA | ASTM-B348 GRADE 2 (CP) | |
| 10001773 | - | CRES | 347 | .812+.005 x .655 | OD x ID | CRES 347 IAW MIL-T-8808 TY 1 SEAMLESS, .655+.0/-0.005 ID | |
| 10001774 | B | Steel | 1018 | 1 3/8" | DIA | 1018 PER ASTM A108 ANNEALED | 75950 |
| 10001775 | - | Bronze | BRONZE, PHOSPHOR | 1/2" | DIA | PHOSPHOR BRONZE, ALLOY C54400, ASTM B139 | |
| 10001776 | - | Steel | 4620 | 5/8" | DIA | 4620 MOLYBDENUM STEEL PER ASTM A331 | |
| 10001777 | - | Misc | NITRONIC 60 | 5/16" | DIA | NITRONICS 60 | |
| 10001778 | - | Steel | 4130 | 1 1/4" | DIA | MIL-S-6758 4130 CHROME MOLY | |
| 10001779 | - | CRES | 416 | 5" x 5.5 x 3/4 | W x L x T | ASTM A582 TYPE 416 COND. A | |
| 10001780 | - | CRES | 416 | 6 ±.015 x 3.375 | DIA | ASTM A582 TYPE 416 COND. A 6.00 ±.015 X 3.375 ±.030 | |
| 10001781 | - | CRES | 416 | .250 ±.010 | DIA | TYPE 416 COND. H HEXAGON | |
| 10001782 | - | CRES | 440C | 3/4" | DIA | CRES QQ-S-763 CLASS 440 C COND. A | |
| 10001783 | - | CRES | 416 | 2 1/4 x 3 1/8 x 5 | W x L | TYPE 416 COND. A 2 1/4 X 3 1/8 X 5 3/8" | |
| 10001784 | - | Aluminum | 6061 | 6" x 1 7/8 ±1/32 | DIA x L | ALUM 6061 T6 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001785 | A | Aluminum | 6061 | .375 x 1.250 +/- .015 | T x W | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 | 88010 |
| 10001786 | - | CRES | 440C | 1 3/8" | DIA | QQ-S-763 CL 440 C COND. A | |
| 10001787 | - | Plastic | ACETAL PLASTIC | 3/4" | DIA | ACETAL PLASTIC PER FED. SPEC. L-P-392 TYPE 1, CLASS 3 | |
| 10001788 | - | CRES | 440C | 1 7/8" | DIA | QQ-S-763 CL 440 C COND. A | |
| 10001789 | - | Aluminum | 6061 | 1/2" x 2" | T x W | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 FLAT STOCK | |
| 10001790 | - | CRES | 347 | 2 1/4" | DIA | AMS-QQ-S-763 347 STAINLESS STEEL | |
| 10001791 | - | CRES | 347 | 1" | DIA | AMS-QQ-S-763 347 STAINLESS STEEL | |
| 10001792 | - | CRES | 304 | 1 5/8" | DIA | AMS-QQ-S-763 COND A CL 304 L | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-------------|--------------------|-----------|---|-------|
| 10001793 | - | Aluminum | 6061 | 4" x 5" | DIA x L | ALUM 6061 TEMPER T651 AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001794 | - | CRES | 17-4 PH | 4 1/4 x 1 1/2 | DIA x L | CRES AMS 5643 COND. H 1075 | |
| 10001795 | - | CRES | 17-4 PH | 4-1/4" x 12" | DIA x L | CRES AMS5643 COND H1075 4-1/4" X 12" +0 - 1/8" | |
| 10001796 | - | CRES | 17-4 PH | 4" x 5 x 6 3/4 | T x W x L | AMS 5643 COND H 1075 4" THK X 5" WD X 6 3/4" LONG | |
| 10001797 | - | CRES | 17-4 PH | 1 1/4 x 4 x 6 3/4 | T x W x L | AMS 5643 COND H 1075 1 1/4 THK X 4" WD X 6 3/4" LONG | |
| 10001798 | - | Steel | 4340 | 1 5/8" | DIA | 4340 CHROME-NICKEL-MOLY STEEL PER MIL-S-5000 COND E4 | |
| 10001799 | - | Misc | INCONEL 718 | 2.000 +.025 - .000 | DIA | AMS 5662 OR AMS 5664 CORROSION & HEAT RESISTANT ALLOY | |
| 10001800 | - | CRES | 321 | .1562 x .144 | OD x ID | SEAMLESS 321 1/8 HARD TUBING PER MIL-T-8973 .006 WALL | |
| 10001801 | - | Nickel Iron | HY MU 80 | .010±.002 x 9.5 | T x W | HY MU 80 PER Y059A005-222 (CARPENER TECH.) | |
| 10001802 | - | Aluminum | 6061 | 2 1/4 x 3 1/2 | T x W | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001803 | - | Aluminum | 6061 | 2 3/4" | SQ | AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 | |
| 10001804 | - | CRES | 416 | 3" | DIA | ASTM A582 TYPE 416 COND. H | |
| 10001805 | - | CRES | 17-4 PH | 1/2" | DIA | AMS 5643 COND. H 1075 | |
| 10001806 | B | Steel | 9310 | 3/4" | DIA | PER SAE-AMS 6265 | 86652 |
| 10001807 | - | Steel | 9310 | 2 1/4" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001808 | A | Steel | 9310 | 1 3/4" | DIA | PER SAE-AMS 6260 | 78815 |
| 10001809 | - | CRES | 416 | 2 1/4 x 1 3/4 | T x W | TYPE 416 COND. A | |
| 10001810 | - | Aluminum | 6061 | 2" x 1 3/4" | T x W | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001811 | A | Aluminum | 6061 | 2 5/8" | DIA | ASTM B211 OR ASTM B221 TEMPER T6511 | 79083 |
| 10001812 | - | Steel | 9310 | 1" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|-----------------------|--------------|--|------|
| 10001813 | - | Aluminum | 6063 | 3/8" x 1/2" | T x W | ALUM 6063 PER ASTM B241 OR ASTM B221 TEMPER T32 | |
| 10001814 | - | Aluminum | 6061 | 1 1/2" | DIA | ALUM 6061 AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 | |
| 10001815 | - | Aluminum | 6061 | 1 3/4" | DIA | ALUM 6061 T6 AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001816 | - | Nylon | NYLON | 3 1/2 x 5 1/4 +1/8 | DIA x L | NYLON LP410 3 1/2 DIA X 5 1/4 +.125 -.000 | |
| 10001817 | - | CRES | 304 | 1 3/4 x .375 | OD x WALL | 304 SEAMLESS ASTM A511 HOT FINISH 1 3/4 OD X .375 WALL | |
| 10001818 | - | Steel | 1215 | 5 1/4 x 5 3/4 | DIA x L | 1215 STEEL PER AMS 5010 5 1/4 X 5 3/4 +.125 - .000 | |
| 10001819 | - | Steel | 1215 | 3 3/4 x 3 1/2 | DIA x L | 1215 STEEL PER AMS 5010 3 3/4 X 3 1/2 +.125 - .000 | |
| 10001820 | - | Steel | 9310 | 2 3/4" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001821 | - | Steel | 9310 | 2" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001822 | - | Steel | 9310 | 1 7/16" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001823 | - | Steel | 9310 | 1.250" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001824 | - | Steel | 9310 | 1 1/2" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001825 | - | CRES | 416 | 1.125 ±.015 | DIA | TYPE 416 COND. T | |
| 10001826 | - | Aluminum | 6061 | 2" x 3" | T x W | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001827 | - | Aluminum | 6061 | 2" x 1 1/4" | T x W | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001828 | - | Aluminum | 6061 | 4" x 1/2" | DIA x L | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 OR EQUIV. | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------------|------------------|--------|---|------|
| 10001829 | - | Aluminum | 6061 | .750 ±.003 | DIA | ALUM 6061 AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 HEX STOCK | |
| 10001830 | - | Aluminum | 6061 | 7/8" x 1/2" | T x W | ALUM 6061 AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 RECT BAR | |
| 10001831 | - | Bronze | BRONZE, LEADED | 3/4" | DIA | LEADED BRONZE PER SAE CA932, ASTM B505 | |
| 10001832 | - | CRES | 304 | 2.500 ± 1/64 | DIA | 304 CRES BAR ANNEALED PER AMS 5639 OR AMS-QQ-S-763 | |
| 10001833 | - | CRES | 303 | .250 ± .015 | DIA | 303 CRES BAR ANNEALED PER AMS 5640 TYPE 1 | |
| 10001834 | - | CRES | 17-4 PH | 1.250 ±.015 | DIA | 17-4PH CRES BAR HEAT TREAT TO COND H1025, RC 34-42 | |
| 10001835 | - | CRES | 304 | .063 ±.005 x 4' | T x W | 304 CRES PER AMS 5913 SHEET STOCK | |
| 10001836 | - | CRES | 416 | 3/8" x 5/8" | T x W | 416 COND. A PER ASTM-A582 RECT STOCK | |
| 10001837 | - | Steel | 9310 | 1/2" | DIA | 9310 STEEL ANNEALED AND COLD FINISHED PER ASTM A331 | |
| 10001838 | - | CRES | 304L | 1.250 | DIA | CL 304L CRES PER AMS-QQ-S-763 COND. A | |
| 10001839 | - | CRES | 13-8 MO | 0.25 | DIA | AMS-5629 COND. H1000 | |
| 10001840 | - | CRES | 321 | .750 | DIA | CL 321 CRES AMS-QQ-S-763 COND. A | |
| 10001841 | - | Aluminum | 2024 | 3" x 3" | T x W | ALUM 2024 PER AMS-QQ-A-225/6 TEMPER 351 RECT BAR | |
| 10001842 | - | CRES | 17-4 PH | 2 7/16" | DIA | 17-4PH PER AMS-5643 COND. H1025 | |
| 10001843 | - | CRES | 17-4 PH | 1" | DIA | 17-4PH PER AMS-5643 COND. H1025 | |
| 10001844 | - | Aluminum | 6061 | 5.00" x 1/2±1/64 | DIA | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001845 | - | Steel | 1215 | 1 5/8" | DIA | 1215 STEEL PER AMS-5010 | |
| 10001846 | - | Aluminum | 2024 | 3 3/8 x 3 ±1/8 | DIA | ALUM 2024 T351 PER AMS-QQ-A-225/6, SLUG | |
| 10001847 | - | CRES | 304 | 5/8" | DIA | 304 CRES BAR, ANNEALED PER AMS-QQ-S-763 | |
| 10001848 | - | Aluminum | 6061 | 1" | DIA | ALUM 6061 T651 PER AMS-QQ-A-225/8 OR ASTM B211, HEX STOCK | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|-----------------------|---------------|---|------|
| 10001849 | - | Aluminum | 6061 | 3 1/8 x 2 +1/8 -0 | DIA | ALUM 6061 T6 PER AMS-QQ-A-225/8 OR ASTM B211, SLUG | |
| 10001850 | - | CRES | 304 | 1/4 x .028 | OD x WALL | 304 TUBING CRES SEAMLESS PER AMS-T-8506, .028 WALL THK. | |
| 10001851 | - | Aluminum | 6061 | .050 x 4' | T x W | ALUM 6061 T6 SHEET PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001852 | - | CRES | 304 | 4 1/2 x 3/4 x 4" | OD/WAL L/L | ASTM A511 SEAMLESS GRADE MT304 ANNEALED, 4 1/2 X 3/4 X 4 | |
| 10001853 | - | Misc | TORLON | 1" | DIA | TORLON ROD PER AMS-3670/3 | |
| 10001854 | - | Misc | TORLON | 5/16" | DIA | TORLON 4301 ROD PER AMS-3670/3 | |
| 10001855 | - | CRES | 17-4 PH | 1/4" | DIA | 17-4PH HEX BAR PER AMS-5643, COND. H1075 | |
| 10001856 | - | CRES | 304 | 3/8" | DIA | 304 SS COND. A PER AMS-QQ-S-763 | |
| 10001857 | - | Aluminum | 6061 | .050 x 4' | T x W | AMS-QQ-A-250/11 OR ASTM B209 OR AMS 4026, TEMPER T4 | |
| 10001858 | - | CRES | 17-4 PH | 2 1/4" | DIA | 17-4PH PER AMS-5643, COND. H1150 | |
| 10001859 | - | Aluminum | 7075 | 1 3/8" | DIA | ALUM 7075 T7351 PER SAE AMS 4124 OR AMS- QQ-A-225/9 | |
| 10001860 | - | Aluminum | 2024 | .688 ±.003 | DIA | ALUM 2024 T351 PER AMS-QQ-A-225/6, HEX BAR | |
| 10001861 | - | Steel | STEEL | .250 x 24 | W x GAUGE | STEEL ASTM A109 CR TEMPER NO. 3, 1/4 H | |
| 10001862 | - | Aluminum | 6061 | 3 1/8" | DIA | ALUM 6061 T651 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001863 | - | Aluminum | 2024 | 5/8" | DIA | ALUM 2024 T351 PER AMS-QQ-A-225/6 | |
| 10001864 | - | CRES | 321 | 2.995 x .066/07 | ID x WALL | TYPE 321 WELDED TUBE, AMS 5575, ANL FULL FIN. & SMOOTH | |
| 10001865 | - | CRES | 321 | 4 1/2 x 4 1/2 +1/8 | DIA | 321 CRES AMS-QQ-S-763 ANNEALED, 4 1/2 X 4 1/2 +1/8 -0 | |
| 10001866 | - | CRES | 17-4 PH | 5/8" | DIA | 17-4PH CRES PER AMS-5643 COND. H1025 | |
| 10001867 | - | CRES | 17-4 PH | 3/8 x 1 1/8 | T x W | 17-4PH CRES AMS-5643 COND. H1050, RECT. | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|-------------------|-----------|---|--------------------------------|
| 10001868 | - | Steel | CARBON STEEL | 5.06 x .375±.005 | L x W | STEEL CLASS B, GRADE 1 MIL-S-13281 30,000 PSI, .09 THK | |
| 10001869 | - | Steel | CARBON STEEL | 6.312 x .375±.005 | L x W | STEEL CLASS B, GRADE 1 MIL-S-13281 30,000 PSI, .09 THK | |
| 10001870 | A | CRES | 17-4 PH | 15/16" | DIA | SAE AMS5643 HEAT TREATED TO COND. H1150 IAW SAE AMS2759/3 | NOC-83033 RN 5R340-1 7/23/2012 |
| 10001871 | - | CRES | 17-4 PH | 5/16 | DIA | 17-4PH CRES AMS-5643 COND. H1150 | |
| 10001872 | - | CRES | 17-4 PH | 2 1/8" | DIA | 17-4PH CRES AMS-5643 COND. A | |
| 10001873 | - | CRES | 304L | 2.250 | DIA | 304L CL CRES AMS-QQ-S-763 COND. A | |
| 10001874 | B | CRES | 321 | .1562 x .016 | OD x WALL | 321 CRES TUBING PER MIL-T-8808, .016 NOM. WALL | 87209 |
| 10001875 | - | CRES | 304L | 2.625 | DIA | ASTM A276 COND. A | |
| 10001876 | - | CRES | 17-4 PH | .3110-.3105 | DIA | 17-4PH CRES PER AMS-5643 COND. A, CENTERLESS GROUND | |
| 10001877 | - | CRES | 321 | 5/16 | DIA | 321 CRES PER AMS-QQ-S-763 OR AMS-5645, COND. A | |
| 10001878 | - | Aluminum | 6061 | 11/16" | DIA | ALUM 6061 T651 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001879 | - | CRES | 321 | 2.250 | DIA | 321 CL CRES AMS-QQ-S-763, COND. A | |
| 10001880 | - | CRES | 321 | .750 x .035 | OD x WALL | 321 PER MIL-T-8808 TYPE 1, COND. A, SEAMLESS | |
| 10001881 | - | CRES | 321 | .375 x .020 | OD x WALL | 321 PER MIL-T-8808 TYPE 1, COND. A, SEAMLESS | |
| 10001882 | - | CRES | 321 | .3125 x .035 | OD x WALL | 321 PER MIL-T-8808 TYPE 1, COND. A, SEAMLESS | |
| 10001883 | - | Aluminum | 7075 | .375 +.015 -.000 | DIA | ALUM 7075 PER AMS-QQ-A-225/9 OR ASTM B211 TEMPER T6 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|----------------------------------|-----------|--|------|
| 10001884 | - | Steel | CARBON STEEL | 3.0±.010 x 24 | W x GAUGE | ASTM A109 CR TEMPER NO. 3, 1/4 H, LONG LENGTH OR COIL | |
| 10001885 | - | Misc | NITRONIC 60 | 5/8" | SQ | NITRONIC 60 PER ASTM A276 | |
| 10001886 | - | Aluminum | 7075 | 1/2" x 3/4" | T x W | ALUM 7075 T651 PER AMS-QQ-A-225/9 OR ASTM B211 | |
| 10001887 | - | Aluminum | 6061 | .375±.005 x 6.900±.005 x 12"±1/4 | | ALUM 6061 T6 PER AMS-QQ-A-250/11 OR ASTM B209 WIDTH PARALLEL WITHIN .005 | |
| 10001888 | - | Misc | TORLON | 9/16" | DIA | TORLON 4301 PER AMS 3670/3A | |
| 10001889 | - | Aluminum | 2024 | 2 1/4" | DIA | ALUM 2024 T-351 PER AMS-QQ-A-225/6 | |
| 10001890 | - | CRES | 416 | .0475/.0465 | DIA | 416 PER ASTM A582/A582M HEAT TREATED TO RC 37-40 & 63 FINISH | |
| 10001891 | - | Aluminum | 2024 | 13/16" | DIA | ALUM 2024-T4 PER AMS-QQ-A-225/6 HEX STOCK | |
| 10001892 | - | CRES | 303 | 3/8" | DIA | 303 COND. A PER ASTM-A-582 HEX STOCK | |
| 10001893 | - | CRES | 21-6-9 | 5/16" x .035 | OD x WALL | TUBING PER AMS 5561 | |
| 10001894 | - | CRES | 410 | 7/8" | DIA | 410 SS PER ASTM-A276 TYPE 410, COND. A | |
| 10001895 | - | CRES | 17-4 PH | 2 15/16" | DIA | 17-4PH PER AMS-5643 COND. H1075 | |
| 10001896 | - | Misc | HIPERNOM | .010±.002 x 9.5 x 120" LONG | | HIPERNOM SHEET IAW Y059A005-222 .010±.002 X 9.5" X 120" | |
| 10001897 | - | Aluminum | 7075 | 1" X 2" | T x W | SAE AMS 4078 COND. T7351 | |
| 10001898 | - | CRES | 430 FR | 1 1/16" | DIA | 430 FR CHROME-IRON IAW Y117A020-102 | |
| 10001899 | - | CRES | 17-4 PH | 1/2" | DIA | 17-4PH COND. A PER AMS-5643 | |
| 10001900 | - | Aluminum | 6061 | 3/4" | DIA | ALUM 6061 T651 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001901 | - | Aluminum | 2024 | 5/8" | DIA | ALUM 2024 T351 PER AMS-QQ-A-225/6 | |
| 10001902 | - | Aluminum | 2024 | 1 5/8" | DIA | ALUM 2024 T351 PER AMS-QQ-A-225/6 | |
| 10001903 | - | Aluminum | 6061 | 1 7/16" | DIA | ALUM 6061 T651 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001904 | - | CRES | 304 | 1/2" | DIA | 304 SS ANNEALED PER AMS 5639, HEX STOCK | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|---------------------|----------------------|-----------|--|------|
| 10001905 | - | Nylon | NYLON | 1 3/8" | DIA | NYLON 616 ROD PER L-P-410 | |
| 10001906 | - | Aluminum | 2024 | 3/4" x 1.250" x 6.5" | T x W x L | ALUM 2024-T351 PER AMS-QQ-A-250/4 | |
| 10001907 | - | Aluminum | 2024 | .125 x 6.0 x 6.0 | T x W x L | ALUM 2024-T3 PER AMS-QQ-A-250/4 | |
| 10001908 | - | Steel | 1141 | 0.625 | DIA | C1141 STEEL ACME SCREW .625 DIA DOUBLE START START THRD | |
| 10001909 | - | CRES | 416 | .870 | SQ | 416 COND A PER CRES | |
| 10001910 | - | Steel | 1215 | .750" | DIA | 1215 COLD ROLLED STEEL PER ASTM-A108 | |
| 10001911 | - | Misc | OPEN | | | | |
| 10001912 | - | Nickel Iron | SINTERED SLUG | 1.50 x 2.625 | DIA x L | 25% NI - 75%IRON | |
| 10001913 | - | Steel | PRECIPITATION STEEL | 4.25-4.75 x 6" | DIA x L | PRECIPITATION HEAT TREATED STEEL IAW AMS5662 | |
| 10001914 | - | CRES | 15-5 PH | 1/4" | DIA | 15-5 PH CRES COND H1075 PER AMS5659 | |
| 10001915 | - | Steel | CARBON STEEL | 3/32 x 3/8 x 7.0 | T x W x L | CARBON STEEL PER ASTM-A109 - 30,000 P.S.I. MIN YIELD PT | |
| 10001916 | - | CRES | 430 FR | .937" | DIA | 430 CHROME IRON IAW Y117A020-101 | |
| 10001917 | - | CRES | 430 FR | .437" | DIA | 430 CHROME IRON IAW Y117A020-101 | |
| 10001918 | - | CRES | 430 FR | .687" | DIA | 430 CHROME IRON IAW Y117A020-101 | |
| 10001919 | - | CRES | 15-5 PH | 1.000" | DIA | 15-5 PH CRES COND H1075 PER AMS5659 | |
| 10001920 | - | CRES | 15-5 PH | 1-3/8" | DIA | 15-5 PH CRES COND H1075 PER AMS5659 | |
| 10001921 | - | CRES | 15-5 PH | 1/2" | DIA | 15-5 PH CRES COND H1075 PER AMS5659 | |
| 10001922 | - | CRES | 15-5 PH | 1-1/4" | DIA | 15-5 PH CRES COND H1075 PER AMS5659 | |
| 10001923 | - | CRES | 17-4 PH | .2500/.2495 | DIA | 17-4 PH CRES COND H1150 PER AMS5643 | |
| 10001924 | - | CRES | 430 FR | 1.000" | DIA | 430 FR CHROME IRON IAW Y117A020-101 | |
| 10001925 | - | CRES | 17-4 PH | 1/4" | DIA | 17-4 PF CRES COND H1025 PER AMS5643 | |
| 10001926 | - | Aluminum | 2024 | 1.250+/- .005 | OD | 2024-T3 WW-T-700/3 T1 (1.250+/- .005OD X .875+/- .010ID) | |
| 10001927 | - | CRES | 15-5 PH | 1-1/8" | DIA | 15-5 PH CRES COND H1075 PER AMS5659 | |
| 10001928 | - | Nylon | NYLON | 5/8" | DIA | 6/6 NYLON BAR PER ASTM D4066 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------------|----------------------------------|-----------|--|------|
| 10001929 | - | Nylon | NYLON | .155" x .0135 | OD x WALL | 6/6 NYLON BAR PER ASTM D4066 .155/.149 OD X .128/.122 ID | |
| 10001930 | - | CRES | 304L | 1.50" | DIA | CRES AMS-QQ-S-763 or ASTM A276/276M COND A | |
| 10001931 | - | Steel | 1141 | .5000+/- .0005 | DIA | 1141 STEEL PER ASTM-A108 | |
| 10001932 | - | Steel | 1015 | 3.250" | DIA | 1015 STEEL PER ASTM-A29 | |
| 10001933 | - | CRES | 304L | 1.750" | DIA | 304L CRES COND A PER AMS-QQ-S-763 | |
| 10001934 | - | Steel | 1015 | 1.750" | DIA | 1015 STEEL PER ASTM-A29 | |
| 10001935 | - | CRES | 301 | 2.500 x 1.500 | OD x ID | 301 CRES COND 1/2H PER AMS 5518 2.500OD X 1.500ID | |
| 10001936 | - | Plastic | PLASTIC | 1/4" | DIA | PLASTIC, POLYAMIDE (NYLON) L-P-410 | |
| 10001937 | - | Aluminum | 6061 | 2.50 x 2.00 x 1.75 | L x W x T | ALUM 6061-T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001938 | - | Aluminum | 6061 | .063 x .750 | T x W | ALUM 6061-T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001939 | - | Aluminum | 2024 | .090 x 4-1/2" | T x W | ALUM 2024-T3 PER AMS-QQ-A-250/4 (.090+/- .005 THK) | |
| 10001940 | - | Aluminum | 6061 | 3/4" x 1-1/2" | T x W | ALUM 6061-T651 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001941 | - | Misc | TEFLON | 1"+/-1/64" | DIA | TEFLON PER ASTM D1710 TYPE 2, CLASS A | |
| 10001942 | - | Aluminum | 6061 | .080+/- .005 x 4" | T x W | ALUM 6061-T6 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001943 | - | Aluminum | 6061 | 3.0" x 3.0" | T x W | ALUM 6061-T6511 PER ASTM B241 OR ASTM B221 | |
| 10001944 | - | Steel | MARAGING STEEL 300 | .625+/- .005 | DIA | 18%NI MARAGING STEEL TYPE III GRADE 300 PER MIL-S-46850 | |
| 10001945 | - | CRES | 410 | .031+/- .0015 x 1.50+/- .06 x 48 | T x W x L | 410 CRES COND A ASTM A240, 666 OR 693 (.031+/- .0015X1.50+/- .06X48LG) | |
| 10001946 | - | Aluminum | 5052 | .375 x 7.125 x 11. | T x W x L | ALUM 5052-H32 AMS-QQ-A-250/8 | |
| 10001947 | - | Aluminum | 6061 | 2.00 x 5.00 x 5.00 | T x W x L | ALUM 6061-T6510 AMS-ASTM B241 OR ASTM B221 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------------|---------------------|-------------|--|-------|
| 10001948 | - | Aluminum | 2024 | 2-5/8" | DIA | ALUM 2024-T351 AMS-QQ-A-225/6 | |
| 10001949 | - | Misc | TORLON | 5/8" | DIA | TORLON 4203 PER AMS 3670 | |
| 10001950 | - | CRES | 17-4 PH | .500 x 1.000 | T x W | 17-4PH COND H1075 PER AMS5643 | |
| 10001951 | - | Steel | GR1018 | .062 x .062 x 144 | T x W x L | GR1018 PER ASTM A108 .062"+/- .001 X .062"+/- .001 X 12 FT | |
| 10001952 | - | Aluminum | 6061 | 4.00" x 6.0" | DIA x L | ALUM 6061-T6351 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001953 | - | CRES | 416 | 3-5/8" x 6FT | DIA x L | 416 CRES PER ASTM 582 COND H | |
| 10001954 | - | Steel | STEEL, LOW ALLOY | 1" | DIA | AMS 6419 (300M) STEEL-LOW ALLOY | |
| 10001955 | - | CRES | 347 | 1/4" | DIA | 8% MIN. DELTA FERRITE | |
| 10001956 | - | Misc | ASTM A519 | 4-1/8" x 3-1/8" x 3 | OD x ID x L | ASTM A519 GR1018 SEAMLESS | |
| 10001957 | - | CRES | 302 | 4.0" x .75" | OD x WALL | 302 CRES PER QQ-S-763 COND A. | |
| 10001958 | - | CRES | 302 | 4-1/4" x .75" | DIA x L | 302 CRES PER AMS-QQ-S-763 COND A | |
| 10001959 | - | Aluminum | 6061 | 2.75" | DIA | 6061-T6 ALUM ALLOY PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001961 | - | Aluminum | 6061 | .312" x 3.50" | DIA x L | 6061-T651 ALUM ALLOY PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10001962 | A | CRES | 416 | 1.875" | HEX | 416 CRES COND. A | 75462 |
| 10001963 | - | Misc | TEFLON | .375" | DIA | TEFLON ASTM-D-1710 | |
| 10001964 | - | Misc | INCONEL 718 | 2-5/8" x 2-3 | OD x ID | INCONEL 718 AMS5589/AMS5590 | |
| 10001965 | - | Bronze | BRONZE, PHOSPHOR | .250" | DIA | BRONZE, PHOSPHOR PER ASTM B139 COMP A TEMP H | |
| 10001966 | - | Aluminum | 7075 | 5/8" x 2" | DIA x L | 7075-T651 ALUM PER AMS-QQ-A-250/12 OR ASTM B209 | |
| 10001967 | - | Aluminum | 7075 | 1/2" x 2" | DIA x L | 7075-T651 ALUM PER AMS-QQ-A-250/12 OR ASTM B209 | |
| 10001968 | - | CRES | 17-4 PH | 3.00" | DIA | 17-4 PH CRES COND. H1075 AMS 5643 | |
| 10001969 | - | CRES | 17-4 PH | 3/8" | DIA | 17-4 PH CRES COND. H1075 AMS 5643 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|--------------|-------------------------|----------------|---|-------|
| 10001970 | - | CRES | 304L | .048" x 1.50" x 48 | T x W x L | 304L COND A PER AMS-QQ-S-763 | |
| 10001971 | - | Misc | TEFLON | 1-1/2" | DIA | TEFLON ASTM D-1710 | |
| 10001972 | - | Misc | TEFLON | 5/8" | DIA | TEFLON ASTM D-1710 | |
| 10001973 | - | CRES | 17-4 PH | 5.0 x 1.900 +/- .050 | DIA x L | 17-4 PH COND H1075 PER AMS 5643 | |
| 10001974 | - | Misc | INCONEL 718 | 2-5/8" | DIA | INCONEL 718 PER AMS5662/AMS5664 | |
| 10001975 | - | Aluminum | 5052 | .040" x 3.00" x 48 | T x W x L | 5052-H32 ALUM PER AMS-QQ-A-250/8 | |
| 10001976 | - | Nickel Iron | NICKEL IRON | 2-5/8" | DIA | NICKEL IRON PER Y202A014-101 | |
| 10001978 | - | CRES | 416 | 3" x 3' | DIA x L | ASTM A582 TYPE 416 COND T (RC 26-32) | |
| 10001979 | - | Copper | BERYLLIUM | 1-3/4" | DIA | BERYLLIUM COPPER ASTM B196 ALLOY 172 COND H | |
| 10001980 | - | Plastic | PLASTIC | 2.50" x 6' | DIA x L | PLASTIC, POLYAMIDE L-P-410 (NYLON 6) | |
| 10001981 | - | Plastic | PLASTIC | 3.00" x 6' | DIA x L | PLASTIC, POLYAMIDE L-P-410 (NYLON 6) | |
| 10001982 | - | CRES | 416 | 3-3/4" x 2" | DIA x L | CRES 416 ASTM A582 COND. T | |
| 10001983 | - | Aluminum | 6061 | .050" x 1.00" x 48 | DIA x W x L | 6061-T6 ALUM ALLOY PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10001984 | - | Nylon | NYLON LP-410 | 1.000" | DIA | L-P-410 NYLON | |
| 10001985 | A | Aluminum | 6061 | 1.25 x 1.25 | T x W | AMS 4027 TEMPER T651 OR AMS 4173 TEMPER T6511 | 88719 |
| 10001986 | - | Aluminum | 2024 | 4.00" x 1" | DIA x L | 2024-T351 ALUMINUM ALLOY PER AMS-QQ-A- 225 OR ASTM B211 | |
| 10001987 | - | Aluminum | 6061 | .50 x 1.00 | T x W | 6061-T651 ALUMINUM ALLOY PER AMS-QQ-A- 250/11 OR ASTM B209 | |
| 10001988 | - | Copper | BERYLLIUM | 1.75 | DIA | BERYLLIUM COPPER ALLOY 172 COND H PER ASTM-B-196 | |
| 10001989 | - | Aluminum | 1100 | 1.125 | DIA | 1100-0 ALUMINUM ALLOY PER AMS-QQ-A-225/1 OR ASTM B211 | |
| 10001990 | A | CRES | 347 | 3" X 18" MAX | DIA x L | 347 CRES 10% FREE FERRITE CF8C ASTM-A- 351/A 351 M | 76078 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|--------------|---------------------------|-----------|--|-----------|
| 10001991 | - | CRES | 420 | 1/4" | DIA | 420 CRES COND A PER ASTM A-582 | |
| 10001992 | - | Copper | COPPER | 9/16" | DIA | COPPER ROD ALLOY 187 1/2 HARD, 99%CU, 1%PB PER ASTM B301 / B301M | |
| 10001993 | - | CRES | 420 | 5/16" | DIA | CRES CL420F COND A PER QQ-S-764 | |
| 10001994 | - | CRES | 416 | 2-7/8" | DIA | CRES 416 COND T PER ASTM A-582 | |
| 10001995 | - | CRES | 416 | 3-5/8 x 2.00 | DIA x L | CRES 416 COND T PER ASTM A-582 | |
| 10001996 | - | CRES | 4130 | 7/8" | DIA | 4130 CHROME MOLY | |
| 10001997 | - | CRES | 410 | 2.00 | DIA | CL 410 CRES COND A PER AMS-QQ-S-763 | |
| 10001998 | - | Aluminum | 6061 | .160 x 2.0 | T x W | SAE AMS 4027 | |
| 10001999 | - | Aluminum | 6061 | .160 x 1.5 x 48 | T x W x L | 6061-T6 ALUMINUM ALLOY PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10002000 | - | Steel | 4340 | 3/8" | DIA | 4340 STEEL ALLOY PER AMS 6409 | |
| 10002001 | - | CRES | 420 | 5/8 | DIA | CRES ASTM A582 TYPE 420 COND A | |
| 10002002 | - | CRES | 416 | .750 +.000 -.001 | DIA | CRES COND. H TYPE 416 | |
| 10002003 | - | CRES | 416 | 3 5/8" | DIA | CRES ASTM 582 TYPE 416 COND. T | |
| 10002004 | - | Aluminum | 6061 | 1" x 6" x 8 3/4" +/- 1/16 | T x W x L | ALUM. 6061 | |
| 10002005 | - | CRES | 416 | 5/8" | DIA | CRES ASTM A582 TYPE 416 COND T | |
| 10002006 | - | Aluminum | 6061 | SEE BOOK | T x W x L | ALUM.6061 T-6 AMS-QQ-A-250/11 OR ASTM B209 | |
| 10002007 | A | CRES | 321 | 13/16 | DIA | CL 321 PER AMS-QQ-S-763 COND. A | 71149 |
| 10002008 | A | Steel | CARBON STEEL | 2 1/4 | DIA | 1018 CARBON STEEL PER ASTM A 108 | NOC-81785 |
| 10002009 | - | Aluminum | 6061 | 3/8 x 5 1/2 x 9 +/- 1/16 | T x W x L | ALUM 6061 T-6 AMS-QQ-A-250/11 OR ASTM B209 | |
| 10002010 | B | Steel | 1018 | 2 1/4" | DIA | 1018 CARBON STEEL IAW ASTM A108 | 87279 |
| 10002011 | A | Nickel Iron | HY MU 80 | .015" x 2995-.305 | T X W | ASTM A753 ALLOY TYPE 4 (COIL) | 86434 |
| 10002012 | - | Nickel Iron | HY MU 80 | .015 x .375"-.385" | DIA | HY MU 80 STRIP BY COIL USED ON C509002311-324 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|--------------|---|-----------|--|-------|
| 10002013 | - | Nickel Iron | HY MU 80 | .015" x .395 - .405" | DIA | HY MU 80 STRIP BY COIL USED ON C509002323 | |
| 10002014 | B | Nickel Iron | HY MU 80 | .014 +/- .003 X .545/.555 | T x W | HY MU 80 STRIP BY COIL USED ON C509002322 MANUFACTURE TO BE CARPENTER | 87210 |
| 10002015 | A | Nickel Iron | HY MU 80 | .010" x .410"- .430" | STRIP | ASTM A753 ALLOY TYPE 4 | 87602 |
| 10002016 | - | Nickel Iron | HY MU 80 | .015" x .614"- .634" | STRIP | HY MU 80 STRIP BY COIL USED ON C509002326 | |
| 10002017 | - | CRES | 410 | 4.00" x 4.00" | DIA x L | CRES 410 CL COND A | |
| 10002018 | - | Aluminum | 6061 | 3/8" x 3/8" | T x W | ALUM.6061 ASTM B241 OR B221 TEMPER T6510 | |
| 10002019 | A | Aluminum | 6061 | .043/.037 X 2" +.125 / -.000 X 2" + .125 / .000 | T x W x L | ALUM 6061 AMS-QQ-A-250/11 OR ASTM B209 T6 | 87803 |
| 10002020 | - | Nickel | NICKEL ALLOY | 5/8" | DIA | NICKEL ALLOY-MARAGING 300 GRADE STEEL BARS IAW C190005002 | |
| 10002021 | - | CRES | 304L | .1385/.1390 | DIA | CL 304L CRES COND. A PER AMS-QQ-S-763 | |
| 10002022 | - | Steel | STEEL | 0.558 | DIA | ACME ROLL THREADED BARS 1141 DBL.LEAD/RIGHT HAND | |
| 10002023 | - | CRES | 304L | 2.0" | DIA | ASTM A276/A276M COND A | |
| 10002024 | - | CRES | 302 | 1.250 | DIA | 302 CRES | |
| 10002025 | - | Nickel Iron | NICKEL IRON | 2.0" | DIA | NICKEL-IRON 1202A014-101 | |
| 10002026 | - | CRES | 410 | 2.250 | DIA | CRES CL410 COND A AMS-QQ-S-763 | |
| 10002027 | - | Nylon | NYLON 6/6 | 1.750 | DIA | D-4066 NYLON 616 GROUP 01 CL1 | |
| 10002028 | - | CRES | 304L | 3.375 x 2" | D X L | ASTM A276/A276M COND A | |
| 10002029 | - | CRES | 304L | 4.75 x 2 3/4" | DIA x L | ASTM A276/A276M COND A | |
| 10002030 | - | CRES | 304L | 1.25 | DIA | ASTM A276/A276M COND A | |
| 10002031 | - | CRES | 304L | .25" | DIA | ASTM A276/A276M COND A | |
| 10002032 | - | CRES | 410 | 1.0" | DIA | ASTM A276/A276M COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-------------|--------------------------|----------|--|-------|
| 10002033 | - | Nickel Iron | NICKEL IRON | 1.375 | DIA | NICKEL-IRON Y202A014-101 | |
| 10002034 | - | CRES | 304L | 0.625 | DIA | ASTM A276/A276M COND A | |
| 10002035 | - | CRES | 304L | 0.1406 | DIA | ASTM A276/A276M COND A | |
| 10002036 | - | Nylon | NYLON 66 | .750 | DIA | GROUP 01 CLASS 1 PER ASTM D4066 | |
| 10002037 | - | CRES | 304 | .1252/.1249 | DIA | ASTM A276/A276M COND. A | |
| 10002038 | - | Nickel Iron | NICKEL IRON | 0.5 | DIA | NICKEL-IRON Y202A014-101 | |
| 10002039 | - | Nickel Iron | NICKEL IRON | 0.875 | DIA | NICKEL-IRON Y202A014-101 | |
| 10002040 | - | CRES | 304 | 0.25 | DIA | ASTM A276/A276M CONDITION A | |
| 10002041 | - | CRES | 410 | 0.5 | DIA | ASTM A276/A276M CONDITION A | |
| 10002042 | - | Misc | A-286 | 0.375 | DIA | AMS 5737 (A-286) | |
| 10002043 | - | CRES | 15-5 PH | 1.25 | DIA | CRES AMS 5659 COND H1075 (15-5 PH) | |
| 10002044 | - | CRES | 15-5 PH | 0.25 | DIA | CRES AMS 5659 COND H1075 (15-5 PH) | |
| 10002045 | - | CRES | 15-5 PH | 0.5 | DIA | CRES AMS 5659 COND H 1075 (15-5 PH) | |
| 10002046 | B | CRES | 15-5 PH | 1.875 | DIA | AMS 5659 COND. H1075 | 76347 |
| 10002047 | - | CRES | 304L | 4" x 5.5 | DIA x L. | ASTM A276/A276M COND A | |
| 10002048 | - | CRES | 17-4 PH | .3750 +/-0000 - /0005 | DIA | CRES AMS 5643 COND H1075(17-4PH) C'LESS GRIND CONF.CONTROL | |
| 10002049 | - | CRES | 17-4 PH | 1 5/8" | DIA | CRES AMS 5643 COND H 1075 | |
| 10002050 | - | Plastic | PLASTIC | 5/8" | DIA | G10 LAMINATED PLASTIC MIL-P-18177 TYPE GEE | |
| 10002051 | - | CRES | 17-4 PH | .625 +/-0.0005-000 | DIA | CRES AMS 5643 COND H1075(17-4PH)C'LESS GRND.CONTRL CON.TRACE. | |
| 10002052 | A | Aluminum | 7075 | 7.0" x 7.0" | DIA x L | ASTM B211 TEMPER T7351 | 88596 |
| 10002053 | A | Aluminum | 7075 | 6.0" x 2.0 | DIA x L | ASTM B211 TEMPER T7351 | 88596 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|---------------|--|---------|--|------|
| 10002054 | - | Plastic | PLASTIC | 5/8" | DIA | G-7 THERM.LAM.PLASTIC INSUL.MIL-I-24768 M24768/17-R-0.625 | |
| 10002055 | - | CRES | 410 | 2.25 | DIA | ASTM A276/A276M COND. A | |
| 10002056 | - | Aluminum | 6061 | 4.895 +.005 / - .000 x .049 +/-005 | DIA | ASTM B241/B241M TEMPER T6 TUBE | |
| 10002057 | - | CRES | 302 | 9/32" | DIA | 302 CRES COND A ASTM A276 9/32" ROD | |
| 10002058 | - | CRES | 17-4 PH | .8750 +0000 / - 0005 | DIA | CRES AMS5643 COND H 1075 CONF.CONTRL.TRACE.C'LESS GRIND | |
| 10002059 | - | CRES | 17-4 PH | .250" | DIA | CRES AMS 5643 COND H 1075 (17-4PH) | |
| 10002060 | - | CRES | 17-4 PH | 4.50" x 5.0" | DIA x L | CRES AMS 5643 COND H1075 | |
| 10002061 | - | Nickel | NICKEL SILVER | .468" x .1256 | DIA x L | POWERED NICKEL SILVER 64%CU,18%NL,18%ZN | |
| 10002062 | - | Nickel Iron | NICKEL IRON | 1 3/8" | DIA | NICKEL-IRON BAR MIL-N-14411 COMP 3 | |
| 10002063 | - | Nickel Iron | NICKEL IRON | 2.0" | DIA | NICKEL-IRON MIL-N-14411 COMP.3 | |
| 10002064 | - | CRES | 302 | 5/16" | DIA | ASTM A276 COND A | |
| 10002065 | - | Nickel Iron | HY MU 80 | 1/2 " | DIA | ASTM A753 ALLOY TYPE 4 | |
| 10002066 | - | Nickel Iron | HY MU 80 | 1" | DIA | ASTM A753 ALLOY TYPE 4 | |
| 10002068 | - | CRES | 17-4 PH | 4.50" x 5.0" | DIA x L | CRES AMS 5643 COND H1025 | |
| 10002069 | - | Misc | INCONEL 718 | 1 1/2" | DIA | INCONEL 718 IAW AMS 5662 OR AMS 5663, HEAT TREATMENT MUST BE PER AMS 2774, EXCEPT THAT HYDROGEN AND ARGON PLUS HYDROGEN ATMOSPHERES ARE NOT PERMITTED. | |
| 10002070 | - | CRES | 304L | 1 1/2" | DIA | ASTM A276/A276M COND A | |
| 10002071 | - | CRES | 304L | 4 3/4" x 2 1/2" | DIA x L | TYPE 304L COND A ASTMA276 (TRACE.REQ'D) | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-------------|------------------------|-------------|--|------|
| 10002072 | - | CRES | 304L | 3 7/8 x 2 1/2 | DIA x L | TYPE 304L COND A ASTM A276 (TRACE.REQ'D) | |
| 10002073 | - | CRES | 304L | 2 1/2" | DIA | TYPE 304L COND A ASTM A276 (TRACE.REQ'D) | |
| 10002074 | - | Misc | INCONEL 718 | 0.375 | DIA | INCONEL 718 IAW AMS 5663, HEAT TREATMENT MUST BE PER AMS 2774, EXCEPT THAT HYDROGEN AND ARGON PLUS HYDROGEN ATMOSPHERES ARE NOT PERMITTED. | |
| 10002075 | - | CRES | 17-4 PH | .3750/.3760 | DIA | 17-4 PH H1075 AMS 5643 C'LESS GRIND | |
| 10002076 | - | Aluminum | 6061 | 1.25" x 1.50" x 3.50 | DIA x L | 6061-T6511 ALUM ASTM B221 | |
| 10002077 | - | Aluminum | 6061 | 1.00 x 1.50 x 2.75 | T x W x L | 6061-T6511 ALUM ASTM B221 | |
| 10002078 | - | Aluminum | 6061 | 1.50 x 2.50 x 2.75 | T x W x L | 6061-T6511 ALUM ASTM B221 | |
| 10002079 | - | Nickel Iron | NICKEL IRON | .3950/.3955 | DIA | NICKEL-IRON IAW Y059A005-236 C'LESS GRIND | |
| 10002080 | - | Nickel Iron | HY MU 80 | 3/4" | DIA | HY MU 80 | |
| 10002081 | - | CRES | 303 | 5 3/8" x 1.00 +/- 1/32 | DIA x L | CRES ASTM A 582 TYPE 303 COND A | |
| 10002082 | - | CRES | 303 | 3 3/4 x 1.00 +/- 1/32 | DIA x L | CRES ASTM A 582 TYPE 303 COND H | |
| 10002083 | - | Aluminum | 6061 | 5/8 x 3 3/4 x 4 1/2 | DIA x W x L | AL6061 AMS-QQ-A-250/11 OR ASTM B209 T651 | |
| 10002084 | - | Nickel Iron | NICKEL IRON | .330-.340 | DIA | NICKEL-IRON 49- CARPENTER 49 | |
| 10002085 | - | Cobalt | COBALT 37% | 21/32" | DIA | 37 COBALT STEEL PER MMPA 0100 | |
| 10002086 | - | Nickel Iron | NICKEL IRON | 1" | DIA | ELECTRICAL IRON PER Y117A017-102 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-------------|------------------------------------|-----------|--|------|
| 10002087 | - | Misc | INCONEL 718 | 9/32" | DIA | INCONEL 718 IAW AMS 5663, HEAT TREATMENT MUST BE PER AMS 2774, EXCEPT THAT HYDROGEN AND ARGON PLUS HYDROGEN ATMOSPHERES ARE NOT PERMITTED. | |
| 10002088 | - | Brass | BRASS | 5/8" | DIA | BRASS ASTM B16 | |
| 10002089 | - | CRES | 321 | 1 5/8" | DIA | CL321 CRES AMS-QQ-S-763 COND A | |
| 10002090 | - | CRES | 410 | 1/2" x 1/8" | W x T | CL410 COND A AMS-QQ-S-763 | |
| 10002091 | - | CRES | 416 | 2 1/4" | DIA | CRES ASTM A 582 416 COND T | |
| 10002092 | - | CRES | 410 | .312 +/- .005 x.250 x 2FT.MAx | W x T x L | AMS5613 CRES 26-33 HRC | |
| 10002093 | - | CRES | 304L | .1875 - .1872 | DIA | AMS-QQ-S-763 CLASS 304L COND A C'LESS GRIND | |
| 10002094 | - | CRES | 15-5 PH | 3 5/8" x 8" + 1/8 | DIA x L | AMS-5659 COND H1075 | |
| 10002095 | - | CRES | 416 | 3" x 1 5/8 x 3/16 | L x W x T | CRES QQ-S-764 TYPE 416 COND A | |
| 10002096 | - | CRES | 416 | 3" x 1 5/8 x 1/2 | L x W x T | CRES QQ-S-764 TYPE 416 COND A | |
| 10002097 | - | CRES | 17-4 PH | 5/8 x 5/8 | DIA | 17-4 PH CRES AMS 5643 COND H1075 | |
| 10002098 | - | CRES | 410 | .012 +/- .002 x 1.410 +/- .005 | T x W | ASTM A240/A 240 M CL410 COND A | |
| 10002099 | - | Misc | TEFLON | 0.312 | DIA | ASTM A 1457 TYPE 1 WHITE | |
| 10002100 | - | CRES | 416 | 1 1/2" | DIA | ASTM A 582/A582M CRES 416 COND T | |
| 10002101 | - | Nickel Iron | NICKEL IRON | .5625 x .375 | DIA x L | FN-1 NICKEL IRON ALLOY SLUG SINTERED METAL | |
| 10002102 | - | Misc | INCONEL 718 | 9/32" | DIA | INCONEL 718 AMS 5663 | |
| 10002103 | - | Misc | INCONEL 718 | 5/32" | DIA | INCONEL 718 AMS 5662 | |
| 10002104 | - | CRES | 304L | 3.250 +/- .015 x 4.500 +/- .050 | DIA | CL 304L CRES AMS-QQ-S-763 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------|--|---------------------|---|-------|
| 10002105 | - | Steel | 1018 | 4.25 x 1/2 x 6.0 | OD x WALL x L | COLD DRAWN SEAMLESS TUBE ASTM A519 GR1018 | |
| 10002106 | - | CRES | 303 | 3 5/8" x 2.00" | DIA | CRES ASTM A 582 303 COND A | |
| 10002108 | - | CRES | 304L | 4 1/2 x .75 | DIA x L. | AMS-QQ-S-763 304L | |
| 10002109 | - | CRES | 304L | 4 1/8 x 4 1/8 x .751 | DIA x L. | 304L | |
| 10002110 | A | Misc | TITANIUM 6AL4V | 4.50" | DIA | AMS 4928 | 76719 |
| 10002111 | A | Misc | TITANIUM 6AL4V | 4 1/8" x 4 1/8" x .75 | T x W | AMS 4928 | 76719 |
| 10002112 | - | CRES | 316 | 1.5 | DIA | COND. A, PER ASTM A276/A276M | |
| 10002113 | - | CRES | 17-4 PH | 1.75 x .5 x .625 | L x W x T | CRES AMS 5643 COND H 1075 | |
| 10002114 | - | Aluminum | 6061 | 3/4" x 1" | T x W | 6061-T6 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10002115 | - | CRES | 5516 | 1.50" + 1/8 x .020 +000 -005 | W x T | AMS 5516 TYPE 302 STRIPSTOCK | |
| 10002116 | - | Aluminum | 6061 | 1/4" x 1 1/8 | T x W | ALUM 6061-T6 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10002117 | - | Aluminum | 6061 | 1" x 1 1/4" | T x W | ALUM 6061-T6 PER AMS-QQ-A-225/8 OR ASTM B211 RECTANGLE | |
| 10002118 | - | Misc | INCONEL 718 | .1249 - 1.25 | DIA | AMS 5662 CENTERLESS GRIND | |
| 10002119 | - | Aluminum | 6061 | 3 1/8 x 1 3/8 x 1/2 | L x W x T | AL6061 ASTM-B209 TEMPER T6511 | |
| 10002120 | - | Aluminum | 6061 | 4 1/8 x 1 3/8 x 1/2 | L x W x T | AL6061 ASTM-B209 TEMPER T6512 | |
| 10002121 | A | Aluminum | 6061 | 1/2" x 1/2" | SQ x T | AMS-QQ-A-200/8, TEMPER T6, T6510 OR T6511 | 87521 |
| 10002122 | A | Tungsten | TUNGSTEN | .125 +.010"-.000 x 1.000+/- .010 x 2.125+/- .030" | W x L x T | AMS-T-21014 CL 1 | 77599 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|--|-----------|---|-------|
| 10002123 | A | Tungsten | TUNGSTEN | .062+.025"- .005"x1.000+/- .010"x2.125+/- .030" | W x L x T | AMS-T-21014 CL 1 | 77599 |
| 10002124 | A | Tungsten | TUNGSTEN | 1.000 +/- .010" | DIA | AMS-T-21014 CL 1 | 77599 |
| 10002125 | A | Tungsten | TUNGSTEN | .500 +/- .010" | DIA | AMS-T-21014 CL 1 | 77599 |
| 10002126 | - | CRES | 304 | 2 1/8" | DIA | CRES ASTM A 276 TYPE 304 COND A | |
| 10002127 | A | Tungsten | TUNGSTEN | .750 +/- .010 | DIA | AMS-T-21014 CL 1 | 77599 |
| 10002128 | - | CRES | 304 | 1 3/4" | DIA | CRES ASTM A 276 TYPE 304 COND A | |
| 10002129 | A | CRES | 416 | 4 1/4" x 1 3/8" | DIA x L | CRES ASTM A 582 TYPE 416 COND T SLUGS | 69803 |
| 10002130 | - | Brass | BRASS SAE 72 | .125 +/- .0025 x .125 +/- .0025 x 2' MAX | T x W | MS 401-1 TYPE II BRASS SAE 72 HALF-HARD | |
| 10002131 | - | CRES | 4130 | .1670 + .000 - .0010 | DIA | AMS-S-6758 C'LESS GROUND | |
| 10002132 | - | Misc | INCONEL 718 | 1.25 | DIA | INCONEL 718 IAW AMS 5663 OR AMS 5662 HEAT TREATED TO AMS 5663 PER AMS 2774, EXCEPT THAT HYDROGEN AND ARGON PLUS HYDROGEN ATMOSPHERES ARE NOT PERMITTED. | |
| 10002133 | - | CRES | 416 | .1563 - .1565 | DIA | ASTM A582/A582M COND. A | |
| 10002134 | - | CRES | 17-4 PH | 1/1/8" | DIA | SAE AMS 5643 COND A HEAT TREAT PER SAE AMS-H-6875 COND. H1050 HARDNESS TO BE RC 31-39 | |
| 10002135 | - | CRES | 17-4 PH | 1 | DIA | AMS 5528 COND A (17-4) HEAT TREAT PER MIL- H-6875 COND H1100 | |
| 10002136 | - | CRES | 17-4 PH | 5/8" | DIA | AMS 5643 COND A HEAT TREAT PER MIL-H- 6875 COND H 1050 | |
| 10002137 | - | CRES | 17-4 PH | 1/4 x 3/8 x 4' MAX | T x W x L | CRES AMS 5643 COND H075 (17-4) PH STRIP | |
| 10002138 | - | CRES | 410 | .2180/.2185 | DIA | AMS-QQ-S-763 410 COND A | |
| 10002139 | - | CRES | 4130 | .2790 / .2795 | DIA | 4130 CHROME MOLY C'LESS GROUND | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|--------------|-------------------------------------|---------|---|-------|
| 10002140 | A | CRES | 4130 | 0.25 | DIA | PER SAE-AMS-S-6758 | 78287 |
| 10002141 | - | Nylon | NYLON LP-410 | 1.75 | DIA | NYLON LP-410 | |
| 10002142 | - | CRES | 416 | 4.625 x 6.000 +.125-.000 | W x L | ASTM-A582 TYE 416 COND T | |
| 10002143 | - | Aluminum | 2024 | 3.750 x .625 | W x L | ALUM 2024 AMS-QQ-A-225/6 TEMPER T-351 | |
| 10002144 | - | Misc | G10180 | 2.625 | DIA | 1018 IAW ASTM-A-108 COLD DRAWN | |
| 10002145 | - | CRES | 304L | 2 | DIA | ASTM A 276 COND. A | |
| 10002146 | - | CRES | 303 | 4 1/4 x 1.00 | W x L | ASTM A 582 TYPE 303 COND A | |
| 10002147 | - | Nickel Iron | NICKEL IRON | 1.50 x 12".00 | DIA x L | 25% NICKEL-75% IRON | |
| 10002148 | - | CRES | 416 | 1/2 x 3/4 | T x W | CRES TYPE 416 COND A | |
| 10002149 | - | CRES | 440C | .1870/.1880 | DIA | CRES QQ-S-763 CL440C COND A | |
| 10002150 | - | CRES | 416 | 0.5 | DIA | CRES TYPE 416 COND T | |
| 10002151 | - | Nickel Iron | NICKEL IRON | .015 +.002 -.004 x .400 +/- .005 | DIA x W | MATERIAL 80% NICKEL IRON IAW MIL-N-14411 COMPOSIT.1-ANNEALED | |
| 10002152 | - | Nickel Iron | NICKEL IRON | .015 + .002/-.004 x .624 ± .010 | DIA x W | MATERIAL 80% NICKEL-IRON IAW MILN14411 COMP.ANNEALED C50900236 | |
| 10002153 | - | CRES | 15-5 PH | 7/8 | DIA | CRES AMS 5659 COND. H1075 | |
| 10002154 | - | CRES | 763 | 1 1/2 | DIA | QQ-S-763 CL410 COND T | |
| 10002155 | - | CRES | 15-5 PH | 13/16 | DIA | AMS 5659 H1075 | |
| 10002156 | - | Misc | ALLOY | .0100 ± .0002 | DIA | METALLIC ALLOY WIRE IAW Y112A009-101 | |
| 10002157 | - | Misc | GOLD | .0067 ± .0002 | DIA | GOLD BRUSH CONTACT WIRE IAW B101291029 | |
| 10002158 | - | CRES | 303 | 15/8" x 2" | DIA | 303 COND A ASTM-582 | |
| 10002159 | - | CRES | 304 | 3 1/4 x 1 3/4 ± 1/8 | DIA x L | ASTM-A-276 TYPE 304 COND. A | |
| 10002160 | - | CRES | 304 | 2.125 | DIA x L | ASTM-A-276 COND A | |
| 10002161 | - | Misc | RYTHON-R4 | 2" | DIA | RYTON-R4 OR EQUVALENT IAW ASTM-D-4067 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|--------------|---|---------------|---|-------|
| 10002162 | - | Misc | RYTHON-R4 | 1" | DIA | RYTON 40% GLASS PPS-BLACK PER ASTM-D4067 | |
| 10002163 | - | Nickel Iron | NICKEL IRON | 0.5 | DIA | Y202H014-1 COMP. A | |
| 10002164 | - | Misc | INCONEL 718 | 1.5 | DIA | INCONEL 718 IAW AMS 5662 (TRACE REQUIRED) | |
| 10002165 | A | CRES | 347 | 1/4" x 1/2" | T X W | 347 SS COND. A AMS-QQ-S-763 | 74111 |
| 10002166 | - | Plastic | PLASTIC | 1.25 | DIA | LAMINATED PLASTIC ROD IAW MIL-I-24768/14 | |
| 10002167 | - | Nickel Iron | NICKEL IRON | 1.125 | DIA | NICKEL IRON Y202A014-1 COMP. 4 | |
| 10002168 | - | Aluminum | 6061 | 1.125 | DIA | AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 | |
| 10002169 | - | CRES | 15-5 PH | 2.5 | DIA | H1075 AMS 5659 | |
| 10002170 | - | CRES | 440C | 3/8 x 3/8 | T x L | CRES CL440C COND A QQ-S-763 | |
| 10002171 | - | CRES | 302 | 1.000 ± .010 x 1.190 ± .010 x .032 ± .002 | L x W x T | QQ-S-766 CLASS 302 COND A | |
| 10002172 | - | CRES | 416 | 5 1/2 x 5.0 +1/8 - 0 | DIA X L | ASTMA582 416 COND A | |
| 10002173 | A | Misc | LP-380C | 7/8 x .062 | O.D.X WALL | METHACRYLATE IAW FED. SPEC. TY 1 CL 1 | 71180 |
| 10002174 | - | Nylon | NYLON | 2 | DIA | 30% GLASS FIBER FILLED 6/6 NYLON OR EQUI.IAW ASTMD4066 | |
| 10002175 | C | Tungsten | TUNGSTEN | .750+.100/-.000 X .250 +.100/-.000 X 12" | W x T X L | AMS-T-21014 CL 1 | 77599 |
| 10002176 | - | Misc | ZYTEL ST 801 | 1.25 | DIA | ASTM D 4066 PA 0162 | |
| 10002177 | - | CRES | 416 | 2.500+000 -.010 x 1.312 +000 -.010 x .060±.001 | L x W x T | ASTM A 582 TYPE 416 COND H | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------|-------------------------------|-----------|--|-------|
| 10002178 | - | CRES | 416 | 2.625 x 1.500 x 1.000 | L x W x T | ASTM A 582 COND H | |
| 10002179 | - | CRES | 410 | 2 1/8" | DIA | 410 COND T IAW AMS-QQ-S-763 2 1/8 ROUND BAR | |
| 10002180 | - | CRES | 416 | 1.25" x 2.000" x 2.125" | T x W x L | CRES 416 COND. H SLUG | |
| 10002181 | - | CRES | 416 | .500" x 1.000" x 3.000" | T x W x L | CRES TYPE 416 COND H SLUG | |
| 10002182 | - | Aluminum | 6061 | 2" x 4" x 4' | T x W x L | ALUMINUM 6061 AMS-QQ-A-250/11 OR ASTM B209 TEMP T651 | |
| 10002183 | - | Cobalt | COBALT 35% | 5/8" | DIA | 35% COBALT STEEL SIMONDS 3500 OR EQUIL PER MMPA SPEC 100-87 RC 35 MIN. | |
| 10002184 | - | Cobalt | COBALT 35% | 1" | DIA | 35% COBALT STEEL SIMONDS 3500 OR EQUIL PER MMPA SPEC 100-87 RC 35 MIN. | |
| 10002185 | - | Cobalt | COBALT 35% | 25/32" | DIA | 35% COBALT STEEL SIMONDS 3500 OR EQUIL PER MMPA SPEC 100-87 RC 35 MIN. | |
| 10002186 | - | Cobalt | COBALT 35% | 3/4" | DIA | 35% COBALT STEEL SIMONDS 3500 OR EQUIL PER MMPA SPEC 100-87 RC 35 MIN. | |
| 10002187 | B | Cobalt | COBALT 17% | 1" | DIA | SIMONDS #81 | 83908 |
| 10002188 | B | Cobalt | COBALT 17% | 5/8" | DIA | SIMONDS #81 | 83908 |
| 10002189 | B | Cobalt | COBALT 17% | 3/4" | BAR | SIMONDS #81 | 83908 |
| 10002190 | B | Cobalt | COBALT 17% | 1 1/8" | DIA | SIMONDS #81 | 83908 |
| 10002191 | B | Cobalt | COBALT 17% | 1 3/4" | DIA | SIMONDS #81 | 83908 |
| 10002192 | - | Aluminum | 6061 | 7.00 +/- .030 x 1.10 +/- .030 | W x L | AL 6061 T6 AMS-QQ-A-225/8 OR ASTM B211 SLUG | |
| 10002193 | - | CRES | 416 | 1/8" x 1/2" x 1 1/2" | T x W x L | CRES TYPE 416 COND T | |
| 10002194 | - | Aluminum | 2024 | 2 1/2" | DIA | AL 2024 T851 AMS-QQ-A-225/6 BARSTOCK | |
| 10002195 | - | Aluminum | 2024 | 1" | DIA | AL 2024 T851 AMS-QQ-A-225/6 BARSTOCK | |
| 10002196 | - | Aluminum | 2024 | 1/2" x 1 3/4" x 2 3/8" | T x W x L | AL 2024 T851 AMS-QQ-A-225/6 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------|---|-----------|--|-------|
| 10002197 | A | Tungston | TUNGSTEN | 9/16" x 11/16" 12" | T x W x L | AMS-T-21014 CL 1 | 77599 |
| 10002198 | - | Misc | DELETED | | | CRES | |
| 10002199 | - | CRES | 416 | 1"x1"x 2.25" | T x W x L | CRES TYPE 416 COND H (31-38) | |
| 10002200 | - | CRES | 17-4 PH | 3/32" x .9+/-0.010 x 6.6 +/-0.010 | T x W x L | 17-4 PH H1050 PER AMS-5604 | |
| 10002201 | - | CRES | 17-4 PH | 1/8" x .650+/- .010 x .9 +/-0.010 | T x W x L | 17-4 PH H1050 PER AMS-5604 | |
| 10002202 | - | Misc | DELETED | | | OBSOLETE SEE 10002315 | |
| 10002203 | - | CRES | 17-4 PH | 2 3/4" | DIA | 17-4 PH CRES BAR COND A HEAT TREAT TO H1025 COND IAW MIL H 6875 | |
| 10002204 | - | CRES | 17-4 PH | 1" | DIA | 17-4 PH CRES BAR COND A HEAT TREAT TO H1025 COND IAW MIL H 6875 | |
| 10002205 | - | Nylon | NYLON 6/6 | 2.625" | DIA | PLASTIC, POLYAMID (NYLON G) LP-410 ROUND BAR | |
| 10002206 | - | Steel | 1018 | 2 3/8" | DIA | 1018 STEEL IAW ASTM-A108 G10180 COLD DRAWN | |
| 10002207 | - | CRES | 17-4 PH | 2.0 x 1.250 x .250 | L x W x T | CRES AMS 5643 COND H 1075 (17-4 PH) | |
| 10002208 | - | CRES | 303 | .032 +.000/-0.001 x 3' +/- 1/2' | DIA x L | ASTM A582 303 COND A | |
| 10002209 | A | Misc | GLASS EPOXY | 1.875" | DIA | GPI-10 GLASS EPOXY PER ASTM D5948-96 OR GLASS EPOXY IAW MIL-1-24768/3 | 78423 |
| 10002210 | - | Steel | 8740 | 3/4" | DIA | 8740 STEEL AMS 6322 COLD DRAWN ANNEALED | |
| 10002211 | - | Aluminum | 6061 | 4.0 x 2.250 x .750 | L x W x T | 6061 T-651 AMS QQA-250/11 OR ASTM B209 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|-------------|--|----------------------|---|------|
| 10002212 | - | Nickel Iron | NICKEL IRON | 1 3/8" | DIA | 49 FM NICKEL IRON IAW Y202A014-201, 202 OR 205 DEC 1.375" | |
| 10002213 | - | CRES | 321 | 1 5/8" | DIA | CRES AMS-QQ-S-763 CL 321 COND A | |
| 10002214 | - | CRES | 321 | 1" | DIA | AMS-QQ-S-763 COND. A | |
| 10002215 | - | CRES | 410 | 3/4" | DIA | CL410 COND. A AMS-QQ-S-763 | |
| 10002216 | - | CRES | 321 | 7/8" | DIA | CL321 COND A AMS-QQ-S-763 | |
| 10002217 | - | Nickel Iron | NICKEL IRON | 1 3/8" | DIA | NICKEL IRON IAW Y202A014-201 BARSTOCK | |
| 10002218 | - | Nickel Iron | NICKEL IRON | .090/.091 | DIA | CARPENTER 49 IAW MIL-N-14411 COMP 3 | |
| 10002219 | - | CRES | 321 | .097/.098 | DIA | CRES AMS-QQ-S-763 CL 321 COND A | |
| 10002220 | - | CRES | 321 | .188 NOM x .035 NOM x 11.890 +.040/-0.0000 | TUBING | CRES TUBING TYPE 321 IAW MIL-T-8808 TY 1 SEAMLESS COND. A (-.005) | |
| 10002221 | - | CRES | 321 | .500 NOM x .035 NOM x 11.460 +.040/-0.0000 | TUBING | CRES TUBING TYPE 321 IAW MIL-T-8808 TY 1 SEAMLESS COND. A (-.005) | |
| 10002222 | - | CRES | 304 | 3 1/4" x 1 9/16" (+1/8 / -0) x L | SLUG | CRES ASTM A 276 TYPE 304 COND. A | |
| 10002223 | - | Aluminum | 6061 | 3 1/4" x 3 1/4" x 9/16" (+1/8 / -0) | SLUG | AL 6610 T-651 ASTM B241 OR ASTM B221 | |
| 10002224 | - | Steel | STEEL | 4 7/16 x 3/16 x 3 (+1/16 / -0) | DIA x WALL x L | SCHEDULE 80 SEAMLESS PIPE IAW ASTM-A53 | |
| 10002225 | - | Steel | 8740 | 1.385 +/- .015 | DIA | COLD DRAWN ANNEALED 8740 STEEL - AMS 6322 | |
| 10002226 | - | CRES | 304 | 5/16" | DIA | AMS-QQ-S-763 COND A 304 CRES | |
| 10002227 | - | CRES | 304 | 1/4" x .012 | OD x WALL | 304 SS COND. A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|---|-----------|--|-------|
| 10002228 | - | CRES | 304L | 3/8" | DIA | CRES AMS-QQ-S-763 or ASTM A276/276M COND A | |
| 10002229 | - | Nickel Iron | NICKEL IRON | .750+/- .010 x .010 +/- .003 | W x T | 80% NICKEL IRON IAW MIL-N-14411 COMPOSITION 1 | |
| 10002230 | - | Nickel Iron | NICKEL IRON | .824+/- .010 x .010+/- .003 | W x T | 80% NICKEL IRON IAW MIL-N-14411 COMPOSITION 1 | |
| 10002231 | - | Misc | TITANIUM 6AL4V | 0.5 | DIA | SAE AMS 4928, ANNEALED | |
| 10002232 | - | CRES | 15-5 PH | 2.25 | DIA | 15-5 PH CRES IAW AMS 5659 COND H1025 | |
| 10002233 | - | CRES | 15-5 PH | 3/16" | DIA | 15-5 PH CRES IAW AMS 5659 COND H1025 | |
| 10002234 | - | CRES | 21-6-9 | .3125/.3155 x .2425+/- .003 | OD x ID | CRES TUBING TYPE 21-6-9 IAW AMS 5561 .3125/.3155 OD x .2425+/- .003 ID | |
| 10002235 | - | Misc | INCONEL 718 | .507-.509 | ID x OD | INCONEL 718 IAW AMS 5663 | |
| 10002236 | - | Misc | NITRALLOY | 0.625 | DIA | NITRALLOY 135M IAW AMS 6470 COND. C BARSTOCK | |
| 10002237 | - | CRES | 21-6-9 | 1.0 x .035 | OD x WALL | CRES TUBING TYPE 21-6-9 IAW AMS 5561 | |
| 10002238 | - | CRES | 21-6-9 | .750 x .035 | OD x WALL | CRES TUBING TYPE 21-6-9 IAW AMS 5561 | |
| 10002239 | - | CRES | 321 | .375 x .028 | OD x WALL | CRES TUBING TYPE 321 IAW AMS 5557 | |
| 10002240 | - | CRES | 321 | .187+/- .001 | DIA | CRES AMS-QQ-S-763 CL 321 COND. A - C'LESS GROUND | |
| 10002241 | - | Aluminum | 6061 | .080+/- .005 x 1.500(+.050/- .000) x 3.500 (+.050/- .000) | SLUG | AL 6061-T6 AMS-QQ-A-250/11 OR ASTM B209 OR AMS-QQ-A-225/8 OR ASTM B211 | |
| 10002242 | A | CRES | 430 FR | 1.00 +/- .100 | DIA | CARPENTER 430FR SOLENOID QUALITY REF Y117A020-101 & ASTM A838 ALLOY 2 | 87814 |
| 10002243 | - | Steel | 1018 | 2.625 | DIA | 1018 IAW ASTM-A-108 G10180 COLD DRAWN | |
| 10002244 | - | Steel | 1018 | 2.125 | DIA | 1018 IAW ASTM-A-108 G10180 COLD DRAWN | |
| 10002245 | - | CRES | 303 | 7.00" x 1.000 | SLUG | CRES ASTM A582 TYPE 303 COND A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|--------------------|--|---------------------|---|-------|
| 10002246 | - | Aluminum | 6061 | .062 x .375 x 1.800 MIN | T x W x L | AL 6061 AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6 | |
| 10002247 | - | Nickel Iron | NICKEL IRON | .66+/- .005 x .010+/- .003 x VARIOUS | W x T x L | 80% NIFE IAW MIL-N-14411 COMP 1 STRIP | |
| 10002248 | - | CRES | 304 | .120+/- .001 x .010+/- .010 x 6.5 | OD x WALL x L | CRES TUBING TYPE 304 IAW ASTM A269 | |
| 10002249 | - | CRES | 304 | .089+/- .001 | DIA | CRES CL 304 COND A IAW SAE-AMS-QQ-S-763 C-LESS GROUND | |
| 10002250 | - | Steel | 1018 | 2 3/4" | DIA | ASTM A 108 GRADE 1018 | |
| 10002251 | - | Nickel Iron | NICKEL IRON | 0.625 | DIA | NICKEL-IRON IAW Y202A014-101 | |
| 10002252 | - | Nickel Iron | HY MU 80 | 3.000 x 4' MAX | DIA x L | C190000118 TYPE 1 HYMU-80 | |
| 10002253 | - | Nylon | NYLON 6/6 | 3.000" | DIA | 30% GLASS FIBER FILLED 6/6 NYLON OR EQUIV. IAW ASTM D-4066 | |
| 10002254 | - | CRES | 304L | 3.000" x 2.80+/- .05 | SLUG | CRES ASTM A278 TYPE 304L COND A | |
| 10002255 | - | Steel | LOW ALLOY STEEL | 3.500" | DIA | STEEL ALLOY IAW AMS 6378 E150 | |
| 10002256 | - | Misc | INCONEL 718 | 3.250 x 2.80+/- .05 | SLUG | NICKEL ALLOY PER AMS 55662 (INCONEL 718) | |
| 10002257 | - | CRES | 304L | 3.000 x 2.125+/- .05 | SLUG | CRES ASTM A276 TYPE 304L COND A | |
| 10002258 | B | Steel | LOW ALLOY STEEL | 2.125" | DIA | SAE AMS6378 (4142H MODIFIED) | 88953 |
| 10002259 | - | CRES | 440C | 1.0625" | DIA | CRES QQ-S-763 TYPE 440C COND A | |
| 10002260 | - | Steel | LOW ALLOY STEEL | 1.750" | DIA | SAE AMS 6378 (4142H MODIFIED) | |
| 10002261 | - | Steel | LOW ALLOY STEEL | .750" | DIA | SAE AMS 6378 (4142H MODIFIED) | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-----------------|---------------------------------------|---------------|---|-------|
| 10002262 | - | Aluminum | 6061 | 4.625 x 4.000 | SLUG | ALUM. 6061-T6 PER AMS-QQ-A-225/8 OR ASTM B211 | |
| 10002263 | - | Steel | 1018 | 8.000 x 5.000 | SLUG | 1018 STEEL ASTM A-29 | |
| 10002264 | - | Aluminum | 6061 | 8.25 x 1/2 x 7.00 | OD x WALL x T | SEAMLESS TUBE ALUMINUM T6 IAW ASTM B221 | |
| 10002265 | - | Steel | LOW ALLOY STEEL | 1.375" | DIA | SAE AMS 6378 (4142H MODIFIED) | |
| 10002266 | - | Aluminum | 6063 | 7 1/8 x 2.000 | SLUG | AL 6063 T-6 ASTM B241 OR ASTM B221 | |
| 10002267 | - | Steel | 4130 | 2 7/8" | DIA | 4130 ALLOY STEEL MIL-S-6758 COND. D | |
| 10002268 | - | Aluminum | 6061 | 3/16 x 12.00" x 12.00" | SQ | 6061 T-651 AL ALLOY | |
| 10002269 | - | Steel | LOW ALLOY STEEL | 2.875" | DIA | SAE AMS 6378 (4142H MODIFIED) | |
| 10002270 | - | Steel | LOW ALLOY STEEL | 3.125" | DIA | SAE AMS 6378 (4142H MODIFIED) | |
| 10002271 | - | Misc | PHOSPHOR BRONZE | .750" | DIA | PHOSPHOR BRONZE BAR ASTM B139 COMP. A TEMP H | |
| 10002272 | - | Aluminum | 2024 | 3.625 x 6.0 | DIA x L | AMS-QQ-A-250/4 TEMP T3 ALUM | |
| 10002273 | - | Misc | GLASS BASE LAM | 3.875 x 3.375 | OD x ID | GLASS BASE LAM MIL-P-79 TYPE GMG-EM88 CL 5 TUBING | |
| 10002274 | - | Steel | LOW ALLOY STEEL | 1.750 | DIA | SAE AMS 6378 (4142H MODIFIED) | |
| 10002275 | - | CRES | 17-4 PH | 3/32" x .9000+/- .010 x 6.660+/- .010 | T x W x L | 17-4 PH H1050 PER AMS-5604 | |
| 10002276 | - | Aluminum | 6061 | 1/2 x 1.0 x 3.00+/- .050 | T x W x L | ALUM 6061-7651 PER AMS-QQ-A-250/11 OR ASTM B209 | |
| 10002277 | A | Misc | DELRIN | 5/16" | DIA | DELRIN 150 PER ASTM-D-4181 POM 111 | 78544 |
| 10002278 | - | Misc | TEFLON | 3/8" | DIA | TEFLON ASTM-D-170 TYPE 1 GRADE 1 CLASS A | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|----------------|--------------------------------------|---------------------|--|-------|
| 10002279 | - | CRES | 303 | 1.000 x 2.500 x 19.000 | T x W x L | CRES 303 ASTM-A-582, HRA | |
| 10002280 | - | Aluminum | 6061 | 10.0 x 1 1/2 x 12" | OD x WALL x L | SEAMLESS TUBE ALUMINUM T6 IAW ASTM B221 | |
| 10002281 | - | Aluminum | 6061 | 3 5/8 | DIA | 6061 ALUM ASTM B221 TEMP. T6 3 5/8 DIA BARSTOCK | |
| 10002282 | B | Misc | TITANIUM 6AL4V | 3.25 | DIA | AMS 4928 COND.A | 76719 |
| 10002283 | - | Misc | NITRONIC 60 | 0.125 | DIA | ASTM-A176/A276M GRADE UNS S21800 | |
| 10002284 | - | CRES | 13--8MO | 3.00 | DIA | AMS-5629 COND. H1000 | |
| 10002285 | - | Nickel Iron | NICKEL IRON | 1.0 | DIA | NICKEL IRON PER Y202A014-202 BARSTOCK | |
| 10002286 | - | CRES | 204 | .120+/- .001 x .010+/- .001 x 6.5 | ODxWAL LxL | CRES TUBING TYPE 204 IAW ASTM A 269 | |
| 10002287 | - | Aluminum | 6061 | 5.0' x 1 1/2" x 12" | DIAxWA LLxL | SEAMLESS ALUM TUBING PER ASTM B221 6061 T6 5.0' ID X 1 1/2" WALL X 12" LONG | |
| 10002288 | - | Aluminum | 6061 | .312 x 7.0 x 11.0 | TxWxL | AL 6061 T6 IAW AMS-QQ-A-250/11 OR ASTM B209 .312x7.0x11.0 PLATE | |
| 10002289 | A | CRES | 416 | 13/16 | DIA | SAE AMS56410 TYPE 2 (TYPE 416 CORROSION AND HEAT-RESISTANT STEEL, FREE MACHINING.) | 87100 |
| 10002290 | - | Aluminum | 5052 | .250+/- .010 x .032+/- .005 | W x T | ALUM 5052 H-34 - AMS-QQ-A-250/8 STRIP | |
| 10002291 | - | Misc | INCONEL 718 | 3.500 x 2.80 +/- .05 | SLUG | NICKEL ALLOY PER AMS 5662 (INCONEL 718) | |
| 10002292 | - | CRES | 304L | 3.500 x 2.125 | DIAxL | CRES 304L ASTM A 276 COND A DIA 3.500x2.125" L SLUG | |
| 10002293 | - | CRES | 304L | 3.500 x 2.8 | DIAxL | CRES 304L ASTM A 276 COND A DIA 3.500x2.8" L SLUG | |
| 10002294 | - | Misc | DELETED | | | OBSOLETE | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|--|---------|--|-------|
| 10002295 | - | Aluminum | 6061 | .250 x 11.000 x 15.750 | | ALUM 6061-T6 X .250 X 11.000 X 15.750 | |
| 10002296 | - | Aluminum | 6061 | 1.00 x 2.500 x 9.700 | | ALUM 6061-T6 X 1.00 X 2.50 X 9.700 | |
| 10002297 | - | Aluminum | 5052 | .090 x 6.8000 x 7.100 | | ALUM 5052-H32 .090 x 6.800 x 7.100 | |
| 10002298 | - | Aluminum | 6061 | 1 1/8 | SQ | ALUM 6061-T6 1-1/8" SQUARE STOCK | |
| 10002299 | - | Aluminum | 6061 | .500 x 2.500 x 11.750 | | ALUM 6061-T6X.500X2.500X11.750 | |
| 10002300 | - | Misc | DELETED | | | OBSOLETE | |
| 10002301 | - | Misc | DELETED | | | OBSOLETE | |
| 10002302 | - | Aluminum | 6061 | .187 x 12.000 x 15.800 | | ALUM 6061-T6X.187X12.00X15.800 | |
| 10002303 | - | CRES | 17-4 PH | 1/2 x 1/2 | SQ | 17-4 PH COND H1075 AMS 5643 1/2 x 1/2 SQUARE | |
| 10002304 | - | CRES | 304 | .256/.257 | DIA | CRES IAW AMS-QQ-S-763 CLASS 304 COND A GROUND BAR DIA .256/.257 | |
| 10002305 | - | CRES | 15-5 PH | 3/8 | BAR | CRES 15-5 PH CRES COND. H 1075 AMS 5659 3/8 BARSTOCK | |
| 10002306 | A | CRES | 321 | .156 + .001 x .118 +.005/-0.000 | OD x ID | SEAMLESS TUBING CRES 321 IAW AMS-5557 .156+ .001 OD x .118 +.005/-0.000 ID | 72266 |
| 10002307 | A | CRES | 321 | .882 +.000/-0.001 x .810 + .005 | OD x ID | SEAMLESS TUBING CRES 321 IAW AMS-5557 .882+ .000/-0.001 OD x .810 + .005 ID | 72266 |
| 10002308 | A | CRES | 321 | 1.060 +.000/-0.002 x .985 +.005 / -0.000 | OD x ID | SEAMLESS TUBING CRES 321 IAW AMS-5557 1.060 +.000/-0.002 OD x .985 +.005/-0.000 ID | 72266 |
| 10002309 | - | Steel | STEEL | 13/32 | DIA | 6150 ALY STEEL BAR COLD DRAWN ANNEALED PER SAE AMS-6448 13/32 DIA | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------|----------------|---------------------|---------|---|-------|
| 10002310 | - | CRES | 416 | 0.25 | DIA | CARPENTER STAINLESS TYPE 416 BQ (NO5 BQ) .250 DIA | |
| 10002311 | - | CRES | 416 | 3 3/8 x 3.015+ 1/16 | DIA x L | CRES TYPE 416 COND T ASTM A 582 DIA 3 3/8 x 3.015+ 1/16 L SLUG | |
| 10002312 | - | Steel | 1010 | .015 x 1 | T x W | C1010 STEEL STRIP STOCK .015 THICK x 1 WIDE | |
| 10002313 | - | Misc | DELTRIN | 3/8 | DIA | DELTRIN 150 ASTM-D-4181 POM 211 OR POM 111 3/8 DIA | |
| 10002314 | - | Iron | NICKEL IRON 49 | .250+.001 | DIA | CARPENTER 49 IAW MIL-N-14411 COMP 3 .250+.001 BARSTOCK | |
| 10002315 | - | Nylon | NYLON | 3/8 | DIA | 30% GLASS FILLED NYLON IAW ASTM D 4066 3/8" DIA ROD | |
| 10002316 | A | CRES | 316L | 3.5x2.8 | DIA x L | COND. A CRES ASTM A276, CHEMICAL COMPOSITION OF MATERIAL SHALL MEET THE FOLLOWING EQUATION AND EXCEED THE MINIMUM RATION VALUE OF 1.7% (Cr) eq=Cr + Mo + 0.7 Nb +3 Ti (NI) eq= Ni + 35 C + 20 N | 86771 |
| 10002317 | A | CRES | 316L | 3.625x2.125 | DIA x L | COND. A CRES ASTM A276, CHEMICAL COMPOSITION OF MATERIAL SHALL MEET THE FOLLOWING EQUATION AND EXCEED THE MINIMUM RATION VALUE OF 1.7% (Cr) eq=Cr + Mo + 0.7 Nb +3 Ti (NI) eq= Ni + 35 C + 20 N | 86771 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------|------------------------|---------------|---|-------|
| 10002318 | A | CRES | 316L | 2.00" | DIA | COND. A CRES ASTM A276, CHEMICAL COMPOSITION OF MATERIAL SHALL MEET THE FOLLOWING EQUATION AND EXCEED THE MINIMUM RATION VALUE OF 1.7% (Cr) eq=Cr + Mo + 0.7 Nb +3 Ti (NI) eq= Ni + 35 C + 20 N | 86771 |
| 10002319 | - | CRES | 316L | 2.50" | DIA | COND. A CRES ASTM A276, CHEMICAL COMPOSITION OF MATERIAL SHALL MEET THE FOLLOWING EQUATION AND EXCEED THE MINIMUM RATION VALUE OF 1.7% (Cr) EG=Cr + Mo + 0.7 Nb +3 Ti (NI) EG= Ni + 35 C / 20 N | |
| 10002320 | - | CRES | 316L | 1.25" | DIA | COND. A CRES ASTM A276/A276M, CHEMICAL COMPOSITION OF MATERIAL SHALL MEET THE FOLLOWING EQUATION AND EXCEED THE MINIMUM RATION VALUE OF 1.7% RATIO=%Cr + %Mo %Ni + %C + %N | |
| 10002321 | - | Aluminum | 6061 | 11/16"x3 1/2" x 6 1/4" | | ALUM 6061 AMS-QQ-A-250/11 OR ASTM B209 11/16"x3 1/2" x 6 1/4" SLUG | |
| 10002322 | - | Aluminum | 6061 | 2"x3"x6 1/4" | | ALUM 6061 AMS-QQ-A-250/11 OR ASTM B209 2" x 3" x 6 1/4" SLUG | |
| 10002323 | - | Aluminum | 6061 | 3/16 x 2 3/8 | T x W | ALUM 6061 AMS-QQ-A-250/11 OR ASTM B209 TEMPER T6 3/16 x 2 3/8 (THK x W) STRIP | |
| 10002324 | - | Cobalt | COBALT 37% | 1.125" | DIA | COBALT STEEL 3500 (37%) PER MMPA-0100-90 DIA 1.125" BARSTOCK | |
| 10002325 | - | Aluminum | 6061 | 5.0" x 1 1/2" x 12" | OD x WALL x L | SEAMLESS ALUM TUBING PER ASTM B221 6061 T6 5.0' OD X 1 1/2" WALL X 12" LONG | |
| 10002326 | A | CRES | 410 | .031+ .002 x .500 | T x W | CRES CL 410 STRIP STOCK ASTM-A240 .031+ .002 THICK X .500 WIDE | 72266 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------------|-------------|----------------------------|-----------|--|-------|
| 10002327 | - | Misc | TEFLON | .015+.003 x .500 x 24" | T x W x L | TEFLON STRIP IAW ASTM-D3308 TYPE 1, GRADE 1 | |
| 10002328 | A | Nickel Iron | HY MU 80 | .010+.003 x .380 + .005 | T x W | HY MU 80 STRIP COIL IAW MIL-N-14411 COMPOSITION/.010+ .003 THICK x .380+ .005 WIDE | 72266 |
| 10002329 | - | CRES | 13-8 MO | 7/16 | DIA | PH13-8MO AMS 5629 COND H 1150 DIA 7/16 | |
| 10002330 | B | Misc | VESPEL | 1 1/4 | DIA | VESPEL SP-21 AMS 3644 CLASS 2 | 72266 |
| 10002331 | A | Iron | IRON | .089/.090 | DIA | CARPENTER 49 IAW MIL-N-14411 CAPABLE OF COMP 3 DIA .089/.090 GROUND BAR | 72266 |
| 10002332 | B | CRES | 304 | .096±.001 | DIA | CRES CL 304, COND A AIW AMS-QQ-S-763 DIA .096+.001 GROUND BAR | 72266 |
| 10002333 | A | CRES | 321 | 1.250 | DIA | AMS-QQ-S-763 COND. A | 72266 |
| 10002334 | - | Aluminum | 6061 | 1.50 x 5.00 | T x W | AL 6061 T6 IAW AMS-QQ-A-250/11 OR ASTM B209 1.50 THK x 5.00 WIDE FLAT STOCK | |
| 10002335 | - | CRES | 17-4 PH | 5/8 | DIA | 5/8 DIA 17-4 PH-HEAT TREAT AT 1100DEG F +/- 10 DEG F FOR 4 HOURS IN AN INERT ATMOSPHERE AND COOL HARDNESS TO BE RC32-38 CONFIGURATION CONTROL | |
| 10002336 | - | Aluminum | 7075 | 1/8 | DIA | AL 7075 T-6 IAW AMS-QQ-A 225/9 CL 1A 1/8 DIA | |
| 10002337 | A | CRES | 321 | 1 | DIA | AMS-QQ-S-763 COND. A | 72266 |
| 10002338 | A | CRES | 321 | .1070±.005 | DIA | 321 SS .1070+.005 GROUND AMS-QQ-S-763 COND A | 72266 |
| 10002339 | A | CRES | 321 | 1 1/8 | DIA | 321 SS COND A ASM-QQ-S-763 COND A 1 1/8 DIA | 72266 |
| 10002340 | A | CRES | 321 | 3/8 | DIA | 321 SS COND A AMS-QQ-S-763 3/8 DIA | 72266 |
| 10002341 | A | CRES | 321 | .750 | DIA | AMS-QQ-S-763 COND. A | 72266 |
| 10002342 | C | Misc | NITRONIC 60 | .125 | DIA | NITRONICS 60 ASTM-A-276 UNS S21800 CENTERLESS GRIND | 90307 |
| 10002343 | A | CRES | 304 | .2460/.2455 | DIA | 304 COND A AMS-QQ-S-763 .2460/.2455 | 72266 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------|------------------------------|--------------|--|-------|
| 10002344 | A | CRES | 304 | .096±.001 | DIA | 304 SS COND A QQS763 GROUND BAR .096+.001 | 72266 |
| 10002345 | A | Aluminum | 6061 | 1 3/8 | DIA | ALUM 6061 QQA 225/8 6061 T651 1 3/8" DIA | 72266 |
| 10002346 | - | Aluminum | 6061 | 6.750 x 5.000 x .080+.005 | L x W x T | AMS-QQ-A-250/11 OR ASTM B209 AL 6061 T-6 6.750 x 5.000 x .080 +.005 SLUG (LG x WD x THK) | |
| 10002347 | - | Aluminum | 6061 | 4" x 3 1/2" x 5/8" | L x W x H | ALUM 6061-T6 AMS-QQ-A-250/11 OR ASTM B209 4" x 3 1/2" x 5/8" ALLOY | |
| 10002348 | A | Aluminum | 6061 | 4 1/2" | DIA | ALUM 6061-T6 ASTM-B-221 4 1/2" DIA ALLOY | 69898 |
| 10002349 | - | Aluminum | 2011 | 3/16" | HEX | ALUM 2011-T3 AMS-QQ-A-225/3 3/16" HEX | |
| 10002350 | - | Aluminum | 2011 | 1/4" | HEX | ALUM 2011-T3 AMS-QQ-A-225/3 1/4" HEX | |
| 10002351 | - | CRES | 4130 | .436-.437 | DIA | 4130 ALLOY STEEL NORMALIZED PER MIL-S- 6758 COND. D4 DIA .436-.437 GROUND BAR | |
| 10002352 | - | CRES | 303 | 2.500" | DIA | CRES ASTM A582 COND A DIA 2.500 BARSTOCK TYPE 303 | |
| 10002353 | - | CRES | 304L | 4.00" x 12"±.125 | DIA x L | CRES ASTM A 276 COND. A - 304L DIA 4.00" x 12"±.125 | |
| 10002354 | - | Aluminum | 6061 | 1/4" x 5/12 x 9 1/4 | L x W x H | AL 6061 AMS-QQ-A-250/11 OR ASTM B209 TEMPER T651 1/4" x 5 1/2 x 9 1/4 | |
| 10002355 | - | Plastic | PHENOLIC | 12 x 36 x .625 | L x W x T | PHENOLIC IAW MIL-24768 G11, FRE 12 x 36 x .625 SHT | |
| 10002356 | - | Cobalt | COBALT 37% | 1 1/6 | DIA | 37% COBALT STEEL DIA 1.170 BAR PER MMPA 0100-90 SPEC - HOT ROLLED | |
| 10002357 | - | CRES | 416 | 3/8 x 5/8 | L x W | TYPE 416 COND. T ASTM A582 3/8" x 5/8" | |
| 10002358 | - | CRES | 17-4 PH | .5000/.5005 | DIA | CRES AMS 5643 COND. H1075 | |
| 10002359 | - | CRES | 316L | 6" x 2 1/2" | DIA x L | CRES ASTM A276 TYPE 316L COND A SLUG 6" DIA x 2 1/2" L (%Cr + %Mo/%Ni + %C + %N) = 1.7% MIN RATIO | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------------|--|-----------|--|-------|
| 10002360 | - | CRES | 316L | 4 1/2" x 1 3/8" | DIA x L | CRES ASTM A276 TYPE 316L COND A SLUG 4 1/2" DIA x 1 3/8" L (%Cr + %Mo/%Ni + %C + %N) = 1.7% MIN RATIO | |
| 10002361 | - | CRES | 316L | 5" x 3" | DIA x L | COND. A CRES ASTM A276, CHEMICAL COMPOSITION OF MATERIAL SHALL MEET THE FOLLOWING EQUATION AND EXCEED THE MINIMUM RATION VALUE OF 1.7% (Cr) EG=Cr + Mo + 0.7 Nb + 3 Ti (Ni) EG= Ni + 35 C / 20 N | |
| 10002362 | - | CRES | 316L | 3 1/2" x 3/4" | DIA x L | CRES ASTM A276 TYPE 316L COND A SLUG 3 1/2" DIA x 3/4" L (%Cr + %Mo/%Ni + %C + %N) = 1.7% MIN RATIO | |
| 10002363 | - | CRES | 410 | .312 + .005 x .250 x .500 +.050/-0.000 | W x T x L | AMS 5613 CRES 26-33 HRC TYPE 410 .312 + .005 x .250 x .500 +.050/-0.000 SLUGS (WxTxL) | |
| 10002364 | - | CRES | 17-4 PH | 1 7/16 | DIA | AMS 5643 17-4 COND H1025 DIA 1 7/16 BARSTOCK | |
| 10002365 | - | CRES | 420 | .250 | DIA | CRES ASTM-A-582 TYPE 420 F COND A DIA .250 GROUND BARSTOCK | |
| 10002366 | D | CRES | 17-4 PH | 1/4" x 1.0" | T x W | 17-4PH CONDITION H 1150 IAW AMS 5643 | 89920 |
| 10002367 | A | GEE | LAMINATED PLASTIC | .020 +.005/-0.005 X 1.00 +.025/- .025 | T X W | LAMINATED PLASTIC MIL-I-24768/27-S-3 | 70210 |
| 10002368 | A | Aluminum | 6061 | 2.25 X 3.5 X 6.25 SLUG | T x W x L | AL 6061 T651 IAW QQ-A-225/8 OR QQ-A-250/11 | 70567 |
| 10002369 | A | Aluminum | 6061 | .875 X 3.5 X 6.25 SLUG | T x W x L | AL 6061 T651 IAW QQ-A-250/11 | 70567 |
| 10002370 | - | GEE | LAMINATED PLASTIC | 3/4 | DIA | LAMINATED PLASTIC M24768/2 (BARSTOCK) | |
| 10002371 | - | CRES | 303 | 5.750" X 1.250" | DIA x L | 303 COND A ASTM-A-582 | |
| 10002372 | A | CRES | 316L | 5.500" x 1.500" | DIA x L | 316L COND A ASTM-A-276 | 80156 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-----------|----------------------------------|---------|--|------|
| 10002373 | - | CRES | 416 | STRIP 1.000 X .010+.001/-.001 | W X T | CRES I.A.W. ASTM A582 COND. A | |
| 10002374 | - | CRES | 304L | 1 7/8 | DIA | CRES ASTM A276 (TRACEABILITY REQ) | |
| 10002375 | - | CRES | 410 | 1 3/4 | DIA | CRES AMS-QQ-S-763 (TRACEABILITY REQ) | |
| 10002376 | - | Plastic | PLASTIC | 1-1/2" X 1' | DIA x L | PLASTIC ROD PEEK IAW MIL-P-46182 TYPE 2 CLASS 3 (REF.CUST.P/N 63403810) | |
| 10002377 | - | Aluminum | 7075 | 3-1/4" | DIA | ALUM 7075-T7351 IAW AMS-QQ-A-225/9 OR ASTM B211 | |
| 10002378 | - | Copper | BERYLLIUM | .018 -.005/+.005 | DIA | BERYLLIUM COPPER WIRE 3/4H TO FULL H IAM ASTM B197/B197M | |
| 10002379 | - | Aluminum | 6061 | .750"+.010/-.010 X 9.500/9.60 | DIA | ALUM 6061 AMS QQ-A-225/8 TEMPER T6 | |
| 10002380 | - | CRES | 316 | 10.0" X .750 | DIA x L | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002381 | - | CRES | 316 | 1.750" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002382 | - | CRES | 316 | 2.500" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002383 | - | CRES | 316 | 4.00" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002384 | - | CRES | 316 | .250" +.000/-.001 | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002385 | - | CRES | 316 | .375" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002386 | - | CRES | 316 | 3.000" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002387 | - | CRES | 316 | .500" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002388 | - | CRES | 316 | 1.125" | DIA | TYPE 316 COND A IAW ASTM-A-276 (UN'S 31600) | |
| 10002389 | - | CRES | 316 | 1.000" | DIA | COND. A, PER ASTM A276/A276M | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------------|--|-------------------|---|-------|
| 10002390 | - | CRES | 410 | .010 +.001/-0.001 X 1.125 | T X W | STRIP STOCK CRES TYPE 410 ASTM A240 | |
| 10002391 | - | Aluminum | 6061 | 2.00 X 4.00 X 2.750 | L X W X T SLUG | ALUMINUM 6061 T6 IAW QQ-A-225/8 OR QQ-A-250/11 | |
| 10002392 | - | Aluminum | 6061 | 2.50 X 3.50 X 5.500 | L X W X T SLUG | ALUMINUM 6061 T6 IAW QQ-A-225/8 OR QQ-A-250/11 | |
| 10002393 | - | Aluminum | 6061 | 3.00 X 3.50 X 1.00 | L X W X T SLUG | ALUMINUM 6061 T6 IAW QQ-A-225/8 OR QQ-A-250/11 | |
| 10002394 | - | Aluminum | 6061 | 3.750 X 3.250 X 1.00 | L X W X T SLUG | ALUMINUM 6061 T6 I.A.W. QQ-A-250/11 TEMPER 6 | |
| 10002395 | A | Misc | TEFLON | .500" | Dia. | TEFLON IAW ASTM D-1710, TYPE I, GRADE 1, CLASS A | 72822 |
| 10002396 | - | CRES | NICKEL IRON 49 | .099+.001/-0.001 | DIA. | CARPENTER 49 IAW Y202A014-101 MUST HAVE 63 FINISH | |
| 10002397 | - | Aluminum | 2017 | 4.00" | DIA. | ALUMINUM 2017 T4 I.A.W. AMS-QQ-A-225 | |
| 10002398 | - | Aluminum | 2024 | 1-1/8" | DIA | AMS QQ-A-225/6 ANNEALED COND. "0" | |
| 10002399 | A | Plastic | PLASTIC | T=.040 L=12.00 W=12.00 | N/A | POLYCARBONATE BELL P/N 299-947-044 BELL APPROVED SOURCE ONLY | 71806 |
| 10002400 | - | Aluminum | 6061 | 5/8 X 1-1/2 | T X W | AMS QQ-A-225/8 COND T6 BAR | |
| 10002401 | - | Aluminum | 6061 | 3/8 X 2 X 2 | T X W X L | ASTM-B221 TEMPER T651 SLUGS | |
| 10002402 | - | Aluminum | 6061 | 0.500 +.010/- .010 x .083 +.010/-0.010 | OD X WALL | WW-T-700-6 ALUM 6061 T6 TUBE | |
| 10002403 | - | Aluminum | 6061 | 1/32"± 1/64" X 48" X 144" | T x W x L | AMS-QQ-A-250/11 ALUM 6061 T6 SHEET STOCK CUT IN 3" WIDE STRIPS BY VENDOR | |
| 10002404 | - | Aluminum | 2024 | 1/32"± 1/64" X 48" X 144" | T x W x L | AMS-QQ-A-250/4 ALUM 2024 T3 SHEET STOCK CUT IN 3" WIDE STRIPS BY VENDOR | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|---------------|------------------------------|-----------|---|-------|
| 10002405 | - | Aluminum | 5052 | 1/32"± 1/64" X 48" X 144" | T x W x L | AMS-QQ-A-250/8 ALUM 5052 TYPE-0 SHEET STOCK CUT IN 3" WIDE STRIPS BY VENDOR | |
| 10002406 | - | Aluminum | 1100 | 1/32"± 1/64" X 48" X 144" | T x W x L | AMS-QQ-A-250/1 ALUM 1100 TYPE-0 SHEET STOCK CUT IN 3" WIDE STRIPS BY VENDOR | |
| 10002407 | - | Aluminum | 7075 | 1/32"± 1/64" X 48" X 144" | T x W x L | AMS-QQ-A-250/12 ALUM 7075 T6 SHEET STOCK CUT IN 3" WIDE STRIPS BY VENDOR | |
| 10002408 | - | Aluminum | 7075 | 1/16"± 1/64" X 4" X 36" | T x W x L | AMS-QQ-A-250/12 ALUM 7075 T6 SHEET STOCK | |
| 10002409 | - | Nylon | NYLON L-P-410 | 3.000" | DIA. | NYLON L-P-410 | |
| 10002410 | - | CRES | 13-8 MO | 3/8" | DIA. | I.A.W. AMS 5629 COND. H1050 | |
| 10002411 | - | CRES | 13-8 MO | 7/16" | DIA. | I.A.W. AMS 5629 COND. H1050 | |
| 10002412 | A | Aluminum | 6061 | 1/4" | DIA. | "I.A.W.AMS-QQ-A-225/8 OR ASTM B211 TEMPER T6" | 75614 |
| 10002413 | A | Aluminum | 6061 | 2.000 ± .005 | SQ. | I.A.W. AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | 72266 |
| 10002414 | B | Aluminum | 6061 | 4.0" X 14.690" +/- .032 | DIA. X L | I.A.W. AMS-QQ-A-225/8 OR ASTM B211 TEMPER T651 | 74818 |
| 10002415 | - | CRES | 304 | 2.500" | DIA. | CRES MIL-5-5059 304 COND.A CONFIGURATION CONTROL-TRACEABILITY REQUIRED | |
| 10002416 | - | Aluminum | 6061 | 2-1/2" x 4" x 8" | T x W x L | ALUMINUM 6061 PLATE PER AMS-Q-A-250111 OR ASTM B209 TEMPER T651 | |
| 10002417 | A | CRES | 13-8 MO | 7/16" | DIA | CAPERENTER PH 13-8 MO IAW AMS 5629 COND. H1100 | 72266 |
| 10002418 | A | Plastic | PLASTIC | .040" X 24" X 48" | T x W x L | POLYCARBONATE BELL P/N 299-947-044 BELL APPROVED SOURCE ONLY | 72121 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|--|--------------|--|-------|
| 10002419 | - | CRES | 17-4 | .3900/.3905 | DIA. | CRES AMS 5643 COND. H1075 (17-4 PH) | |
| 10002420 | - | CRES | 416 | .062+.002/- .003 X 1.750" X 1.750" | T x W x L | ASTM A582/A582M TYPE 416 COND. H | |
| 10002421 | - | CRES | 15-5 PH | 5/8" | DIA. | SAE AMS 5659 COND. H1075 | |
| 10002422 | - | Misc | INCONEL | 5" X 3" SLUG | DIA X L | INCONEL AMS 5662 OR AMS 5663 | |
| 10002423 | - | Brass | BRASS | .032" X 1" X 36" | T x W x L | BRASS, C2600, HALF HARD | |
| 10002424 | - | CRES | 15-5 PH | 1.250" X8.850/8.900" | DIA x L | 15-5 PH I.A.W. AMS 5659 H1025 | |
| 10002425 | - | Aluminum | 1100 | 1-1/2" | DIA. | AL 1100 I.A.W. AMS-QQ-A-225/1 OR ASTM B211 TEMPER 0 | |
| 10002426 | - | CRES | 416 | 5.000" X .750" | DIA x L | ASTM A582 TYPE 416 COND H | |
| 10002427 | - | CRES | 416 | 4.250" X .500 | DIA x L | ASTM A582 TYPE 416 COND H | |
| 10002428 | - | CRES | 416 | 4.000" | DIA | ASTM A582/A582M TYPE 416 COND. H | |
| 10002429 | - | CRES | 304L | 1.0" X 1.0" | T X W | CRES 304L IAW ASTM-A240 | |
| 10002430 | - | CRES | 17-4 PH | 2-1/2" | DIA | 17-4 PH AMS 5643 H1075 CONDITION A | |
| 10002431 | A | Steel | 1018 | 1.750" X .125" | OD X WALL | STEEL ASTM A513 GRADE 1026 | 73653 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|--------------|---------------------|-----------|---|-------|
| 10002432 | - | Nickel Iron | HYMU-80 | .015" X 1.50" | T X W | HYMU-80 STRIP STOCK | |
| 10002433 | - | Aluminum | 7075 | 1.5" X 3.5" X 4.00" | SLUG | AL7075 IAW SAE-AMS-QQ-A-225/9 TEMPER T7351 | |
| 10002434 | - | CRES | 17-4 PH | 3/8" X 3/4" | T X W | CRES AMS 5643 COND. H1075 (17-4 PH) | |
| 10002435 | - | Steel | 4140 | 1" | DIA. | SAE AMS 6349 (4140 NORMALIZED) | |
| 10002436 | - | Steel | 4140 | 1/2" | DIA. | SAE AMS 6349 (4140 NORMALIZED) | |
| 10002437 | - | Steel | 4140 | 1.250" | DIA. | SAE AMS 6349 (4140 NORMALIZED) | |
| 10002438 | - | GRAPHITE | TRA-1 CARBON | 0.0625" | DIA. | K130A053-T101 DETAIL 2 SUGGESTED SOURCE: POCO GRAPHITE | |
| 10002439 | - | Aluminum | 6061 | 1"X2" | TXW | 6061 AL TEMPER T651 AMS-QQ-A-250/11 | |
| 10002440 | - | Aluminum | 6061 | 5" X 5" X 9" | T X W X L | 6061 A1 TEMPER T651 AMS-QQ-A-250/11 | |
| 10002441 | C | Bronze | BRONZE | 3/8" | DIA | OIL IMPREGNATED SINTERED BRONZE IAW SAE AMS4805 OR ASTM B438 DESIGNATION CODE CT-1000-K26 | 90307 |
| 10002442 | A | Sintered | Iron-Copper | 1/2" | DIA. | RAW MATERIAL ONLY PER ASTM B439 GRADE B | 75755 |
| 10002443 | - | Brass | Brass | .010 X 2" | T X W | STRIP BRASS HALF-HARD TEMPER IAW ASTM-B36/B36M AMS-4507 | |
| 10002444 | - | CRES | 416 | 6" X 3/4" | D X L | ASTM A582 416 COND A | |
| 10002445 | - | Cres | 303 | 5-1/4" x 1-1/8" | D X L | ASTM A582 303 COND A OR 303 SE | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|-------------|------------------------------------|-------------------|---|-------|
| 10002446 | C | CRES | 321 | .186 +.001 X .010 +/- .001 | O.D. X WALL | TYPE 321 IAW MIL-T-8808 | 75736 |
| 10002447 | - | Aluminum | 6061 | 7" X 9" | DIA. X L | AMS-QQ-A-225/8 6061-T6 7"DIA. X 9"LONG SLUG | |
| 10002448 | A | Laminate | PLASTIC | 1" | Dia. | M24768/2-R-1.00 PER MIL-I-24768/2 | 76021 |
| 10002449 | B | Copper | COPPER | 3.250" | DIA. | ASTM B152/B152M TYPE ETP OR ASTM B187/B187M, TEMPER H04 | 87779 |
| 10002450 | - | Misc | INCONEL 718 | 1" | DIA. | SAE AMS 5662 OR SAE AMS 5663 | |
| 10002451 | - | WIRE | NICKEL-IRON | .0060 +/- .0005 X .010 +/- .001 | T x W | MIL-N-14411 COMP-3 | |
| 10002452 | - | Aluminum | 6061 | DIA 7.250 X 9 | DIA. L | AMS-QQ-A-225/8 COND. T6 | |
| 10002453 | - | Aluminum | 6061 | DIA. 7.250 X 2.250 | DIA. L | AMS-QQ-A-225/8 COND. T6 | |
| 10002454 | - | Steel | 9310 | 1/4" | DIA. | SAE-AMS-6265 | |
| 10002455 | - | Steel | 9310 | 1/8" | DIA. | SAE-AMS-6265 | |
| 10002456 | - | Steel | 9310 | 3/8" | DIA. | SAE-AMS-6265 | |
| 10002457 | - | Misc | TITANIUM | 3.750 X 2.250X .250 | O.D X I.D X WT | ASTM B265 HYDROGEN CONTENT LIMIT .006 % MAX, OXYGEN CONTENT LIMIT .15% MAX | |
| 10002458 | - | Aluminum | 1100 | 1 1/2" | OD | 11" LONG ALUMINUM AMS-QQ-A-225/8 | |
| 10002459 | - | Brass | BRASS | 1/8 X 1/4 | W x T | ASTM B36 TEMPER 1/2 H | |
| 10002460 | - | CRES | 416 | 3.75 | DIA. | COND. A SE FREE PER ASTM-A582 | |
| 10002461 | A | Plastic | PLASTIC | 1.50" | DIA | POLYCARBONATE ROD IAW ASTM-D3935-02 "PC0110G20A33230" | 80181 |
| 10002462 | - | Plastic | PLASTIC | 3.50" | DIA | POLYCARBONATE ROD IAW ASTM-D3935-02 "PC0150B24740" | |
| 10002463 | - | CRES | 316 | 8.00 X .750 | O.D x L | COND. A PER ASTM-A-276 | |
| 10002464 | - | Plastic | PLASTIC | 6.00" | DIA. | POLYCARBONATE ROD IAW ASTM-D3935-02 "PC0150B34740" | |
| 10002465 | - | Misc | TITANIUM | 3.75 | DIA. | 6AL-4V PER MIL-T-9047 2 FT LONG | |
| 10002466 | A | Aluminum | 6061 | 2 1/4 x 2 1/4 | Square | ASTM B221, T6511 | 88771 |
| 10002467 | - | | | | | DO NOT USE THIS NUMBER | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|------------------------------------|----------------|--|---|
| 10002468 | - | Nickel Iron | | | | DO NOT USE THIS NUMBER | |
| 10002469 | A | CRES | 17-4 PH | 1/2" | DIA | SAE AMS5643 HEAT TREATED TO COND. H1150 IAW SAE AMS2759/3 | NOC-83034 RN 5R342-1 & -1 7/23/2012 |
| 10002470 | A | CRES | 304 | 5/32" | DIA | AMS-QQ-S-763 COND A | NOC-83759 |
| 10002471 | A | Nickel Iron | NICKEL IRON 49 | 3 1/2" x 4' MAX | DIA X L | ASTM A 753, ALLOY TYPE 2 | NOC-81203 |
| 10002472 | A | Nickel Iron | NICKEL IRON 49 | 4" X 1' MAX | DIA X L | ASTM A 753, ALLOY TYPE 2 | NOC-81203 |
| 10002473 | A | Nickel Iron | NICKEL IRON 49 | 1 3/8" | DIA | ASTM A 753, ALLOY TYPE 2 | NOC-81203 |
| 10002474 | A | Nickel Iron | NICKEL IRON 49 | 1" | DIA | ASTM A 753, ALLOY TYPE 2 | NOC-81203 |
| 10002475 | A | Misc | DELTRIN | 1 1/4 | DIA | DELTRIN 511P OR 500 | NOC-83616 |
| 10002476 | - | Aluminum | 6061 | 3 5/8 | DIA | ASTM B221 COND. T6 | |
| 10002477 | - | CRES | 416 | 7/8 | DIA | CARPENTER 416 BQ-ANNEALED | |
| 10002478 | - | CRES | 304L | 1" | DIA | AMS-QQ-S-763 | |
| 10002479 | A | Aluminum | 6061 | 3.750 x 1.00 +.062/-0.000 | W x T | SAE-AMS-4027 T6 OR T651 | |
| 10002480 | - | Aluminum | 6061 | 3.750 X 3.250 X 1.00 +.025/-000 | LXWXT | SAE-AMS-4027 COND. T-6 | |
| 10002481 | - | Aluminum | 6061 | .250 +/--.002 X .035 +/--.002 | O.D. X WALL | SAE AMS-QQ-A-200/8, SAE AMS 4082, SAE AMS 4083, SAE AMS-WW-T-700/6 COND. T-6 | |
| 10002482 | - | Aluminum | 6061 | 2" X 3/4" | W X T | ASTM B 221 6061-T6511 | 83647 |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------|----------------------|-----------|---|------|
| 10002483 | - | Aluminum | 2024 | 3/4 X 1.5 X 4.5 | T X W X L | TEMPERATURE AGED FROM 2024-T351 TO 2024-T851 IAW SAE AMS2770 (MADE FROM 10001428) | |
| 10002484 | - | Aluminum | 2024 | 3.250 X 1.625 | D X L | TEMPERATURE AGED FROM 2024-T351 TO 2024-T851 IAW SAE AMS2770 (MADE FROM 10001380) | |
| 10002485 | - | CRES | 301 or 302 | .002/.004 x .500 MIN | T X W | SAE AMS5519 OR SAW AMS5906 FULL HARD | |
| 10002486 | - | Aluminum | 2024 | 3/4" x 1.250" x 6.5" | T x W x L | TEMPERATURE AGED FROM 2024-T351 TO 2024-T851 IAW SAE AMS2770 (MADE FROM 10001906) | |
| 10002487 | - | Aluminum | 6061 | 3.125 | D | SAE AMS 4117 T6 OR SAE AMS-QQ-A-200/8 T6, T6510 OR T6511 | |
| 10002488 | - | Bronze | BRONZE | 1.375 | DIA | DRY SINTERED BRONZE PER SAE AMS 4805 NOT OIL IMPREGNATED | |
| 10002489 | - | CRES | 15-5 PH | 0.25 | DIA | SAE AMS 5659 COND H1025 | |
| 10002490 | - | CRES | 15-5 PH | 1.5 | DIA | SAE AMS5659 COND. H1025 | |
| 10002491 | - | Aluminum | 7075 | 2.75 | DIA | AL7075-T73, OR T7351 IAW SAE AMS 4124 | |
| 10002492 | - | CRES | 13-8 MO | 1 3/8 | DIA | PER AMS 5629 (PH13-8MO) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1050 | |
| 10002493 | - | CRES | 13-8 MO | 1" | DIA | PER AMS 5629 (PH13-8MO) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1050 | |
| 10002494 | - | CRES | 17-4 PH | 3/8" | DIA | PER AMS 5643 (17-4PH) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |
| 10002495 | - | CRES | 13-8 MO | 2 3/8" | DIA | PER AMS 5629 (PH13-8MO) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1050 | |
| 10002496 | - | CRES | 17-4 PH | 3/4" | DIA | PER AMS 5643 (17-4PH) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |
| 10002497 | - | CRES | 17-4 PH | 5/8 | DIA | PER AMS 5643 (17-4PH) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |
| 10002498 | - | CRES | 17-4 PH | 1/2" | DIA | PER AMS 5643 (17-4PH) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|----------|---|----------------|---|-------|
| 10002499 | A | CRES | 17-4 PH | 1/4 | DIA | PER AMS 5643 (17-4PH) THRU HARDEN IAW SAE AMS2759/3 TO COND. H1075 | 85030 |
| 10002500 | - | CRES | 17-4 PH | 1 1/2" | DIA | PER AMS 5643 (17-4PH) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |
| 10002501 | - | CRES | 15-5 PH | 7/8 X 1.00 | T X W | PER AMS 5659 (15-5PH) COND. H1150 | |
| 10002502 | - | CRES | 15-5 PH | 5/8 X 1.00 | T X W | PER AMS 5659 (15-5PH) COND. H1150 | |
| 10002503 | - | Aluminum | 6061 | 2.75 | DIA | SAE AMS 4027 or SAE AMS 4115 COND. T651 | |
| 10002504 | - | CRES | 17-4 PH | 7/8 X 1.00 | T X W | PER SAE AMS5643 THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |
| 10002505 | - | CRES | 17-4 PH | 5/8 X 1.00 | T X W | PER SAE AMS5643 THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1075 | |
| 10002506 | A | Aluminum | 6061 | 1/4 X 1/2 ALTERNATE 1/4 X 3/4 | T X W | IAW SAE AMS4027 T651 OR T6511 OR ASTM B221 OR SAE AMS-QQ-A-200/8 | 85610 |
| 10002507 | - | | | | | | |
| 10002508 | - | Aluminum | 7075 | 2" X 4" | T X W | AL ALLOY 7075-T73 OR T731 PER SAE AMS4078 OR SAE AMS4124 | |
| 10002510 | - | CRES | 13-8 MO | 3/8" | DIA | PER AMS 5629 (PH13-8MO) THRU HARDEN IAW SAE AMS 2759/3 TO COND. H1050 | |
| 10002511 | - | Titanium | 6AL-4V | .025 +/- .003 THICK X .875 +/- .01 WIDE | T X W | TITANIUM ALLOY 6AL-4V (TYPE AB-1) IAW Y117A035 (NJ P/N R13740-901) | |
| 10002512 | - | Bronze | BRONZE | 0.375 | DIA | DRY SINTERED BRONZE PER SAE AMS 4805 NOT OIL IMPREGNATED | |
| 10002513 | - | Aluminum | 6061 | 1.25 O.D. X .125 WALL | O.D. X WALL | ASTM B221 OR AMS-QQ-A-200/8 | |
| 10002514 | - | Titanium | 6AL-4V | 9.0 X 1.3 | D X L | TITANIUM BAR IAW AMS 6931 6AL-4V | |
| 10002515 | | | | | | | |
| 10002516 | - | Aluminum | 6061 | 3.625" | DIA | SAE AMS-QQ-A-225/8 T651 | |
| 10002517 | - | Misc | INCONEL | 1.5" | DIA | INCONEL 718 IAW SAE AMS 5662 | |
| 10002518 | - | Misc | INCONEL | 2" | DIA | INCONEL 718 IAW SAE AMS 5662 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|-------------|----------------|-------------|--------|--|-------|
| 10002519 | - | CRES | 15-5PH | .5" | DIA | IAW SAE AMS 5659, HEAT TREAT TO CONDITION H1025 IAW SAE AMS 2759/3, HARDNESS 34-42 HRC | |
| 10002520 | - | CRES | 15-5PH | 1.250" | DIA | IAW SAE AMS 5659, HEAT TREAT TO CONDITION H1025 IAW SAE AMS 2759/3, HARDNESS 34-42 HRC | |
| 10002521 | - | Nickel Iron | NICKEL IRON 49 | 1/2" | DIA | ASTM A753 ALLOY TYPE 2 (Y202A014-101) MOOG APPROVED SUPPLIER REQUIRED | |
| 10002522 | - | CRES | 303 | .3100/.3097 | DIA | ASTM AA582/A582M COND. A MOOG APPROVED SUPPLIER ONLY | |
| 10002523 | - | CRES | 416 | 1 3/16" | DIA | ASTM A582/A582M COND. A MOOG APPROVED SUPPLIER REQUIRED | |
| 10002524 | A | Aluminum | 2024-T351 | 5.50 | DIA | IAW SAE- AMS-QQ-A-225/6 MOOG APPROVED SUPPLIER REQUIRED | 86906 |
| 10002525 | A | Aluminum | 2024-T351 | 2.00 | SQ | IAW SAE- AMS-QQ-A-225/6 MOOG APPROVED SUPPLIER ONLY | 86907 |
| 10002526 | - | CRES | 455 | 0.50 | DIA | CUSTOM 455 STEEL PER AMS 5617, HEAT TREATED TO H1000 PER AMS 2759/3, 44 HRC MIN. | |
| 10002527 | - | CRES | 431 | 1.875 | DIA | PER SAE AMS5628 | |
| 10002528 | - | CRES | 431 | 3.5 | DIA | PER SAE AMS5628 | |
| 10002529 | - | Misc | TEFLON | 2.75 | DIA | PER ASTM D1710 GRADE 1, CLASS A | |
| 10002530 | - | Nickel Iron | NICKEL IRON | 2 1/2 | DIA | ASTM A753 TYPE 2 GRADE 2 OR MIL-N-14411 COMP 3 | |
| 10002531 | - | Nickel Iron | NICKEL IRON | 3.00 | DIA | ASTM A753 TYPE 2 GRADE 2 OR MIL-N-14411 COMP 3 | |
| 10002532 | - | Aluminum | 1100 | 1.5 | DIA | PER ASTM B221 TEMPER F | |
| 10002533 | - | CRES | PH 13-8 Mo | 1.875 | DIA | AMS 5629 TY 1, H1025 SOLUTION AND AGED PER BPS4140 BELL CERTIFIED SOURCE ONLY | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|------------|---------------------------|-----------------|--|------|
| 10002534 | - | CRES | 15-5PH | 1.625 | DIA | IAW SAE AMS 5659, HEAT TREAT TO CONDITION H1025 IAW SAE AMS 2759/3, HARDNESS 34-42 HRC | |
| 10002535 | - | CRES | 304L | 4.00" DIA X 4.00" LONG | EA | SAE AMS-QQ-S-763 COND A | |
| 10002536 | - | CRES | 304L | 2.625 | DIA | SAE AMS-QQ-S-763 COND. A | |
| 10002537 | - | Aluminum | 6061 | 3.5 | DIA | SAE AMS4117, T-6 OR T651 | |
| 10002538 | - | CRES | 304L | 0.125 | DIA | SAE AMS-QQ-S-763 COND. A BARS TO BE 4' TO 6' LONG | |
| 10002539 | - | Aluminum | 6061 | 0.125 | DIA | SAE AMS4117, T-6 OR T651 BARS TO BE 4' TO 6' LONG | |
| 10002540 | - | CRES | 321 | 0.125 | DIA | SAE AMS-QQ-S-763 COND. A | |
| 10002541 | - | Aluminum | 1100 | 1.187 | DIA | ASTM-B211, H14 OR H18 | |
| 10002542 | - | STEEL | 4330M | 1.500 X 9.400 +/- .050 | D X L (SLUG) | AMS 6411 PRE-HARDENED TO 28/34 HRC MOOG APPROVED SUPPLIER (YARDE METALS) | |
| 10002543 | - | CRES | 304L | 1/4" | DIA | AMS-QQ-S-763 CLASS 304L COND A MOOG APPROVED SUPPLIER REQUIRED | |
| 10002544 | - | CRES | 430FR | 2.625 +.006/- .000 | DIA | ASTM A838 ALLOY 2 | |
| 10002545 | - | CRES | 13-8 MO | 1 | DIA | SAE AMS5629 COND. H1000 | |
| 10002546 | - | CRES | 13-8 MO | 1.5 | DIA | SAE AMS5629 COND. H1000 | |
| 10002547 | - | Aluminum | 7075 | .75 x 1.5 | T X W | AL 7075-T73511 PER SAE AMS4617 | |
| 10002548 | - | Aluminum | 7075 | .625 x 2.0 | T X W | AL 7075-T73 SHEET OR T7351 PLATE PER SAE AMS 4078 | |
| 10002549 | - | CRES | 17-4PH | 2.125 | DIA | SAE AMS5643 COND. H1025 | |
| 10002550 | - | CRES | 17-4PH | 0.375 | DIA | SAE AMS5643 COND. H1025 | |
| 10002551 | - | STEEL | M-50 | 0.375 | DIA | M-50 BEARING STEEL PER SAE AMS6491 (VIM-VAR) | |
| 10002552 | - | STEEL | AERMET 100 | 0.375 | DIA | AERMET 100 PER SAE AMS6532 AGED AT 900° F | |
| 10002553 | - | CRES | 440C | 5/8 X 1-1/4 | T X W | SAE AMS5618 OR SAE AMS5630 | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|----------|--------------|--------------------------------------|--------|---|-------|
| 10002554 | - | Bronze | BRONZE | 1.375 | DIA | CT-1000-K26 PER ASTM B438 OIL IMPREGNATED BRONZE | |
| 10002555 | - | CRES | 13-8PH | 2 | DIA | 13-8PH COND. H1000 PER SAE AMS5629 | |
| 10002556 | - | CRES | 17-4PH | 5/8 X 1.250 | T X W | SAE AMS5643 COND. H1075 | |
| 10002557 | - | Aluminum | 6061 | 2 7/16 | DIA | SAE AMS4117 6061-T6 OR T651 | |
| 10002558 | - | Aluminum | 6061 | 1 9/16 | DIA | SAE AMS4117 6061-T6 OR T651 | |
| 10002559 | - | Misc | DELRIN | 1 1/4 | DIA | DELRIN 150 ASTM-D-4181 POM 111 | |
| 10002560 | - | CRES | 416 | 3/16 SQ | SQ | ASTM A582/A582M COND. A CUT INTO 1' LENGTHS | |
| 10002561 | - | Titanium | 6AL-4V | 4.250" x 2.375" (+.050/-0 length) | D X L | TITANIUM BAR IAW AMS 6931 6AL-4V | |
| 10002562 | - | Titanium | 6AL-4V | 3.250" x 2.250" (+.050/-0 length) | D X L | TITANIUM BAR IAW AMS 6931 6AL-4V | |
| 10002563 | - | Bronze | BRONZE, ALUM | 0.375 | DIA | SAE AMS4640 | |
| 10002564 | - | CRES | 316 | 0.750 | DIA | TYPE 316 COND B IAW ASTM A276/A276M | |
| 10002565 | B | P-6 | P-6 | 1.125 X .010 | LB | P-6 Material, Cold Finish, Unannealed IAW Y117A016-101 | 91032 |
| 10002566 | - | Aluminum | 6061 | 3.250 | DIA | AL 6061 T6 per ASTM B211 or ASTM B221 | |
| 10002567 | - | CRES | 440C | 2 | DIA | AMS5618 OR AMS5630 | |
| 10002568 | - | Nylon | Nylon 6/6 | 1.25 | DIA | PA66 (NYLON 6-6) PER ASTM D6779 PA0171 | |
| 10002569 | - | BRONZE | BRONZE, ALUM | 0.500" | DIA | ALUMINUM BRONZE NICKEL C95500 ASTM-B505 | |
| 10002570 | | | | | | | |
| 10002571 | | | | | | 1 | |
| 10002572 | | | | | | | |
| 10002573 | | | | | | | |
| 10002574 | | | | | | | |
| 10002575 | | | | | | | |
| 10002576 | | | | | | | |
| 10002577 | | | | | | | |
| 10002578 | | | | | | | |
| 10002579 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002580 | | | | | | | |
| 10002581 | | | | | | | |
| 10002582 | | | | | | | |
| 10002583 | | | | | | | |
| 10002584 | | | | | | | |
| 10002585 | | | | | | | |
| 10002586 | | | | | | | |
| 10002587 | | | | | | | |
| 10002588 | | | | | | | |
| 10002589 | | | | | | | |
| 10002590 | | | | | | | |
| 10002591 | | | | | | | |
| 10002592 | | | | | | | |
| 10002593 | | | | | | | |
| 10002594 | | | | | | | |
| 10002595 | | | | | | | |
| 10002596 | | | | | | | |
| 10002597 | | | | | | | |
| 10002598 | | | | | | | |
| 10002599 | | | | | | | |
| 10002600 | | | | | | | |
| 10002601 | | | | | | | |
| 10002602 | | | | | | | |
| 10002603 | | | | | | | |
| 10002604 | | | | | | | |
| 10002605 | | | | | | | |
| 10002606 | | | | | | | |
| 10002607 | | | | | | | |
| 10002608 | | | | | | | |
| 10002609 | | | | | | | |
| 10002610 | | | | | | | |
| 10002611 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002612 | | | | | | | |
| 10002613 | | | | | | | |
| 10002614 | | | | | | | |
| 10002615 | | | | | | | |
| 10002616 | | | | | | | |
| 10002617 | | | | | | | |
| 10002618 | | | | | | | |
| 10002619 | | | | | | | |
| 10002620 | | | | | | | |
| 10002621 | | | | | | | |
| 10002622 | | | | | | | |
| 10002623 | | | | | | | |
| 10002624 | | | | | | | |
| 10002625 | | | | | | | |
| 10002626 | | | | | | | |
| 10002627 | | | | | | | |
| 10002628 | | | | | | | |
| 10002629 | | | | | | | |
| 10002630 | | | | | | | |
| 10002631 | | | | | | | |
| 10002632 | | | | | | | |
| 10002633 | | | | | | | |
| 10002634 | | | | | | | |
| 10002635 | | | | | | | |
| 10002636 | | | | | | | |
| 10002637 | | | | | | | |
| 10002638 | | | | | | | |
| 10002639 | | | | | | | |
| 10002640 | | | | | | | |
| 10002641 | | | | | | | |
| 10002642 | | | | | | | |
| 10002643 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002644 | | | | | | | |
| 10002645 | | | | | | | |
| 10002646 | | | | | | | |
| 10002647 | | | | | | | |
| 10002648 | | | | | | | |
| 10002649 | | | | | | | |
| 10002650 | | | | | | | |
| 10002651 | | | | | | | |
| 10002652 | | | | | | | |
| 10002653 | | | | | | | |
| 10002654 | | | | | | | |
| 10002655 | | | | | | | |
| 10002656 | | | | | | | |
| 10002657 | | | | | | | |
| 10002658 | | | | | | | |
| 10002659 | | | | | | | |
| 10002660 | | | | | | | |
| 10002661 | | | | | | | |
| 10002662 | | | | | | | |
| 10002663 | | | | | | | |
| 10002664 | | | | | | | |
| 10002665 | | | | | | | |
| 10002666 | | | | | | | |
| 10002667 | | | | | | | |
| 10002668 | | | | | | | |
| 10002669 | | | | | | | |
| 10002670 | | | | | | | |
| 10002671 | | | | | | | |
| 10002672 | | | | | | | |
| 10002673 | | | | | | | |
| 10002674 | | | | | | | |
| 10002675 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002676 | | | | | | | |
| 10002677 | | | | | | | |
| 10002678 | | | | | | | |
| 10002679 | | | | | | | |
| 10002680 | | | | | | | |
| 10002681 | | | | | | | |
| 10002682 | | | | | | | |
| 10002683 | | | | | | | |
| 10002684 | | | | | | | |
| 10002685 | | | | | | | |
| 10002686 | | | | | | | |
| 10002687 | | | | | | | |
| 10002688 | | | | | | | |
| 10002689 | | | | | | | |
| 10002690 | | | | | | | |
| 10002691 | | | | | | | |
| 10002692 | | | | | | | |
| 10002693 | | | | | | | |
| 10002694 | | | | | | | |
| 10002695 | | | | | | | |
| 10002696 | | | | | | | |
| 10002697 | | | | | | | |
| 10002698 | | | | | | | |
| 10002699 | | | | | | | |
| 10002700 | | | | | | | |
| 10002701 | | | | | | | |
| 10002702 | | | | | | | |
| 10002703 | | | | | | | |
| 10002704 | | | | | | | |
| 10002705 | | | | | | | |
| 10002706 | | | | | | | |
| 10002707 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002708 | | | | | | | |
| 10002709 | | | | | | | |
| 10002710 | | | | | | | |
| 10002711 | | | | | | | |
| 10002712 | | | | | | | |
| 10002713 | | | | | | | |
| 10002714 | | | | | | | |
| 10002715 | | | | | | | |
| 10002716 | | | | | | | |
| 10002717 | | | | | | | |
| 10002718 | | | | | | | |
| 10002719 | | | | | | | |
| 10002720 | | | | | | | |
| 10002721 | | | | | | | |
| 10002722 | | | | | | | |
| 10002723 | | | | | | | |
| 10002724 | | | | | | | |
| 10002725 | | | | | | | |
| 10002726 | | | | | | | |
| 10002727 | | | | | | | |
| 10002728 | | | | | | | |
| 10002729 | | | | | | | |
| 10002730 | | | | | | | |
| 10002731 | | | | | | | |
| 10002732 | | | | | | | |
| 10002733 | | | | | | | |
| 10002734 | | | | | | | |
| 10002735 | | | | | | | |
| 10002736 | | | | | | | |
| 10002737 | | | | | | | |
| 10002738 | | | | | | | |
| 10002739 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002740 | | | | | | | |
| 10002741 | | | | | | | |
| 10002742 | | | | | | | |
| 10002743 | | | | | | | |
| 10002744 | | | | | | | |
| 10002745 | | | | | | | |
| 10002746 | | | | | | | |
| 10002747 | | | | | | | |
| 10002748 | | | | | | | |
| 10002749 | | | | | | | |
| 10002750 | | | | | | | |
| 10002751 | | | | | | | |
| 10002752 | | | | | | | |
| 10002753 | | | | | | | |
| 10002754 | | | | | | | |
| 10002755 | | | | | | | |
| 10002756 | | | | | | | |
| 10002757 | | | | | | | |
| 10002758 | | | | | | | |
| 10002759 | | | | | | | |
| 10002760 | | | | | | | |
| 10002761 | | | | | | | |
| 10002762 | | | | | | | |
| 10002763 | | | | | | | |
| 10002764 | | | | | | | |
| 10002765 | | | | | | | |
| 10002766 | | | | | | | |
| 10002767 | | | | | | | |
| 10002768 | | | | | | | |
| 10002769 | | | | | | | |
| 10002770 | | | | | | | |
| 10002771 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002772 | | | | | | | |
| 10002773 | | | | | | | |
| 10002774 | | | | | | | |
| 10002775 | | | | | | | |
| 10002776 | | | | | | | |
| 10002777 | | | | | | | |
| 10002778 | | | | | | | |
| 10002779 | | | | | | | |
| 10002780 | | | | | | | |
| 10002781 | | | | | | | |
| 10002782 | | | | | | | |
| 10002783 | | | | | | | |
| 10002784 | | | | | | | |
| 10002785 | | | | | | | |
| 10002786 | | | | | | | |
| 10002787 | | | | | | | |
| 10002788 | | | | | | | |
| 10002789 | | | | | | | |
| 10002790 | | | | | | | |
| 10002791 | | | | | | | |
| 10002792 | | | | | | | |
| 10002793 | | | | | | | |
| 10002794 | | | | | | | |
| 10002795 | | | | | | | |
| 10002796 | | | | | | | |
| 10002797 | | | | | | | |
| 10002798 | | | | | | | |
| 10002799 | | | | | | | |
| 10002800 | | | | | | | |
| 10002801 | | | | | | | |
| 10002802 | | | | | | | |
| 10002803 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002804 | | | | | | | |
| 10002805 | | | | | | | |
| 10002806 | | | | | | | |
| 10002807 | | | | | | | |
| 10002808 | | | | | | | |
| 10002809 | | | | | | | |
| 10002810 | | | | | | | |
| 10002811 | | | | | | | |
| 10002812 | | | | | | | |
| 10002813 | | | | | | | |
| 10002814 | | | | | | | |
| 10002815 | | | | | | | |
| 10002816 | | | | | | | |
| 10002817 | | | | | | | |
| 10002818 | | | | | | | |
| 10002819 | | | | | | | |
| 10002820 | | | | | | | |
| 10002821 | | | | | | | |
| 10002822 | | | | | | | |
| 10002823 | | | | | | | |
| 10002824 | | | | | | | |
| 10002825 | | | | | | | |
| 10002826 | | | | | | | |
| 10002827 | | | | | | | |
| 10002828 | | | | | | | |
| 10002829 | | | | | | | |
| 10002830 | | | | | | | |
| 10002831 | | | | | | | |
| 10002832 | | | | | | | |
| 10002833 | | | | | | | |
| 10002834 | | | | | | | |
| 10002835 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002836 | | | | | | | |
| 10002837 | | | | | | | |
| 10002838 | | | | | | | |
| 10002839 | | | | | | | |
| 10002840 | | | | | | | |
| 10002841 | | | | | | | |
| 10002842 | | | | | | | |
| 10002843 | | | | | | | |
| 10002844 | | | | | | | |
| 10002845 | | | | | | | |
| 10002846 | | | | | | | |
| 10002847 | | | | | | | |
| 10002848 | | | | | | | |
| 10002849 | | | | | | | |
| 10002850 | | | | | | | |
| 10002851 | | | | | | | |
| 10002852 | | | | | | | |
| 10002853 | | | | | | | |
| 10002854 | | | | | | | |
| 10002855 | | | | | | | |
| 10002856 | | | | | | | |
| 10002857 | | | | | | | |
| 10002858 | | | | | | | |
| 10002859 | | | | | | | |
| 10002860 | | | | | | | |
| 10002861 | | | | | | | |
| 10002862 | | | | | | | |
| 10002863 | | | | | | | |
| 10002864 | | | | | | | |
| 10002865 | | | | | | | |
| 10002866 | | | | | | | |
| 10002867 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002868 | | | | | | | |
| 10002869 | | | | | | | |
| 10002870 | | | | | | | |
| 10002871 | | | | | | | |
| 10002872 | | | | | | | |
| 10002873 | | | | | | | |
| 10002874 | | | | | | | |
| 10002875 | | | | | | | |
| 10002876 | | | | | | | |
| 10002877 | | | | | | | |
| 10002878 | | | | | | | |
| 10002879 | | | | | | | |
| 10002880 | | | | | | | |
| 10002881 | | | | | | | |
| 10002882 | | | | | | | |
| 10002883 | | | | | | | |
| 10002884 | | | | | | | |
| 10002885 | | | | | | | |
| 10002886 | | | | | | | |
| 10002887 | | | | | | | |
| 10002888 | | | | | | | |
| 10002889 | | | | | | | |
| 10002890 | | | | | | | |
| 10002891 | | | | | | | |
| 10002892 | | | | | | | |
| 10002893 | | | | | | | |
| 10002894 | | | | | | | |
| 10002895 | | | | | | | |
| 10002896 | | | | | | | |
| 10002897 | | | | | | | |
| 10002898 | | | | | | | |
| 10002899 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002900 | | | | | | | |
| 10002901 | | | | | | | |
| 10002902 | | | | | | | |
| 10002903 | | | | | | | |
| 10002904 | | | | | | | |
| 10002905 | | | | | | | |
| 10002906 | | | | | | | |
| 10002907 | | | | | | | |
| 10002908 | | | | | | | |
| 10002909 | | | | | | | |
| 10002910 | | | | | | | |
| 10002911 | | | | | | | |
| 10002912 | | | | | | | |
| 10002913 | | | | | | | |
| 10002914 | | | | | | | |
| 10002915 | | | | | | | |
| 10002916 | | | | | | | |
| 10002917 | | | | | | | |
| 10002918 | | | | | | | |
| 10002919 | | | | | | | |
| 10002920 | | | | | | | |
| 10002921 | | | | | | | |
| 10002922 | | | | | | | |
| 10002923 | | | | | | | |
| 10002924 | | | | | | | |
| 10002925 | | | | | | | |
| 10002926 | | | | | | | |
| 10002927 | | | | | | | |
| 10002928 | | | | | | | |
| 10002929 | | | | | | | |
| 10002930 | | | | | | | |
| 10002931 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002932 | | | | | | | |
| 10002933 | | | | | | | |
| 10002934 | | | | | | | |
| 10002935 | | | | | | | |
| 10002936 | | | | | | | |
| 10002937 | | | | | | | |
| 10002938 | | | | | | | |
| 10002939 | | | | | | | |
| 10002940 | | | | | | | |
| 10002941 | | | | | | | |
| 10002942 | | | | | | | |
| 10002943 | | | | | | | |
| 10002944 | | | | | | | |
| 10002945 | | | | | | | |
| 10002946 | | | | | | | |
| 10002947 | | | | | | | |
| 10002948 | | | | | | | |
| 10002949 | | | | | | | |
| 10002950 | | | | | | | |
| 10002951 | | | | | | | |
| 10002952 | | | | | | | |
| 10002953 | | | | | | | |
| 10002954 | | | | | | | |
| 10002955 | | | | | | | |
| 10002956 | | | | | | | |
| 10002957 | | | | | | | |
| 10002958 | | | | | | | |
| 10002959 | | | | | | | |
| 10002960 | | | | | | | |
| 10002961 | | | | | | | |
| 10002962 | | | | | | | |
| 10002963 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002964 | | | | | | | |
| 10002965 | | | | | | | |
| 10002966 | | | | | | | |
| 10002967 | | | | | | | |
| 10002968 | | | | | | | |
| 10002969 | | | | | | | |
| 10002970 | | | | | | | |
| 10002971 | | | | | | | |
| 10002972 | | | | | | | |
| 10002973 | | | | | | | |
| 10002974 | | | | | | | |
| 10002975 | | | | | | | |
| 10002976 | | | | | | | |
| 10002977 | | | | | | | |
| 10002978 | | | | | | | |
| 10002979 | | | | | | | |
| 10002980 | | | | | | | |
| 10002981 | | | | | | | |
| 10002982 | | | | | | | |
| 10002983 | | | | | | | |
| 10002984 | | | | | | | |
| 10002985 | | | | | | | |
| 10002986 | | | | | | | |
| 10002987 | | | | | | | |
| 10002988 | | | | | | | |
| 10002989 | | | | | | | |
| 10002990 | | | | | | | |
| 10002991 | | | | | | | |
| 10002992 | | | | | | | |
| 10002993 | | | | | | | |
| 10002994 | | | | | | | |
| 10002995 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10002996 | | | | | | | |
| 10002997 | | | | | | | |
| 10002998 | | | | | | | |
| 10002999 | | | | | | | |
| 10003000 | | | | | | | |
| 10003001 | | | | | | | |
| 10003002 | | | | | | | |
| 10003003 | | | | | | | |
| 10003004 | | | | | | | |
| 10003005 | | | | | | | |
| 10003006 | | | | | | | |
| 10003007 | | | | | | | |
| 10003008 | | | | | | | |
| 10003009 | | | | | | | |
| 10003010 | | | | | | | |
| 10003011 | | | | | | | |
| 10003012 | | | | | | | |
| 10003013 | | | | | | | |
| 10003014 | | | | | | | |
| 10003015 | | | | | | | |
| 10003016 | | | | | | | |
| 10003017 | | | | | | | |
| 10003018 | | | | | | | |
| 10003019 | | | | | | | |
| 10003020 | | | | | | | |
| 10003021 | | | | | | | |
| 10003022 | | | | | | | |
| 10003023 | | | | | | | |
| 10003024 | | | | | | | |
| 10003025 | | | | | | | |
| 10003026 | | | | | | | |
| 10003027 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003028 | | | | | | | |
| 10003029 | | | | | | | |
| 10003030 | | | | | | | |
| 10003031 | | | | | | | |
| 10003032 | | | | | | | |
| 10003033 | | | | | | | |
| 10003034 | | | | | | | |
| 10003035 | | | | | | | |
| 10003036 | | | | | | | |
| 10003037 | | | | | | | |
| 10003038 | | | | | | | |
| 10003039 | | | | | | | |
| 10003040 | | | | | | | |
| 10003041 | | | | | | | |
| 10003042 | | | | | | | |
| 10003043 | | | | | | | |
| 10003044 | | | | | | | |
| 10003045 | | | | | | | |
| 10003046 | | | | | | | |
| 10003047 | | | | | | | |
| 10003048 | | | | | | | |
| 10003049 | | | | | | | |
| 10003050 | | | | | | | |
| 10003051 | | | | | | | |
| 10003052 | | | | | | | |
| 10003053 | | | | | | | |
| 10003054 | | | | | | | |
| 10003055 | | | | | | | |
| 10003056 | | | | | | | |
| 10003057 | | | | | | | |
| 10003058 | | | | | | | |
| 10003059 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003060 | | | | | | | |
| 10003061 | | | | | | | |
| 10003062 | | | | | | | |
| 10003063 | | | | | | | |
| 10003064 | | | | | | | |
| 10003065 | | | | | | | |
| 10003066 | | | | | | | |
| 10003067 | | | | | | | |
| 10003068 | | | | | | | |
| 10003069 | | | | | | | |
| 10003070 | | | | | | | |
| 10003071 | | | | | | | |
| 10003072 | | | | | | | |
| 10003073 | | | | | | | |
| 10003074 | | | | | | | |
| 10003075 | | | | | | | |
| 10003076 | | | | | | | |
| 10003077 | | | | | | | |
| 10003078 | | | | | | | |
| 10003079 | | | | | | | |
| 10003080 | | | | | | | |
| 10003081 | | | | | | | |
| 10003082 | | | | | | | |
| 10003083 | | | | | | | |
| 10003084 | | | | | | | |
| 10003085 | | | | | | | |
| 10003086 | | | | | | | |
| 10003087 | | | | | | | |
| 10003088 | | | | | | | |
| 10003089 | | | | | | | |
| 10003090 | | | | | | | |
| 10003091 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003092 | | | | | | | |
| 10003093 | | | | | | | |
| 10003094 | | | | | | | |
| 10003095 | | | | | | | |
| 10003096 | | | | | | | |
| 10003097 | | | | | | | |
| 10003098 | | | | | | | |
| 10003099 | | | | | | | |
| 10003100 | | | | | | | |
| 10003101 | | | | | | | |
| 10003102 | | | | | | | |
| 10003103 | | | | | | | |
| 10003104 | | | | | | | |
| 10003105 | | | | | | | |
| 10003106 | | | | | | | |
| 10003107 | | | | | | | |
| 10003108 | | | | | | | |
| 10003109 | | | | | | | |
| 10003110 | | | | | | | |
| 10003111 | | | | | | | |
| 10003112 | | | | | | | |
| 10003113 | | | | | | | |
| 10003114 | | | | | | | |
| 10003115 | | | | | | | |
| 10003116 | | | | | | | |
| 10003117 | | | | | | | |
| 10003118 | | | | | | | |
| 10003119 | | | | | | | |
| 10003120 | | | | | | | |
| 10003121 | | | | | | | |
| 10003122 | | | | | | | |
| 10003123 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003124 | | | | | | | |
| 10003125 | | | | | | | |
| 10003126 | | | | | | | |
| 10003127 | | | | | | | |
| 10003128 | | | | | | | |
| 10003129 | | | | | | | |
| 10003130 | | | | | | | |
| 10003131 | | | | | | | |
| 10003132 | | | | | | | |
| 10003133 | | | | | | | |
| 10003134 | | | | | | | |
| 10003135 | | | | | | | |
| 10003136 | | | | | | | |
| 10003137 | | | | | | | |
| 10003138 | | | | | | | |
| 10003139 | | | | | | | |
| 10003140 | | | | | | | |
| 10003141 | | | | | | | |
| 10003142 | | | | | | | |
| 10003143 | | | | | | | |
| 10003144 | | | | | | | |
| 10003145 | | | | | | | |
| 10003146 | | | | | | | |
| 10003147 | | | | | | | |
| 10003148 | | | | | | | |
| 10003149 | | | | | | | |
| 10003150 | | | | | | | |
| 10003151 | | | | | | | |
| 10003152 | | | | | | | |
| 10003153 | | | | | | | |
| 10003154 | | | | | | | |
| 10003155 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003156 | | | | | | | |
| 10003157 | | | | | | | |
| 10003158 | | | | | | | |
| 10003159 | | | | | | | |
| 10003160 | | | | | | | |
| 10003161 | | | | | | | |
| 10003162 | | | | | | | |
| 10003163 | | | | | | | |
| 10003164 | | | | | | | |
| 10003165 | | | | | | | |
| 10003166 | | | | | | | |
| 10003167 | | | | | | | |
| 10003168 | | | | | | | |
| 10003169 | | | | | | | |
| 10003170 | | | | | | | |
| 10003171 | | | | | | | |
| 10003172 | | | | | | | |
| 10003173 | | | | | | | |
| 10003174 | | | | | | | |
| 10003175 | | | | | | | |
| 10003176 | | | | | | | |
| 10003177 | | | | | | | |
| 10003178 | | | | | | | |
| 10003179 | | | | | | | |
| 10003180 | | | | | | | |
| 10003181 | | | | | | | |
| 10003182 | | | | | | | |
| 10003183 | | | | | | | |
| 10003184 | | | | | | | |
| 10003185 | | | | | | | |
| 10003186 | | | | | | | |
| 10003187 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003188 | | | | | | | |
| 10003189 | | | | | | | |
| 10003190 | | | | | | | |
| 10003191 | | | | | | | |
| 10003192 | | | | | | | |
| 10003193 | | | | | | | |
| 10003194 | | | | | | | |
| 10003195 | | | | | | | |
| 10003196 | | | | | | | |
| 10003197 | | | | | | | |
| 10003198 | | | | | | | |
| 10003199 | | | | | | | |
| 10003200 | | | | | | | |
| 10003201 | | | | | | | |
| 10003202 | | | | | | | |
| 10003203 | | | | | | | |
| 10003204 | | | | | | | |
| 10003205 | | | | | | | |
| 10003206 | | | | | | | |
| 10003207 | | | | | | | |
| 10003208 | | | | | | | |
| 10003209 | | | | | | | |
| 10003210 | | | | | | | |
| 10003211 | | | | | | | |
| 10003212 | | | | | | | |
| 10003213 | | | | | | | |
| 10003214 | | | | | | | |
| 10003215 | | | | | | | |
| 10003216 | | | | | | | |
| 10003217 | | | | | | | |
| 10003218 | | | | | | | |
| 10003219 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003220 | | | | | | | |
| 10003221 | | | | | | | |
| 10003222 | | | | | | | |
| 10003223 | | | | | | | |
| 10003224 | | | | | | | |
| 10003225 | | | | | | | |
| 10003226 | | | | | | | |
| 10003227 | | | | | | | |
| 10003228 | | | | | | | |
| 10003229 | | | | | | | |
| 10003230 | | | | | | | |
| 10003231 | | | | | | | |
| 10003232 | | | | | | | |
| 10003233 | | | | | | | |
| 10003234 | | | | | | | |
| 10003235 | | | | | | | |
| 10003236 | | | | | | | |
| 10003237 | | | | | | | |
| 10003238 | | | | | | | |
| 10003239 | | | | | | | |
| 10003240 | | | | | | | |
| 10003241 | | | | | | | |
| 10003242 | | | | | | | |
| 10003243 | | | | | | | |
| 10003244 | | | | | | | |
| 10003245 | | | | | | | |
| 10003246 | | | | | | | |
| 10003247 | | | | | | | |
| 10003248 | | | | | | | |
| 10003249 | | | | | | | |
| 10003250 | | | | | | | |
| 10003251 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003252 | | | | | | | |
| 10003253 | | | | | | | |
| 10003254 | | | | | | | |
| 10003255 | | | | | | | |
| 10003256 | | | | | | | |
| 10003257 | | | | | | | |
| 10003258 | | | | | | | |
| 10003259 | | | | | | | |
| 10003260 | | | | | | | |
| 10003261 | | | | | | | |
| 10003262 | | | | | | | |
| 10003263 | | | | | | | |
| 10003264 | | | | | | | |
| 10003265 | | | | | | | |
| 10003266 | | | | | | | |
| 10003267 | | | | | | | |
| 10003268 | | | | | | | |
| 10003269 | | | | | | | |
| 10003270 | | | | | | | |
| 10003271 | | | | | | | |
| 10003272 | | | | | | | |
| 10003273 | | | | | | | |
| 10003274 | | | | | | | |
| 10003275 | | | | | | | |
| 10003276 | | | | | | | |
| 10003277 | | | | | | | |
| 10003278 | | | | | | | |
| 10003279 | | | | | | | |
| 10003280 | | | | | | | |
| 10003281 | | | | | | | |
| 10003282 | | | | | | | |
| 10003283 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003284 | | | | | | | |
| 10003285 | | | | | | | |
| 10003286 | | | | | | | |
| 10003287 | | | | | | | |
| 10003288 | | | | | | | |
| 10003289 | | | | | | | |
| 10003290 | | | | | | | |
| 10003291 | | | | | | | |
| 10003292 | | | | | | | |
| 10003293 | | | | | | | |
| 10003294 | | | | | | | |
| 10003295 | | | | | | | |
| 10003296 | | | | | | | |
| 10003297 | | | | | | | |
| 10003298 | | | | | | | |
| 10003299 | | | | | | | |
| 10003300 | | | | | | | |
| 10003301 | | | | | | | |
| 10003302 | | | | | | | |
| 10003303 | | | | | | | |
| 10003304 | | | | | | | |
| 10003305 | | | | | | | |
| 10003306 | | | | | | | |
| 10003307 | | | | | | | |
| 10003308 | | | | | | | |
| 10003309 | | | | | | | |
| 10003310 | | | | | | | |
| 10003311 | | | | | | | |
| 10003312 | | | | | | | |
| 10003313 | | | | | | | |
| 10003314 | | | | | | | |
| 10003315 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003316 | | | | | | | |
| 10003317 | | | | | | | |
| 10003318 | | | | | | | |
| 10003319 | | | | | | | |
| 10003320 | | | | | | | |
| 10003321 | | | | | | | |
| 10003322 | | | | | | | |
| 10003323 | | | | | | | |
| 10003324 | | | | | | | |
| 10003325 | | | | | | | |
| 10003326 | | | | | | | |
| 10003327 | | | | | | | |
| 10003328 | | | | | | | |
| 10003329 | | | | | | | |
| 10003330 | | | | | | | |
| 10003331 | | | | | | | |
| 10003332 | | | | | | | |
| 10003333 | | | | | | | |
| 10003334 | | | | | | | |
| 10003335 | | | | | | | |
| 10003336 | | | | | | | |
| 10003337 | | | | | | | |
| 10003338 | | | | | | | |
| 10003339 | | | | | | | |
| 10003340 | | | | | | | |
| 10003341 | | | | | | | |
| 10003342 | | | | | | | |
| 10003343 | | | | | | | |
| 10003344 | | | | | | | |
| 10003345 | | | | | | | |
| 10003346 | | | | | | | |
| 10003347 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003348 | | | | | | | |
| 10003349 | | | | | | | |
| 10003350 | | | | | | | |
| 10003351 | | | | | | | |
| 10003352 | | | | | | | |
| 10003353 | | | | | | | |
| 10003354 | | | | | | | |
| 10003355 | | | | | | | |
| 10003356 | | | | | | | |
| 10003357 | | | | | | | |
| 10003358 | | | | | | | |
| 10003359 | | | | | | | |
| 10003360 | | | | | | | |
| 10003361 | | | | | | | |
| 10003362 | | | | | | | |
| 10003363 | | | | | | | |
| 10003364 | | | | | | | |
| 10003365 | | | | | | | |
| 10003366 | | | | | | | |
| 10003367 | | | | | | | |
| 10003368 | | | | | | | |
| 10003369 | | | | | | | |
| 10003370 | | | | | | | |
| 10003371 | | | | | | | |
| 10003372 | | | | | | | |
| 10003373 | | | | | | | |
| 10003374 | | | | | | | |
| 10003375 | | | | | | | |
| 10003376 | | | | | | | |
| 10003377 | | | | | | | |
| 10003378 | | | | | | | |
| 10003379 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003380 | | | | | | | |
| 10003381 | | | | | | | |
| 10003382 | | | | | | | |
| 10003383 | | | | | | | |
| 10003384 | | | | | | | |
| 10003385 | | | | | | | |
| 10003386 | | | | | | | |
| 10003387 | | | | | | | |
| 10003388 | | | | | | | |
| 10003389 | | | | | | | |
| 10003390 | | | | | | | |
| 10003391 | | | | | | | |
| 10003392 | | | | | | | |
| 10003393 | | | | | | | |
| 10003394 | | | | | | | |
| 10003395 | | | | | | | |
| 10003396 | | | | | | | |
| 10003397 | | | | | | | |
| 10003398 | | | | | | | |
| 10003399 | | | | | | | |
| 10003400 | | | | | | | |
| 10003401 | | | | | | | |
| 10003402 | | | | | | | |
| 10003403 | | | | | | | |
| 10003404 | | | | | | | |
| 10003405 | | | | | | | |
| 10003406 | | | | | | | |
| 10003407 | | | | | | | |
| 10003408 | | | | | | | |
| 10003409 | | | | | | | |
| 10003410 | | | | | | | |
| 10003411 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003412 | | | | | | | |
| 10003413 | | | | | | | |
| 10003414 | | | | | | | |
| 10003415 | | | | | | | |
| 10003416 | | | | | | | |
| 10003417 | | | | | | | |
| 10003418 | | | | | | | |
| 10003419 | | | | | | | |
| 10003420 | | | | | | | |
| 10003421 | | | | | | | |
| 10003422 | | | | | | | |
| 10003423 | | | | | | | |
| 10003424 | | | | | | | |
| 10003425 | | | | | | | |
| 10003426 | | | | | | | |
| 10003427 | | | | | | | |
| 10003428 | | | | | | | |
| 10003429 | | | | | | | |
| 10003430 | | | | | | | |
| 10003431 | | | | | | | |
| 10003432 | | | | | | | |
| 10003433 | | | | | | | |
| 10003434 | | | | | | | |
| 10003435 | | | | | | | |
| 10003436 | | | | | | | |
| 10003437 | | | | | | | |
| 10003438 | | | | | | | |
| 10003439 | | | | | | | |
| 10003440 | | | | | | | |
| 10003441 | | | | | | | |
| 10003442 | | | | | | | |
| 10003443 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003444 | | | | | | | |
| 10003445 | | | | | | | |
| 10003446 | | | | | | | |
| 10003447 | | | | | | | |
| 10003448 | | | | | | | |
| 10003449 | | | | | | | |
| 10003450 | | | | | | | |
| 10003451 | | | | | | | |
| 10003452 | | | | | | | |
| 10003453 | | | | | | | |
| 10003454 | | | | | | | |
| 10003455 | | | | | | | |
| 10003456 | | | | | | | |
| 10003457 | | | | | | | |
| 10003458 | | | | | | | |
| 10003459 | | | | | | | |
| 10003460 | | | | | | | |
| 10003461 | | | | | | | |
| 10003462 | | | | | | | |
| 10003463 | | | | | | | |
| 10003464 | | | | | | | |
| 10003465 | | | | | | | |
| 10003466 | | | | | | | |
| 10003467 | | | | | | | |
| 10003468 | | | | | | | |
| 10003469 | | | | | | | |
| 10003470 | | | | | | | |
| 10003471 | | | | | | | |
| 10003472 | | | | | | | |
| 10003473 | | | | | | | |
| 10003474 | | | | | | | |
| 10003475 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003476 | | | | | | | |
| 10003477 | | | | | | | |
| 10003478 | | | | | | | |
| 10003479 | | | | | | | |
| 10003480 | | | | | | | |
| 10003481 | | | | | | | |
| 10003482 | | | | | | | |
| 10003483 | | | | | | | |
| 10003484 | | | | | | | |
| 10003485 | | | | | | | |
| 10003486 | | | | | | | |
| 10003487 | | | | | | | |
| 10003488 | | | | | | | |
| 10003489 | | | | | | | |
| 10003490 | | | | | | | |
| 10003491 | | | | | | | |
| 10003492 | | | | | | | |
| 10003493 | | | | | | | |
| 10003494 | | | | | | | |
| 10003495 | | | | | | | |
| 10003496 | | | | | | | |
| 10003497 | | | | | | | |
| 10003498 | | | | | | | |
| 10003499 | | | | | | | |
| 10003500 | | | | | | | |
| 10003501 | | | | | | | |
| 10003502 | | | | | | | |
| 10003503 | | | | | | | |
| 10003504 | | | | | | | |
| 10003505 | | | | | | | |
| 10003506 | | | | | | | |
| 10003507 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003508 | | | | | | | |
| 10003509 | | | | | | | |
| 10003510 | | | | | | | |
| 10003511 | | | | | | | |
| 10003512 | | | | | | | |
| 10003513 | | | | | | | |
| 10003514 | | | | | | | |
| 10003515 | | | | | | | |
| 10003516 | | | | | | | |
| 10003517 | | | | | | | |
| 10003518 | | | | | | | |
| 10003519 | | | | | | | |
| 10003520 | | | | | | | |
| 10003521 | | | | | | | |
| 10003522 | | | | | | | |
| 10003523 | | | | | | | |
| 10003524 | | | | | | | |
| 10003525 | | | | | | | |
| 10003526 | | | | | | | |
| 10003527 | | | | | | | |
| 10003528 | | | | | | | |
| 10003529 | | | | | | | |
| 10003530 | | | | | | | |
| 10003531 | | | | | | | |
| 10003532 | | | | | | | |
| 10003533 | | | | | | | |
| 10003534 | | | | | | | |
| 10003535 | | | | | | | |
| 10003536 | | | | | | | |
| 10003537 | | | | | | | |
| 10003538 | | | | | | | |
| 10003539 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003540 | | | | | | | |
| 10003541 | | | | | | | |
| 10003542 | | | | | | | |
| 10003543 | | | | | | | |
| 10003544 | | | | | | | |
| 10003545 | | | | | | | |
| 10003546 | | | | | | | |
| 10003547 | | | | | | | |
| 10003548 | | | | | | | |
| 10003549 | | | | | | | |
| 10003550 | | | | | | | |
| 10003551 | | | | | | | |
| 10003552 | | | | | | | |
| 10003553 | | | | | | | |
| 10003554 | | | | | | | |
| 10003555 | | | | | | | |
| 10003556 | | | | | | | |
| 10003557 | | | | | | | |
| 10003558 | | | | | | | |
| 10003559 | | | | | | | |
| 10003560 | | | | | | | |
| 10003561 | | | | | | | |
| 10003562 | | | | | | | |
| 10003563 | | | | | | | |
| 10003564 | | | | | | | |
| 10003565 | | | | | | | |
| 10003566 | | | | | | | |
| 10003567 | | | | | | | |
| 10003568 | | | | | | | |
| 10003569 | | | | | | | |
| 10003570 | | | | | | | |
| 10003571 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003572 | | | | | | | |
| 10003573 | | | | | | | |
| 10003574 | | | | | | | |
| 10003575 | | | | | | | |
| 10003576 | | | | | | | |
| 10003577 | | | | | | | |
| 10003578 | | | | | | | |
| 10003579 | | | | | | | |
| 10003580 | | | | | | | |
| 10003581 | | | | | | | |
| 10003582 | | | | | | | |
| 10003583 | | | | | | | |
| 10003584 | | | | | | | |
| 10003585 | | | | | | | |
| 10003586 | | | | | | | |
| 10003587 | | | | | | | |
| 10003588 | | | | | | | |
| 10003589 | | | | | | | |
| 10003590 | | | | | | | |
| 10003591 | | | | | | | |
| 10003592 | | | | | | | |
| 10003593 | | | | | | | |
| 10003594 | | | | | | | |
| 10003595 | | | | | | | |
| 10003596 | | | | | | | |
| 10003597 | | | | | | | |
| 10003598 | | | | | | | |
| 10003599 | | | | | | | |
| 10003600 | | | | | | | |
| 10003601 | | | | | | | |
| 10003602 | | | | | | | |
| 10003603 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003604 | | | | | | | |
| 10003605 | | | | | | | |
| 10003606 | | | | | | | |
| 10003607 | | | | | | | |
| 10003608 | | | | | | | |
| 10003609 | | | | | | | |
| 10003610 | | | | | | | |
| 10003611 | | | | | | | |
| 10003612 | | | | | | | |
| 10003613 | | | | | | | |
| 10003614 | | | | | | | |
| 10003615 | | | | | | | |
| 10003616 | | | | | | | |
| 10003617 | | | | | | | |
| 10003618 | | | | | | | |
| 10003619 | | | | | | | |
| 10003620 | | | | | | | |
| 10003621 | | | | | | | |
| 10003622 | | | | | | | |
| 10003623 | | | | | | | |
| 10003624 | | | | | | | |
| 10003625 | | | | | | | |
| 10003626 | | | | | | | |
| 10003627 | | | | | | | |
| 10003628 | | | | | | | |
| 10003629 | | | | | | | |
| 10003630 | | | | | | | |
| 10003631 | | | | | | | |
| 10003632 | | | | | | | |
| 10003633 | | | | | | | |
| 10003634 | | | | | | | |
| 10003635 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003636 | | | | | | | |
| 10003637 | | | | | | | |
| 10003638 | | | | | | | |
| 10003639 | | | | | | | |
| 10003640 | | | | | | | |
| 10003641 | | | | | | | |
| 10003642 | | | | | | | |
| 10003643 | | | | | | | |
| 10003644 | | | | | | | |
| 10003645 | | | | | | | |
| 10003646 | | | | | | | |
| 10003647 | | | | | | | |
| 10003648 | | | | | | | |
| 10003649 | | | | | | | |
| 10003650 | | | | | | | |
| 10003651 | | | | | | | |
| 10003652 | | | | | | | |
| 10003653 | | | | | | | |
| 10003654 | | | | | | | |
| 10003655 | | | | | | | |
| 10003656 | | | | | | | |
| 10003657 | | | | | | | |
| 10003658 | | | | | | | |
| 10003659 | | | | | | | |
| 10003660 | | | | | | | |
| 10003661 | | | | | | | |
| 10003662 | | | | | | | |
| 10003663 | | | | | | | |
| 10003664 | | | | | | | |
| 10003665 | | | | | | | |
| 10003666 | | | | | | | |
| 10003667 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003668 | | | | | | | |
| 10003669 | | | | | | | |
| 10003670 | | | | | | | |
| 10003671 | | | | | | | |
| 10003672 | | | | | | | |
| 10003673 | | | | | | | |
| 10003674 | | | | | | | |
| 10003675 | | | | | | | |
| 10003676 | | | | | | | |
| 10003677 | | | | | | | |
| 10003678 | | | | | | | |
| 10003679 | | | | | | | |
| 10003680 | | | | | | | |
| 10003681 | | | | | | | |
| 10003682 | | | | | | | |
| 10003683 | | | | | | | |
| 10003684 | | | | | | | |
| 10003685 | | | | | | | |
| 10003686 | | | | | | | |
| 10003687 | | | | | | | |
| 10003688 | | | | | | | |
| 10003689 | | | | | | | |
| 10003690 | | | | | | | |
| 10003691 | | | | | | | |
| 10003692 | | | | | | | |
| 10003693 | | | | | | | |
| 10003694 | | | | | | | |
| 10003695 | | | | | | | |
| 10003696 | | | | | | | |
| 10003697 | | | | | | | |
| 10003698 | | | | | | | |
| 10003699 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003700 | | | | | | | |
| 10003701 | | | | | | | |
| 10003702 | | | | | | | |
| 10003703 | | | | | | | |
| 10003704 | | | | | | | |
| 10003705 | | | | | | | |
| 10003706 | | | | | | | |
| 10003707 | | | | | | | |
| 10003708 | | | | | | | |
| 10003709 | | | | | | | |
| 10003710 | | | | | | | |
| 10003711 | | | | | | | |
| 10003712 | | | | | | | |
| 10003713 | | | | | | | |
| 10003714 | | | | | | | |
| 10003715 | | | | | | | |
| 10003716 | | | | | | | |
| 10003717 | | | | | | | |
| 10003718 | | | | | | | |
| 10003719 | | | | | | | |
| 10003720 | | | | | | | |
| 10003721 | | | | | | | |
| 10003722 | | | | | | | |
| 10003723 | | | | | | | |
| 10003724 | | | | | | | |
| 10003725 | | | | | | | |
| 10003726 | | | | | | | |
| 10003727 | | | | | | | |
| 10003728 | | | | | | | |
| 10003729 | | | | | | | |
| 10003730 | | | | | | | |
| 10003731 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003732 | | | | | | | |
| 10003733 | | | | | | | |
| 10003734 | | | | | | | |
| 10003735 | | | | | | | |
| 10003736 | | | | | | | |
| 10003737 | | | | | | | |
| 10003738 | | | | | | | |
| 10003739 | | | | | | | |
| 10003740 | | | | | | | |
| 10003741 | | | | | | | |
| 10003742 | | | | | | | |
| 10003743 | | | | | | | |
| 10003744 | | | | | | | |
| 10003745 | | | | | | | |
| 10003746 | | | | | | | |
| 10003747 | | | | | | | |
| 10003748 | | | | | | | |
| 10003749 | | | | | | | |
| 10003750 | | | | | | | |
| 10003751 | | | | | | | |
| 10003752 | | | | | | | |
| 10003753 | | | | | | | |
| 10003754 | | | | | | | |
| 10003755 | | | | | | | |
| 10003756 | | | | | | | |
| 10003757 | | | | | | | |
| 10003758 | | | | | | | |
| 10003759 | | | | | | | |
| 10003760 | | | | | | | |
| 10003761 | | | | | | | |
| 10003762 | | | | | | | |
| 10003763 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003764 | | | | | | | |
| 10003765 | | | | | | | |
| 10003766 | | | | | | | |
| 10003767 | | | | | | | |
| 10003768 | | | | | | | |
| 10003769 | | | | | | | |
| 10003770 | | | | | | | |
| 10003771 | | | | | | | |
| 10003772 | | | | | | | |
| 10003773 | | | | | | | |
| 10003774 | | | | | | | |
| 10003775 | | | | | | | |
| 10003776 | | | | | | | |
| 10003777 | | | | | | | |
| 10003778 | | | | | | | |
| 10003779 | | | | | | | |
| 10003780 | | | | | | | |
| 10003781 | | | | | | | |
| 10003782 | | | | | | | |
| 10003783 | | | | | | | |
| 10003784 | | | | | | | |
| 10003785 | | | | | | | |
| 10003786 | | | | | | | |
| 10003787 | | | | | | | |
| 10003788 | | | | | | | |
| 10003789 | | | | | | | |
| 10003790 | | | | | | | |
| 10003791 | | | | | | | |
| 10003792 | | | | | | | |
| 10003793 | | | | | | | |
| 10003794 | | | | | | | |
| 10003795 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003796 | | | | | | | |
| 10003797 | | | | | | | |
| 10003798 | | | | | | | |
| 10003799 | | | | | | | |
| 10003800 | | | | | | | |
| 10003801 | | | | | | | |
| 10003802 | | | | | | | |
| 10003803 | | | | | | | |
| 10003804 | | | | | | | |
| 10003805 | | | | | | | |
| 10003806 | | | | | | | |
| 10003807 | | | | | | | |
| 10003808 | | | | | | | |
| 10003809 | | | | | | | |
| 10003810 | | | | | | | |
| 10003811 | | | | | | | |
| 10003812 | | | | | | | |
| 10003813 | | | | | | | |
| 10003814 | | | | | | | |
| 10003815 | | | | | | | |
| 10003816 | | | | | | | |
| 10003817 | | | | | | | |
| 10003818 | | | | | | | |
| 10003819 | | | | | | | |
| 10003820 | | | | | | | |
| 10003821 | | | | | | | |
| 10003822 | | | | | | | |
| 10003823 | | | | | | | |
| 10003824 | | | | | | | |
| 10003825 | | | | | | | |
| 10003826 | | | | | | | |
| 10003827 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003828 | | | | | | | |
| 10003829 | | | | | | | |
| 10003830 | | | | | | | |
| 10003831 | | | | | | | |
| 10003832 | | | | | | | |
| 10003833 | | | | | | | |
| 10003834 | | | | | | | |
| 10003835 | | | | | | | |
| 10003836 | | | | | | | |
| 10003837 | | | | | | | |
| 10003838 | | | | | | | |
| 10003839 | | | | | | | |
| 10003840 | | | | | | | |
| 10003841 | | | | | | | |
| 10003842 | | | | | | | |
| 10003843 | | | | | | | |
| 10003844 | | | | | | | |
| 10003845 | | | | | | | |
| 10003846 | | | | | | | |
| 10003847 | | | | | | | |
| 10003848 | | | | | | | |
| 10003849 | | | | | | | |
| 10003850 | | | | | | | |
| 10003851 | | | | | | | |
| 10003852 | | | | | | | |
| 10003853 | | | | | | | |
| 10003854 | | | | | | | |
| 10003855 | | | | | | | |
| 10003856 | | | | | | | |
| 10003857 | | | | | | | |
| 10003858 | | | | | | | |
| 10003859 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003860 | | | | | | | |
| 10003861 | | | | | | | |
| 10003862 | | | | | | | |
| 10003863 | | | | | | | |
| 10003864 | | | | | | | |
| 10003865 | | | | | | | |
| 10003866 | | | | | | | |
| 10003867 | | | | | | | |
| 10003868 | | | | | | | |
| 10003869 | | | | | | | |
| 10003870 | | | | | | | |
| 10003871 | | | | | | | |
| 10003872 | | | | | | | |
| 10003873 | | | | | | | |
| 10003874 | | | | | | | |
| 10003875 | | | | | | | |
| 10003876 | | | | | | | |
| 10003877 | | | | | | | |
| 10003878 | | | | | | | |
| 10003879 | | | | | | | |
| 10003880 | | | | | | | |
| 10003881 | | | | | | | |
| 10003882 | | | | | | | |
| 10003883 | | | | | | | |
| 10003884 | | | | | | | |
| 10003885 | | | | | | | |
| 10003886 | | | | | | | |
| 10003887 | | | | | | | |
| 10003888 | | | | | | | |
| 10003889 | | | | | | | |
| 10003890 | | | | | | | |
| 10003891 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003892 | | | | | | | |
| 10003893 | | | | | | | |
| 10003894 | | | | | | | |
| 10003895 | | | | | | | |
| 10003896 | | | | | | | |
| 10003897 | | | | | | | |
| 10003898 | | | | | | | |
| 10003899 | | | | | | | |
| 10003900 | | | | | | | |
| 10003901 | | | | | | | |
| 10003902 | | | | | | | |
| 10003903 | | | | | | | |
| 10003904 | | | | | | | |
| 10003905 | | | | | | | |
| 10003906 | | | | | | | |
| 10003907 | | | | | | | |
| 10003908 | | | | | | | |
| 10003909 | | | | | | | |
| 10003910 | | | | | | | |
| 10003911 | | | | | | | |
| 10003912 | | | | | | | |
| 10003913 | | | | | | | |
| 10003914 | | | | | | | |
| 10003915 | | | | | | | |
| 10003916 | | | | | | | |
| 10003917 | | | | | | | |
| 10003918 | | | | | | | |
| 10003919 | | | | | | | |
| 10003920 | | | | | | | |
| 10003921 | | | | | | | |
| 10003922 | | | | | | | |
| 10003923 | | | | | | | |

BARSTOCK LOG

| Part Number | Rev. | Type | Material | Size | Config | Description | NOC* |
|-------------|------|------|----------|------|--------|-------------|------|
| 10003924 | | | | | | | |
| 10003925 | | | | | | | |